



```
SSSSSSSS YY YY SSSSSSS LL NN NN MM MM
SSSSSSSS YY YY SSSSSSS LL NN NN MM MM
SS SS YY YY SS SS LL NN NN MMMM MMMM
SS SS YY YY SS SS LL NN NN MMMM MMMM
SS SS YY YY SS SS LL NN NN MM MM
SSSSSS YY YY SSSSS SS LL NN NN MM MM
SSSSSS YY YY SSSSS SS LL NN NN MM MM
SS SS SS LL LL LLLLLLLLLL NN NN MM MM
SSSSSS YY YY SSSSS SSSSSSSSS
```

```
LL LL I I I I I SSSSSSS
LL LL I I I I I SSSSSSS
LL LL I I I I I SS
LL LL I I I I I SS
LL LL I I I I I SS
LL LL I I I I I SSSSS
LL LL I I I I I SSSSS
LL LL I I I I I SS
LL LL I I I I I SS
LL LL I I I I I SS
LL LL I I I I I SSSSS
LL LL I I I I I SSSSS
```

|     |      |              |                             |
|-----|------|--------------|-----------------------------|
| (2) | 511  | DECLARATIONS |                             |
| (3) | 620  | EX\$CRELNT   | - CREATE LOGICAL NAME TABLE |
| (4) | 1206 | EX\$CRELNM   | - CREATE LOGICAL NAME       |
| (5) | 1819 | EX\$DELLNM   | - DELETE LOGICAL NAME       |
| (6) | 2070 | EX\$TRNLNM   | - TRANSLATE LOGICAL NAME    |



```
0000 1      .TITLE SYSLNM - SYSTEM SERVICES TO MANIPULATE LOGICAL NAMES AND TABLES.
0000 2      .IDENT 'V04-000'
0000 3
0000 4
0000 5      *****
0000 6      *
0000 7      *  COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 8      *  DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 9      *  ALL RIGHTS RESERVED.
0000 10     *
0000 11     *  THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 12     *  ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 13     *  INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 14     *  COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 15     *  OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 16     *  TRANSFERRED.
0000 17     *
0000 18     *  THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 19     *  AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 20     *  CORPORATION.
0000 21     *
0000 22     *  DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 23     *  SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 24     *
0000 25     *
0000 26     *****
0000 27
0000 28     TODD M. KATZ 01-APR-83
0000 29
0000 30     SYSTEM SERVICES TO MANIPULATE LOGICAL NAMES
0000 31
0000 32     CREATE LOGICAL NAME TABLES
0000 33     CREATE LOGICAL NAME
0000 34     DELETE LOGICAL NAME
0000 35     TRANSLATE LOGICAL NAME
0000 36
0000 37     MODIFICATION HISTORY:
0000 38
0000 39     V03-027 RAS0327      Ron Schaefer      24-Jul-1984
0000 40     Back out RAS0322 and make the LNMS_LENGTH itemcode
0000 41     be a longword value.
0000 42
0000 43     V03-026 RAS0322      Ron Schaefer      10-Jul-1984
0000 44     Fix $TRNLNM item LNMS_LENGTH to only write a word field.
0000 45
0000 46     V03-025 RAS0312      Ron Schaefer      21-Jun-1984
0000 47     Fix ORB alignment within logical name table.
0000 48
0000 49     V03-024 TMK0014      Todd M. Katz      21-Apr-1984
0000 50     The interface to the internal logical name routine
0000 51     LNMSDELETE_LNMB has been changed. Update $DELLNM, which calls
0000 52     this routine, to reflect this new interface.
0000 53
0000 54     The performance measurement cell used to monitor the rate of
0000 55     logical name translations is currently located within the
0000 56     internal logical name routine LNMSSEARCHLOG. Unfortunately,
0000 57     because of its current placement, any attempts to delete
```



0000 58 : specific logical names will also increment this counter. This  
0000 59 : is because the system service \$DELLNM will call the routine  
0000 60 : LNMSSEARCHLOG in such a situation. Therefore, in order to be  
0000 61 : able to make a more accurate measurement of the overall rate  
0000 62 : of logical name translations, I have decided to move this  
0000 63 : performance measurement cell from its current single location  
0000 64 : to several more appropriate locations. One of these new  
0000 65 : locations is within the system service \$TRNLNM, just before the  
0000 66 : call to LNMSSEARCHLOG.  
0000 67 :

V03-023 TMK0013 Todd M. Katz 29-Mar-1984  
0000 68 : Modify the logical name system services to make use of the  
0000 69 : updated internal protection checking mechanisms. What this  
0000 70 : requires is a modification to SYSSCRELNT so that all shareable  
0000 71 : logical name tables are created with a quad-word aligned Object  
0000 72 : Rights Block in place of a un-aligned CHIP protection template.  
0000 73 :

0000 74 : Restrict all names which appear with a directory table to 31  
0000 75 : characters consisting of the DEC multi-national alphanumeric  
0000 76 : character set plus \$ and -. This restriction applies to both  
0000 77 : logical names and logical name table names. The reason for this  
0000 78 : restriction is that in the future we might want to support  
0000 79 : hierarchial name spaces. If we decide to do so we would have to  
0000 80 : invent and then impose a structure on logical name table names.  
0000 81 : This restriction gives us sufficient leeway (and more  
0000 82 : importantly sufficient available characters) to be able to  
0000 83 : define a hierarchial name space structure in the future.  
0000 84 :

V03-022 TMK0012 Todd M. Katz 07-Mar-1984  
0000 85 : The fixed portion of each and every translation block has been  
0000 86 : increased by a word, LNM\$W\_HASH, in order to potentially hold  
0000 87 : the translation's hash code value. Furthermore, SYSSCRELNT and  
0000 88 : SYSSCRELNM have been modified so that this field within each  
0000 89 : and every translation block is initialized to 0. This hash code  
0000 90 : field will be used in an optimization of logical name table name  
0000 91 : processing. As such, only certain logical names, those that are  
0000 92 : contained within the process or system directory and may be used  
0000 93 : in logical name table processing, need to have the hash code  
0000 94 : fields of each of their translations initialized to their  
0000 95 : equivalence string's hash code value. This initialization  
0000 96 : actually takes place within the routine LNMSINSLOGTAB in the  
0000 97 : module LNMSUB.  
0000 98 :

V03-021 TMK0011 Todd M. Katz 13-Feb-1984  
0000 99 : Add SS\$ NOLOGTAB to the list of errors than can be returned  
0000 100 : by SYSSCRELNT, SYSSCRELNM, and SYSSDELLNM.  
0000 101 :

0000 102 : Fix a bug in \$TRNLNM. At the present time the very first  
0000 103 : longword in the item list is not being probed. Obviously this  
0000 104 : could result in a disastrous kernel mode ACCVIO.  
0000 105 :

0000 106 : Fix up \$TRNLNM's processing of the PARENT item. The most  
0000 107 : important change I have made here, besides a general fixup  
0000 108 : of the code, is to return 0 bytes in the parent item if the LNMB  
0000 109 : being looked at is not for a logical name table. This is because  
0000 110 : logical names, with the exception of logical name tables, do not  
0000 111 : have parents.  
0000 112 :  
0000 113 :  
0000 114 :



0000 115 :  
0000 116 :  
0000 117 :  
0000 118 :  
0000 119 :  
0000 120 :  
0000 121 :  
0000 122 :  
0000 123 :  
0000 124 :  
0000 125 :  
0000 126 :  
0000 127 :  
0000 128 :  
0000 129 :  
0000 130 :  
0000 131 :  
0000 132 :  
0000 133 :  
0000 134 :  
0000 135 :  
0000 136 :  
0000 137 :  
0000 138 :  
0000 139 :  
0000 140 :  
0000 141 :  
0000 142 :  
0000 143 :  
0000 144 :  
0000 145 :  
0000 146 :  
0000 147 :  
0000 148 :  
0000 149 :  
0000 150 :  
0000 151 :  
0000 152 :  
0000 153 :  
0000 154 :  
0000 155 :  
0000 156 :  
0000 157 :  
0000 158 :  
0000 159 :  
0000 160 :  
0000 161 :  
0000 162 :  
0000 163 :  
0000 164 :  
0000 165 :  
0000 166 :  
0000 167 :  
0000 168 :  
0000 169 :  
0000 170 :  
0000 171 :

Optimize the processing of STRNLNM's item list. This is done by having two separate code segments - one to probe and return variable length character string items (TABLE, STRING, PARENT), and the other to probe and return longword length items (LENGTH, ATTRIBUTES, MAX\_INDEX). In addition, since ACMODEs are only a byte, ACMODE items are now being probed and filled in in-line. Also, optimize a few instructions within this system service.

V03-020 TMK0010 Todd M. Katz 29-Dec-1983

Re-write SYSSDELLNM for the case when the name of the logical name table entry to be deleted has been specified. What was being done was incorrect. It allowed the possibility of deleting several logical names from different tables. The correct way to implement this is as follows:

1. Search for the first instance of a logical name table entry in one of the specified logical name tables which possesses the specified access mode.
2. Check to make sure that the caller has write access to the containing logical name table.
3. Delete the logical name table entry and all outer mode aliases within the same logical name table.

The process and system directory logical name tables are now being created with the LNMB\$V NODELETE bit set within their LNMB\$B FLAGS fields to indicate that these tables should never be deleted. Therefore, it is no longer necessary for SYSSCRELNT to set this bit within the appropriate directory table to protect it from being deleted during the insertion of the table entry for the new logical name table, and conversely SYSSCRELNT must never clear this bit within a directory table after the attempt at insertion has been made.

Fix a bug in the creation of logical names without translations by SYSSCRELNM. This used to work, but has broken mysteriously. The problem is that during the first processing of the item list, the number of translations specified by the list and the cumulated size of their translation strings is saved on the stack for use in computing the amount of storage required to be allocated for the new logical name block. These stack associated counters were not being appropriately initialized to zero in the case when no item list (and thus no translations) was present. This resulted in the size of the table name and the address of the table name buffer being popped off the stack and used as the values of these counters. As might be expected this would cause the system service to fail in a variety of interesting ways. Often, since the saved logical name table name descriptor had been removed from the stack but the pointer to the saved descriptor in R9 had not changed, this would lead to a failure to find a logical name table and termination of the system service. Also, since the values used in computing the amount of storage required for the new logical name were random, the value computed could be so large as to cause the storage allocation attempt to fail.



0000 172 :  
0000 173 :  
0000 174 :  
0000 175 :  
0000 176 :  
0000 177 :  
0000 178 :  
0000 179 :  
0000 180 :  
0000 181 :  
0000 182 :  
0000 183 :  
0000 184 :  
0000 185 :  
0000 186 :  
0000 187 :  
0000 188 :  
0000 189 :  
0000 190 :  
0000 191 :  
0000 192 :  
0000 193 :  
0000 194 :  
0000 195 :  
0000 196 :  
0000 197 :  
0000 198 :  
0000 199 :  
0000 200 :  
0000 201 :  
0000 202 :  
0000 203 :  
0000 204 :  
0000 205 :  
0000 206 :  
0000 207 :  
0000 208 :  
0000 209 :  
0000 210 :  
0000 211 :  
0000 212 :  
0000 213 :  
0000 214 :  
0000 215 :  
0000 216 :  
0000 217 :  
0000 218 :  
0000 219 :  
0000 220 :  
0000 221 :  
0000 222 :  
0000 223 :  
0000 224 :  
0000 225 :  
0000 226 :  
0000 227 :  
0000 228 :

V03-019 TMK0009 Todd M. Katz 18-Dec-1983  
Remove all mention of LNMSV\_SYSTEM and LNMSV\_GROUP from  
SYS\$CRELNT. The system table and all group tables will be  
handcrafted, and there will not be a way to create such a  
table by means of the system service interface.

Also, change some PUSHRS into PUSHLS (or MOVQs) and POPRS into  
POPLs (or MOVQs) where appropriate for performance reasons.

V03-018 TMK0008 Todd M. Katz 26-Oct-1983  
Quota checking when logical name tables are being created  
is presently incorrect. Currently, when a logical name  
table is created only one type of quota check is made. That  
check makes sure that the quota holder of the parent logical  
name table has sufficient quota for both the logical name table  
itself and any quota which will be specifically allocated to it.  
Actually, two quota checks should be made. The quota holder of  
the parent logical name table should have sufficient quota for  
the quota that will be specifically allocated to the new table;  
but in addition, the containing table (the system or process  
directory table) must have sufficient quota for the logical  
name table itself. This is consistent with how quota deductions  
are made for logical names, and it is consistent with the  
philosophy that logical name tables are just logical names with  
a special type of translation.

V03-017 TMK0007 Todd M. Katz 26-Sep-1983  
Change the default protection that is assigned to new shareable  
logical name tables to SYSTEM:RWED OWNER:RWED GROUP: WORLD:  
so that by default, the system can access and modify any  
shareable logical name table.

V03-016 TMK0006 Todd M. Katz 16-Sep-1983  
Fix a branch in EXE\$CRELNT. If no attributes were specified,  
this service should branch to check out the table name  
parameter; however, it is branching into the wrong place. This  
results in an inability to create a logical name table if  
attributes are not specified. This fixes the problem.

V03-015 TMK0005 Todd M. Katz 08-Aug-1983  
Make several modifications to each of the logical name system  
services.

#### Changes to EXE\$CRELNT:

1. Change access mode processing. The new logical name table  
may not be created in an access mode inner to that of the  
caller unless the user has SYSNAM privilege and has  
specified an access mode as an optional system service  
argument. A new logical name table may still be created  
with an access mode outer to the mode of the caller, even if  
the caller does not have SYSNAM privilege, if the caller  
explicitly specifies an access mode as an optional system  
service parameter.

2. A new logical name table maybe marked within the table



0000 229 :  
0000 230 :  
0000 231 :  
0000 232 :  
0000 233 :  
0000 234 :  
0000 235 :  
0000 236 :  
0000 237 :  
0000 238 :  
0000 239 :  
0000 240 :  
0000 241 :  
0000 242 :  
0000 243 :  
0000 244 :  
0000 245 :  
0000 246 :  
0000 247 :  
0000 248 :  
0000 249 :  
0000 250 :  
0000 251 :  
0000 252 :  
0000 253 :  
0000 254 :  
0000 255 :  
0000 256 :  
0000 257 :  
0000 258 :  
0000 259 :  
0000 260 :  
0000 261 :  
0000 262 :  
0000 263 :  
0000 264 :  
0000 265 :  
0000 266 :  
0000 267 :  
0000 268 :  
0000 269 :  
0000 270 :  
0000 271 :  
0000 272 :  
0000 273 :  
0000 274 :  
0000 275 :  
0000 276 :  
0000 277 :  
0000 278 :  
0000 279 :  
0000 280 :  
0000 281 :  
0000 282 :  
0000 283 :  
0000 284 :  
0000 285 :

header as either the system table or a group table (but not both) by setting one of the new attribute bits (reserved to DIGITAL) LNMSV\_SYSTEM or LNMSV\_GROUP respectively. The caller must be in executive or kernel mode to do so.

3. It is necessary to have quota access to the parent logical name table in order to be able create a subtable. In addition if the table being creating is shareable, and the caller is specifying a name, then the caller must have write access to the system directory table. Previously, read and write access to the parent logical name table was what was being checked. This is not only insufficient but wrong. I have also moved these access checks so that they are performed immediately after the parent logical name table is located.
4. SYSNAM was formerly required to specify the name of a shareable logical name table and not let the system default name it (ie - insert the name into the system directory table). The meaning of SYSNAM has been restricted to refer only to the access of the system logical name table, LNMSYSTEM\_TABLE, and to the creation and deletion of inner access mode logical names and tables.
5. If no protection mask was specified, then default the protection to 0:RWED.
6. It is never necessary to do any protection checking when process-private logical name tables are involved. Therefore, do not allocate or fill in the CHIP protection structure template when creating a process-private logical name table, and do not perform any protection checking during the creation of such tables.

#### Changes to EXESCRELNM:

1. Change access mode processing. The new logical name may not be created in an access mode inner to that of the caller unless the user has SYSNAM privilege and has specified an access mode as an optional system service argument. A new logical name may still be created with an access mode outer to the mode of the caller, even if the caller does not have SYSNAM privilege, if the caller explicitly specifies an access mode as an optional system service parameter.
2. It is only necessary to have write access to the logical name table in order to be able to insert a logical name within it. Previously, both read and write access was required.
3. In order to be able to insert a logical name into the system directory table a caller must be able to write access the table itself. Previously, the caller could perform such an insertion if they had SYSNAM privilege. The meaning of SYSNAM has been restricted to refer only to the access of the system logical name table, LNMSYSTEM\_TABLE, and to the creation and deletion of inner access mode logical names and

0000 286 :  
0000 287 :  
0000 288 :  
0000 289 :  
0000 290 :  
0000 291 :  
0000 292 :  
0000 293 :  
0000 294 :  
0000 295 :  
0000 296 :  
0000 297 :  
0000 298 :  
0000 299 :  
0000 300 :  
0000 301 :  
0000 302 :  
0000 303 :  
0000 304 :  
0000 305 :  
0000 306 :  
0000 307 :  
0000 308 :  
0000 309 :  
0000 310 :  
0000 311 :  
0000 312 :  
0000 313 :  
0000 314 :  
0000 315 :  
0000 316 :  
0000 317 :  
0000 318 :  
0000 319 :  
0000 320 :  
0000 321 :  
0000 322 :  
0000 323 :  
0000 324 :  
0000 325 :  
0000 326 :  
0000 327 :  
0000 328 :  
0000 329 :  
0000 330 :  
0000 331 :  
0000 332 :  
0000 333 :  
0000 334 :  
0000 335 :  
0000 336 :  
0000 337 :  
0000 338 :  
0000 339 :  
0000 340 :  
0000 341 :  
0000 342 :

tables.

4. It is never necessary to do any protection checking when process-private logical name tables are involved. Therefore, do not perform any protection checking prior to the insertion of new logical names into such tables.

#### Changes to EXE\$DELLNM:

1. Change access mode processing. Logical names or logical name tables in access modes inner to that of the caller may not be deleted unless the user has SYSNAM privilege and has specified an access mode as an optional system service argument. Logical names or logical name tables in access modes outer to the mode of the caller may still be deleted if the caller explicitly specifies an access mode as an optional system service parameter, even if the caller does not have SYSNAM privilege.
2. When a single logical name table entry was to be deleted this system service was requiring delete access to the containing logical name table before allowing the deletion to proceed. When all logical name table entries within a logical name table were to be deleted, no access checking was being done. This is incorrect. The access requirements for the deletion of logical name tables and logical names are as follows:
  - a. To delete a logical name, write access to the containing logical name table is required.
  - b. To delete a logical name table, either delete access to the table itself or write access to its containing logical name table (the system directory table) is required.
3. It is never necessary to do any protection checking when process-private logical name tables are involved. Therefore, do not perform any protection checking prior to the deletion of any process-private logical name table entry.

#### Changes to EXE\$TRNLNM:

1. This system service would accept an invalid access mode as an optional system service parameter without returning an error. Add access mode error checking.
2. It is never necessary to do any protection checking when process-private logical name tables are involved. Therefore, do not perform any protection checking if the target logical name table entry is process-private.

V03-014 RAS0166 Ron Schaefer 5-Jul-1983  
Reverse polarity of branch in positioning to a translation  
index within a \$TRNLNM itmlst. Also optimize #1s.

V03-013 WMC0001 Wayne Cardoza 23-Jun-1983  
Add chained item lists, parent item code.



0000 343 :  
0000 344 :  
0000 345 :  
0000 346 :  
0000 347 :  
0000 348 :  
0000 349 :  
0000 350 :  
0000 351 :  
0000 352 :  
0000 353 :  
0000 354 :  
0000 355 :  
0000 356 :  
0000 357 :  
0000 358 :  
0000 359 :  
0000 360 :  
0000 361 :  
0000 362 :  
0000 363 :  
0000 364 :  
0000 365 :  
0000 366 :  
0000 367 :  
0000 368 :  
0000 369 :  
0000 370 :  
0000 371 :  
0000 372 :  
0000 373 :  
0000 374 :  
0000 375 :  
0000 376 :  
0000 377 :  
0000 378 :  
0000 379 :  
0000 380 :  
0000 381 :  
0000 382 :  
0000 383 :  
0000 384 :  
0000 385 :  
0000 386 :  
0000 387 :  
0000 388 :  
0000 389 :  
0000 390 :  
0000 391 :  
0000 392 :  
0000 393 :  
0000 394 :  
0000 395 :  
0000 396 :  
0000 397 :  
0000 398 :  
0000 399 :

- V03-012 RAS0160 Ron Schaefer 16-Jun-1983  
Charge all arguments to be by-reference. This affects  
ACMODE all services  
ATTR \$CRELNM, \$CRELNT and \$TRNLNM  
PROMSK \$CRELNT  
QUOTA \$CRELNT
- V03-011 DMW4046 DMWalp 9-Jun-1983  
Post intergration of new logical name structures  
1.) MAX\_INDEX in TRNLNM returns the maximum index  
if non-negative, else -1  
2.) Clean up the setting default index value of  
zero in TRNLNM  
3.) Replace ^XFFFF with LNMS\_LNMB\_ADDR as item value
- V03-010 DMW4038 DMWalp 25-May-1983  
Fix check for LNMS\_LNMB\_ADDR item
- V03-009 RAS0158 Ron Schaefer 25-May-1983  
Add protection structure and checking to logical  
name tables. Currently, only SOGW protection is implemented.  
Correct item list buffer probing in \$TRNLNM to make  
it tolerate longer than necessary buffers.
- V03-008 DMW4029 DMWalp 25-May-1983  
Added code to CRELNM to allow MTL and mailbox UCB to be  
intergrated with the new logical name structures. This  
includes the addition of LNMS\_LNMB\_ADDR and work to allow  
LNMSC\_BACKPTR to be accpeted thru system service interface.
- V03-007 TMK0004 Todd M. Katz 30-Apr-1983  
When VMS must default name a new logical name table, it is  
given a name of the form LNMSxxxxxxx instead of a name of  
the form LNT\$xxxxxxx.
- V03-006 TMK0003 Todd M. Katz 25-Apr-1983  
Make multiple to changes to the routines within this module:  
EXE\$CRELNT:  
1. Un-comment the SETIPL that was commented out for debugging  
purposes.  
2. Change several instructions to conform to VMS coding  
requirements.  
3. If a process-private logical name table is to be created,  
the size of the logical name block is saved on the stack,  
the system pool logical name block is deallocated, the size  
is retrieved, and process-private P1 space is allocated. I  
was saving this size as a word on the stack, and this was  
creating problems allocating P1 space, after the size was  
popped off the stack because I neglected to zero out the  
high order word. To fix this problem, size is now saved as  
a longword on the stack.



0000 400 :  
0000 401 :  
0000 402 :  
0000 403 :  
0000 404 :  
0000 405 :  
0000 406 :  
0000 407 :  
0000 408 :  
0000 409 :  
0000 410 :  
0000 411 :  
0000 412 :  
0000 413 :  
0000 414 :  
0000 415 :  
0000 416 :  
0000 417 :  
0000 418 :  
0000 419 :  
0000 420 :  
0000 421 :  
0000 422 :  
0000 423 :  
0000 424 :  
0000 425 :  
0000 426 :  
0000 427 :  
0000 428 :  
0000 429 :  
0000 430 :  
0000 431 :  
0000 432 :  
0000 433 :  
0000 434 :  
0000 435 :  
0000 436 :  
0000 437 :  
0000 438 :  
0000 439 :  
0000 440 :  
0000 441 :  
0000 442 :  
0000 443 :  
0000 444 :  
0000 445 :  
0000 446 :  
0000 447 :  
0000 448 :  
0000 449 :  
0000 450 :  
0000 451 :  
0000 452 :  
0000 453 :  
0000 454 :  
0000 455 :  
0000 456 :

4. R2 is now saved before calling LNMSLOCKW (which destroys it) instead of after.

5. Instead of picking up the QUOTA argument twice from the user's parameter list, it is picked up and saved the first time it is needed.

6. Pickup ACMODE as a byte instead of a longword.

7. Change the name of TABNAM to RESNAM, TABLEN to RESLEN, and LOGNAM to TABNAM.

8. If the new table is mapped to an existing table, then save the address of the existing LNMB on the stack before deleting the new LNMB so that the table's name maybe returned if required.

#### EXESCRELNM:

1. Fix an incorrect probing of the TABNAM parameter.

2. Un-comment the SETIPL that was commented out for debugging purposes.

3. Do not perform any validation of the item list (except for the STRING item) during the first pass.

4. Return SSS\_NOGRPNAM instead of SSS\_NOPRIV if the user does not have sufficient privilege to create a shareable logical name.

5. If a process-private logical name is to be created, the size of the logical name block is saved on the stack, the system pool logical name block is deallocated, the size is retrieved, and process-private P1 space is allocated. I was saving this size as a word on the stack, and this was creating problems allocating P1 space, after the size was popped off the stack because I neglected to zero out the high order word. To fix this problem, size is now saved as a longword on the stack.

6. Pickup the address of all item buffers before probing. After probing refer only to system service copies of these addresses, and not to user copies.

7. As each translation block is created, check to make sure that creation of this block would not result in the exceeding of the space allocated for the logical name block.

8. Change several instructions to conform to VMS coding requirements.

9. Pickup ACMODE as a byte instead of a longword.

#### EXESDELLNM:

1. Un-comment the SETIPL that was commented out for debugging



0000 457 :  
0000 458 :  
0000 459 :  
0000 460 :  
0000 461 :  
0000 462 :  
0000 463 :  
0000 464 :  
0000 465 :  
0000 466 :  
0000 467 :  
0000 468 :  
0000 469 :  
0000 470 :  
0000 471 :  
0000 472 :  
0000 473 :  
0000 474 :  
0000 475 :  
0000 476 :  
0000 477 :  
0000 478 :  
0000 479 :  
0000 480 :  
0000 481 :  
0000 482 :  
0000 483 :  
0000 484 :  
0000 485 :  
0000 486 :  
0000 487 :  
0000 488 :  
0000 489 :  
0000 490 :  
0000 491 :  
0000 492 :  
0000 493 :  
0000 494 :  
0000 495 :  
0000 496 :  
0000 497 :  
0000 498 :  
0000 499 :  
0000 500 :  
0000 501 :  
0000 502 :  
0000 503 :  
0000 504 :  
0000 505 :  
0000 506 :  
0000 507 :  
0000 508 :  
0000 509 :--

purposes.

2. When the deletion of a specific logical name in an access mode other than user has been requested, all outer access mode logical names with the same name and in the same table are also deleted.

3. Pickup ACMODE as a byte instead of a longword.

#### EXE\$TRNLNM:

1. Fix an incorrect probing of the TABNAM parameter.
2. Un-comment the SETIPL that was commented out for debugging purposes.
3. Pickup the address of all item buffers before probing. After probing refer only to system service copies of these addresses, and not to user copies.
4. Change how the index of INDEX items are validated.
5. Change several instructions to conform to VMS coding requirements.
6. Return the attribute bit LNMSV\_SHAREABLE in the ATTRIBUTES item whenever the name being translated is shareable.
7. Pickup ACMODE as a byte instead of a longword.
8. Change how the ACMODE argument is interrupted. If the argument is 0, maximize with the mode of the caller; otherwise, the specified mode is used to qualify the search.
9. Change the attribute bit LNMSV\_NOT\_EXIST to LNMSV\_EXISTS. This bit will be set in the ATTRIBUTES item buffers of those indexes that do exist, and clear in the ATTRIBUTES item buffers of those indexes that do not exist.

V03-005 BLS0219 Benn Schreiber 19-Apr-1983  
Make some BSBW's into JSB's with longword displacements.

V03-004 TMK0002 Todd M. Katz 18-Apr-1983  
Fix a broken ASSUME statement. This ASSUME broke when I changed the structure of a table header by removing the field LNMT\$SL LOGNAM. Also, no longer fill in this "non-existent" field when creating a logical name table.

V03-003 TMK0001 Todd M. Katz 18-Mar-1983  
Re-write SYSS\$CRELNT. Add SYSS\$CRELNM, SYSS\$DELLNM, SYSS\$TRNLNM.



```
0000 511      .SBTTL  DECLARATIONS
0000 512
0000 513 :
0000 514 : MACRO LIBRARY CALLS
0000 515 :
0000 516
0000 517      $ARMDEF      ;DEFINE ACCESS RIGHTS MASK
0000 518      $CADEF      ;DEFINE CONDITIONAL ASSEMBLY SWITCHES
0000 519      $DYNDEF     ;DEFINE DATA STRUCTURE TYPE CODES
0000 520      $IPLDEF     ;DEFINE INTERRUPT PRIORITY LEVELS
0000 521      $LNMDDEF    ;DEFINE LOGICAL NAME ATTRIBUTES
0000 522      $LNMDSTRDEF  ;DEFINE LOGICAL NAME STRUCTURES OFFSETS
0000 523      $ORBDEF     ;DEFINE OBJECT RIGHTS BLOCK OFFSETS
0000 524      $PCBDEF     ;DEFINE PCB OFFSETS
0000 525      $PRDEF      ;DEFINE PROCESSOR REGISTER NUMBERS
0000 526      $PRVDEF     ;DEFINE PRIVILEGE BITS
0000 527      $PSLDEF     ;DEFINE PROCESSOR STATUS FIELDS
0000 528      $SSDEF      ;DEFINE SYSTEM STATUS VALUES
0000 529
0000 530 :
0000 531 : LOCAL SYMBOLS
0000 532 :
0000 533 : ARGUMENT LIST OFFSET DEFINITIONS FOR CREATE LOGICAL NAME TABLE.
0000 534 :
0000 535
00000004 0000 536 CTATTR=4      ;ADDRESS OF TABLE ATTRIBUTES
00000008 0000 537 CTRESNAM=8    ;ADDRESS OF TABLE NAME STRING DESCRIPTOR
0000000C 0000 538 CTRESLEN=12   ;ADDRESS OF WORD TO RECEIVE LENGTH OF TABLE NAME
00000010 0000 539 CTQUOTA=16    ;ADDRESS OF TABLE QUOTA
00000014 0000 540 CTPROT=20     ;ADDRESS OF PROTECTION MASK
00000018 0000 541 CTTABNAM=24   ;ADDRESS OF TABLE NAME STRING DESCRIPTOR
0000001C 0000 542 CTPARTAB=28   ;PARENT TABLE NAME DESCRIPTOR
00000020 0000 543 CTACMODE=32   ;ADDRESS OF ACCESS MODE
0000 544
0000 545 :
0000 546 : ARGUMENT LIST OFFSET DEFINITIONS FOR CREATE LOGICAL NAME.
0000 547 :
0000 548
00000004 0000 549 CNATTR=4      ;ADDRESS OF ATTRIBUTES
00000008 0000 550 CNTABNAM=8    ;ADDRESS OF TABLE NAME STRING DESCRIPTOR
0000000C 0000 551 CNLOGNAM=12   ;ADDRESS OF LOGICAL NAME STRING DESCRIPTOR
00000010 0000 552 CNACMODE=16   ;ADDRESS OF ACCESS MODE
00000014 0000 553 CNITMLST=20   ;ADDRESS OF ITEM LIST
0000 554
0000 555 :
0000 556 : ARGUMENT LIST OFFSET DEFINITIONS FOR DELETE LOGICAL NAME.
0000 557 :
0000 558
00000004 0000 559 DNTABNAM=4    ;ADDRESS OF TABLE NAME STRING DESCRIPTOR
00000008 0000 560 DNLOGNAM=8    ;ADDRESS OF LOGICAL NAME STRING DESCRIPTOR
0000000C 0000 561 DNACMODE=12   ;ADDRESS OF ACCESS MODE
0000 562
0000 563 :
0000 564 : ARGUMENT LIST OFFSET DEFINITIONS FOR TRANSLATE LOGICAL NAME.
0000 565 :
0000 566
00000004 0000 567 TRATTR=4      ;ADDRESS OF TRANSLATION FLAGS
```



```
00000008 0000 568 TRTABNAM=8 ;ADDRESS OF TABLE NAME STRING DESCRIPTOR
0000000C 0000 569 TRLOGNAM=12 ;ADDRESS OF LOGICAL NAME STRING DESCRIPTOR
00000010 0000 570 TRACMODE=16 ;ADDRESS OF ACCESS MODE
00000014 0000 571 TRITMLST=20 ;ADDRESS OF ITEM LIST
0000 572
0000 573 ;
0000 574 ; PROTECTION MASK CONSTANTS FOR CHECKING.
0000 575 ;
0000 576
00000001 0000 577 READ_ACCESS = ARMSM_READ
00000002 0000 578 WRITE_ACCESS = ARMSM_WRITE
00000004 0000 579 QUOTA_ACCESS = ARMSM_EXECUTE
00000008 0000 580 DELETE_ACCESS = ARMSM_DELETE
0000 581
0000 582 ;
0000 583 ; ASSUME STATEMENTS FOR LOGICAL NAME BLOCK, LOGICAL NAME TRANSLATION, AND
0000 584 ; LOGICAL NAME TABLE HEADER.
0000 585 ;
0000 586
0000 587 ASSUME LNMB$B_TYPE+1, EQ, LNMB$B_ACMODE
0000 588 ASSUME LNMB$B_ACMODE+1, EQ, LNMB$B_TABLE
0000 589 ASSUME LNMB$B_TABLE+4, EQ, LNMB$B_FLAGS
0000 590 ASSUME LNMB$B_FLAGS+1, EQ, LNMB$B_NAME
0000 591
0000 592 ASSUME LNMX$B_FLAGS, EQ, 0
0000 593 ASSUME LNMX$B_FLAGS+1, EQ, LNMX$B_INDEX
0000 594 ASSUME LNMX$B_INDEX+1, EQ, LNMX$B_HASH
0000 595 ASSUME LNMX$B_HASH+2, EQ, LNMX$B_XLATION
0000 596
0000 597 ASSUME LNMTH$B_FLAGS, EQ, 0
0000 598 ASSUME LNMTH$B_FLAGS+1, EQ, LNMTH$B_HASH
0000 599 ASSUME LNMTH$B_HASH+4, EQ, LNMTH$B_ORB
0000 600 ASSUME LNMTH$B_ORB+4, EQ, LNMTH$B_NAME
0000 601 ASSUME LNMTH$B_NAME+4, EQ, LNMTH$B_PARENT
0000 602 ASSUME LNMTH$B_PARENT+4, EQ, LNMTH$B_CHILD
0000 603 ASSUME LNMTH$B_CHILD+4, EQ, LNMTH$B_SIBLING
0000 604 ASSUME LNMTH$B_SIBLING+4, EQ, LNMTH$B_QTABLE
0000 605 ASSUME LNMTH$B_QTABLE+4, EQ, LNMTH$B_BYTESLM
0000 606 ASSUME LNMTH$B_BYTESLM+4, EQ, LNMTH$B_BYTES
0000 607
00000000 608 .PSECT YF$SLNM
0000 609
0000 610 ;
0000 611 ; LOCAL DATA
0000 612 ;
0000 613
00000014 0000 614 LNM_HEX_TAB_LEN = 4 + 8 + 8 ;SIZE OF 'LNMS' + pid + addr
0000 615 HEXDIGITS:
0000 616 .ASCII /0123456789ABCDEF/ ;TABLE TO CONVERT INTEGER TO HEX DIGIT
0010 617
0010 618 ; .PAGE
```

42 41 39 38 37 36 35 34 33 32 31 30  
46 45 44 43

```
0010 620 .SBTTL EXESCRELNT - CREATE LOGICAL NAME TABLE
0010 621
0010 622 :+
0010 623 : EXESCRELNT - CREATE LOGICAL NAME TABLE
0010 624 :
0010 625 : THIS SERVICE PROVIDES THE CAPABILITY TO CREATE A LOGICAL NAME TABLE.
0010 626 :
0010 627 : INPUTS:
0010 628 :
0010 629 : CTATTR(AP) = ADDRESS OF TABLE ATTRIBUTES.
0010 630 : CTRESNAM(AP) = ADDRESS OF DESCRIPTOR TO RECEIVE TABLE NAME STRING.
0010 631 : CTRESLEN(AP) = ADDRESS OF WORD TO RECEIVE LENGTH OF TABLE NAME.
0010 632 : CTQUOTA(AP) = ADDRESS OF BYTE QUOTA FOR TABLE AND NAMES CONTAINED THEREI
0010 633 : CTPROT(AP) = ADDRESS OF SOGW PROTECTION MASK.
0010 634 : CTTABNAM(AP) = ADDRESS OF TABLE NAME STRING DESCRIPTOR.
0010 635 : CTPARTAB(AP) = ADDRESS OF PARENT TABLE NAME DESCRIPTOR.
0010 636 : CTACMODE(AP) = ADDRESS OF ACCESS MODE OF LOGICAL NAME TABLE TO BE CREATED
0010 637 :
0010 638 : R4 = CURRENT PROCESS PCB ADDRESS.
0010 639 :
0010 640 : OUTPUTS:
0010 641 :
0010 642 : R0 LOW BIT CLEAR INDICATES FAILURE TO CREATE LOGICAL NAME TABLE ENTRY.
0010 643 :
0010 644 : R0 = $$$ ACCVIO - TABLE NAME DESCRIPTOR, LOGICAL NAME
0010 645 : DESCRIPTOR, LOGICAL NAME STRING, PARENT TABLE NAME
0010 646 : DESCRIPTOR, PARENT TABLE NAME STRING CANNOT BE READ BY
0010 647 : CALLING ACCESS MODE. TABLE NAME LENGTH WORD, TABLE NAME
0010 648 : STRING BUFFER CANNOT BE WRITTEN BY CALLING ACCESS MODE.
0010 649 :
0010 650 : R0 = $$$ BADPARAM - INVALID ATTRIBUTE OR ACCESS MODE SPECIFIED.
0010 651 : PARENT LOGICAL NAME TABLE NAME NOT SPECIFIED.
0010 652 :
0010 653 : R0 = $$$ DUPLNAM - ATTEMPT MADE TO SUPERSEDE NON-ALIASABLE
0010 654 : LOGICAL NAME TABLE ENTRY OF THE SAME OR AN INNER ACCESS
0010 655 : MODE.
0010 656 :
0010 657 : R0 = $$$ EXLNMQUOTA - INSUFFICIENT QUOTA AVAILABLE IN THE
0010 658 : PARENT LOGICAL NAME TABLE'S QUOTA TABLE FOR THE
0010 659 : CREATION OF THE NEW LOGICAL NAME TABLE ENTRY.
0010 660 :
0010 661 : R0 = $$$ INSMEM - SUFFICIENT SYSTEM DYNAMIC MEMORY DOES NOT
0010 662 : EXIST TO ALLOCATE THE NEW LOGICAL NAME TABLE ENTRY AND
0010 663 : IMPLICIT RESOURCE WAIT IS NOT ENABLED.
0010 664 :
0010 665 : R0 = $$$ IVLOGNAM - ZERO OR GREATER THAN MAXIMUM LENGTH
0010 666 : LOGICAL OR PARENT TABLE NAME STRING SPECIFIED.
0010 667 :
0010 668 : R0 = $$$ IVLOGTAB - INVALID PARENT TABLE NAME SPECIFIED OR
0010 669 : INVALID LOGICAL NAME TABLE NAME SPECIFIED.
0010 670 :
0010 671 : R0 = $$$ NOLOGTAB - PARENT TABLE SPECIFIED DOES NOT EXIST.
0010 672 :
0010 673 : R0 = $$$ NOPRIV - PROCESS DOES NOT HAVE PRIVILEGE TO CREATE
0010 674 : SPECIFIED LOGICAL NAME TABLE ENTRY.
0010 675 :
0010 676 : R0 = $$$_PARENT_DEL - INSERTION OF NEW LOGICAL NAME TABLE ENTRY
```



0010 677 :  
0010 678 :  
0010 679 :  
0010 680 :  
0010 681 :  
0010 682 :  
0010 683 :  
0010 684 :  
0010 685 :  
0010 686 :  
0010 687 :  
0010 688 :  
0010 689 :  
0010 690 :  
0010 691 :  
0010 692 :  
0010 693 :  
0010 694 :  
0010 695 :  
0010 696 :  
0010 697 :  
0010 698 :  
0010 699 :  
0010 700 :  
0010 701 :  
0010 702 :  
0010 703 :  
0010 704 :  
0010 705 :  
00000000 706 :  
001F' 0000 707 :  
31 0002 708 :  
0005 709 :  
00000010 710 :  
0010 711 :  
50 0C 3C 0010 712 900\$:  
04 0013 713 :  
50 14 3C 0014 714 910\$:  
04 0017 715 :  
50 0124 8F 3C 0018 716 920\$:  
04 001D 717 930\$:  
50 015C 8F 3C 001E 718 940\$:  
04 0023 719 :  
0024 720 :  
0024 721 :  
0024 722 :  
0024 723 :  
0024 724 :  
0024 725 :  
0024 726 :  
0024 727 :  
0024 728 :  
0024 729 :  
0024 730 :  
0024 731 :  
0024 732 :  
0024 733 :

WOULD HAVE RESULTED IN THE DELETION OF A (GRAND)PARENT  
LOGICAL NAME TABLE ENTRY.

RO = \$\$\$ RESULTOVF - BUFFER NOT LARGE ENOUGH TO CONTAIN NAME  
OF NEW LOGICAL NAME TABLE.

RO = \$\$\$ TOOMANYLNM - TOO MANY LEVELS OF RECURSION IN SEARCH  
FOR PARENT TABLE.

RO LOW BIT SET INDICATES SUCCESSFUL COMPLETION.

RO = \$\$\$ LNMCREATED - NORMAL COMPLETION, NEW LOGICAL NAME TABLE  
ENTRY CREATED.

RO = \$\$\$ NORMAL - NORMAL COMPLETION, LNMSV CREATE IF SET AND  
THE LOGICAL NAME TABLE ENTRY ALREADY EXISTED.

RO = \$\$\$ SUPERSEDE - NORMAL COMPLETION, NEW LOGICAL NAME TABLE  
ENTRY SUPERSEDED A PREVIOUSLY EXISTING ENTRY AT THE SAME  
OR OUTER ACCESS MODE IN THE SPECIFIED PARENT LOGICAL  
NAME TABLE.

SIDE EFFECTS:

THIS ROUTINE EXITS AT IPL 2, AND MUST CONTINUE TO DO SO, BECAUSE  
IT IS CALLED AT SYSTEM INITIALIZATION TIME.

.PSECT Y\$EXEPAGED  
.ENTRY EXE\$CRELNT, ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>  
BRW EXE\$CRELNT

.PSECT YF\$\$LNM  
.ENABLE LSB

MOVZWL #\$\$\$\_ACCVIO,RO ;ACCESS VIOLATION  
RET  
MOVZWL #\$\$\$\_BADPARAM,RO ;BAD SYSTEM SERVICE PARAMETER  
RET  
MOVZWL #\$\$\$\_INSFMEM,RO ;NO PRIVILEGE TO CREATE TABLE ENTRY  
RET  
MOVZWL #\$\$\$\_IVLOGTAB,RO ;INVALID LOGICAL NAME TABLE NAME  
RET

VALIDATE AND COPY PARAMETERS AS NECESSARY. REGISTER ASSIGNMENT FOR THE  
PARAMETERS ARE AS FOLLOWS:

R5 = ACCESS MODE.  
R6 = PROTECTION MASK.  
R7 = ATTRIBUTE BITS.  
R8 = ADDRESS OF PROBED AND COPIED PARENT TABLE NAME DESCRIPTOR.  
R9 = ADDRESS OF PROBED AND COPIED TABLE NAME DESCRIPTOR.  
R10 = ADDRESS OF PROBED AND COPIED LOGICAL NAME DESCRIPTOR.  
R11 = ADDRESS OF WORD TO RECEIVE TABLE NAME LENGTH.



|          |          |    |    |      |     |            |                        |  |  |
|----------|----------|----|----|------|-----|------------|------------------------|--|--|
| 5B       | 0C       | AC | D0 | 0024 | 734 | EXECRELNT: |                        |  |  |
|          |          | 06 | 13 | 0024 | 735 | MOVL       | CTRESLEN(AP),R11       |  | :ADDRESS OF TABLE NAME LENGTH WORD       |
|          |          |    |    | 0028 | 736 | BEQL       | 10\$                   |  | :BRANCH IF NOT PRESENT                   |
|          |          |    |    | 002A | 737 | IFNOWRT    | #2,(R11),900\$         |  | :CHECK WRITE ACCESS TO WORD              |
|          |          |    |    | 0030 | 738 |            |                        |  |  |
| 56       | 14       | AC | D0 | 0030 | 739 | MOVL       | CTPROT(AP),R6          |  | :ADDRESS OF PROTECTION MASK WORD         |
|          |          | 07 | 12 | 0034 | 740 | BNEQ       | 15\$                   |  | :BRANCH IF ONE PRESENT                   |
| 56       | FF00     | 8F | 3C | 0036 | 741 | MOVZWL     | #^XFF00,R6             |  | :DEFAULT THE PROTECTION TO S:RWED O:RWED |
|          |          | 09 | 11 | 003B | 742 | BRB        | 20\$                   |  |  |
|          |          |    |    | 003D | 743 | IFNORD     | #2,(R6),900\$          |  | :CHECK READ ACCESS TO WORD               |
| 56       | 66       | 3C |    | 0043 | 744 | MOVZWL     | (R6),R6                |  | :GET VALUE                               |
|          |          |    |    | 0046 | 745 |            |                        |  |  |
| 59       | 08       | AC | D0 | 0046 | 746 | MOVL       | CTRESNAM(AP),R9        |  | :ADDRESS OF TABLE NAME DESCRIPTOR        |
|          |          | 12 | 13 | 004A | 747 | BEQL       | 30\$                   |  | :BRANCH IF NOT PRESENT                   |
| 51       | 59       | D0 |    | 004C | 748 | MOVL       | R9,R1                  |  | :SET UP CALL                             |
| 00000000 | EF       | 16 |    | 004F | 749 | JSB        | L^EXESPROBEW_DSC       |  | :PROBE DESCRIPTOR AND WRITE PROBE BUFFER |
| C5       | 50       | E9 |    | 0055 | 750 | BLBC       | R0,930\$               |  | :CAN'T WRITE BUFFER OR READ DESCRIPTOR   |
| 7E       | 51       | 7D |    | 0058 | 751 | MOVQ       | R1,-(SP)               |  | :SAVE TABLE NAME DESCRIPTOR              |
| 59       | 5E       | D0 |    | 005B | 752 | MOVL       | SP,R9                  |  | :ADDRESS OF TABLE NAME DESCRIPTOR        |
|          |          |    |    | 005E | 753 |            |                        |  |  |
| 57       | 04       | AC | D0 | 005E | 754 | MOVL       | CTATTR(AP),R7          |  | :TABLE ATTRIBUTES                        |
|          |          | 12 | 13 | 0062 | 755 | BEQL       | 35\$                   |  | :BRANCH IF NOT PRESENT                   |
|          |          |    |    | 0064 | 756 | IFNORD     | #4,(R7),900\$          |  | :CHECK READ ACCESS TO VALUE              |
|          |          |    |    | 006A | 757 | MOVL       | (R7),R7                |  | :GET VALUE                               |
| 57       | FEFFFFFC | 8F | D3 | 006D | 758 | BITL       | #^C<-                  |  |  |
|          |          |    |    | 0074 | 759 |            | LNMSM_CONFINE! -       |  | :CONFINE TO PROCESS                      |
|          |          |    |    | 0074 | 760 |            | LNMSM_CREATE IF! -     |  | :SUPERCEDE VS. MAP                       |
|          |          |    |    | 0074 | 761 |            | LNMSM_NO_ALIAS -       |  | :DO NOT ALLOW ALIASES                    |
|          |          |    |    | 0074 | 762 |            | >,R7                   |  |  |
|          | 9E       | 12 |    | 0074 | 763 | BNEQ       | 910\$                  |  | :INVALID TABLE ATTRIBUTES                |
|          |          |    |    | 0076 | 764 |            |                        |  |  |
|          |          |    |    | 0076 | 765 | ASSUME     | LNMSC_TABNAMLEN,LE,512 |  |  |
|          |          |    |    | 0076 | 766 |            |                        |  |  |
| 5A       | 18       | AC | D0 | 0076 | 767 | MOVL       | CTTABNAM(AP),R10       |  | :ADDRESS OF TABLE NAME DESCRIPTOR        |
|          |          | 1F | 13 | 007A | 768 | BEQL       | 40\$                   |  | :BRANCH IF NOT PRESENT                   |
|          |          |    |    | 007C | 769 | IFNORD     | #8,(R10),900\$         |  | :CHECK ACCESS TO DESCRIPTOR              |
| 51       | 6A       | 7D |    | 0082 | 770 | MOVQ       | (R10),R1               |  | :RETRIEVE TABLE NAME DESCRIPTOR          |
| 51       | 51       | 3C |    | 0085 | 771 | MOVZWL     | R1,R1                  |  | :ZERO HIGH ORDER WORD OF LENGTH          |
|          | 94       | 13 |    | 0088 | 772 | BEQL       | 940\$                  |  | :ERROR IF ZERO LENGTH TABLE NAME         |
| 1F       | 51       | B1 |    | 008A | 773 | CMPL       | R1,LNMSC_TABNAMLEN     |  | :CHECK SIZE OF TABLE NAME STRING?        |
|          | 8F       | 1A |    | 008D | 774 | BGTRU      | 940\$                  |  | :ERROR IF SPECIFIED SIZE EXCEEDS MAXIMUM |
|          |          |    |    | 008F | 775 | IFNORD     | R1,(R2),44\$           |  | :CHECK ACCESS TO TABLE NAME BUFFER       |
| 7E       | 51       | 7D |    | 0095 | 776 | MOVQ       | R1,-(SP)               |  | :SAVE TABLE NAME DESCRIPTOR              |
| 5A       | 5E       | D0 |    | 0098 | 777 | MOVL       | SP,R10                 |  | :ADDRESS OF TABLE NAME DESCRIPTOR        |
|          |          |    |    | 009B | 778 |            |                        |  |  |
| 58       | 1C       | AC | D0 | 009B | 779 | MOVL       | CTPARTAB(AP),R8        |  | :ADDRESS OF PARENT TABLE DESCRIPTOR      |
|          |          | 29 | 13 | 009F | 780 | BEQL       | 42\$                   |  | :ERROR IF NOT PRESENT                    |
|          |          |    |    | 00A1 | 781 | IFNORD     | #8,(R8),44\$           |  | :CHECK ACCESS TO DESCRIPTOR              |
| 50       | 68       | 7E |    | 00A7 | 782 | MOVAQ      | (R8),R0                |  | :ADDRESS OF DESCRIPTOR                   |
|          | FF53     | 30 |    | 00AA | 783 | BSBW       | LNMSPROBER             |  | :PROBE PARENT TABLE NAME STRING          |
|          | 1D       | 50 | E9 | 00AD | 784 | BLBC       | R0,43\$                |  | :BRANCH IF CAN'T READ OR NOT PRESENT     |
| 7E       | 51       | 7D |    | 00B0 | 785 | MOVQ       | R1,-(SP)               |  | :SAVE PARENT TABLE NAME DESCRIPTOR       |
| 58       | 5E       | D0 |    | 00B3 | 786 | MOVL       | SP,R8                  |  | :ADDRESS OF PARENT TABLE NAME DESCRIPTOR |
|          |          |    |    | 00B6 | 787 |            |                        |  |  |
| 50       | 20       | AC | D0 | 00B6 | 788 | MOVL       | CIACMODE(AP),R0        |  | :GET SPECIFIED ACCESS MODE               |
|          |          | 1D | 13 | 00BA | 789 | BEQL       | 50\$                   |  | :BRANCH IF NOT PRESENT                   |
|          |          |    |    | 00BC | 790 | IFNORD     | #1,(R0),44\$           |  | :CHECK READ ACCESS TO BYTE               |



| PC | Inst | Op | Op2 | Op3 | Op4 | Op5 | Op6 | Op7 | Op8 | Op9 | Op10 | Op11 | Op12 | Op13 | Op14 | Op15 | Op16 | Op17 | Op18 | Op19 | Op20 | Op21 | Op22 | Op23 | Op24 | Op25 | Op26 | Op27 | Op28 | Op29 | Op30 | Op31 | Op32 | Op33 | Op34 | Op35 | Op36 | Op37 | Op38 | Op39 | Op40 | Op41 | Op42 | Op43 | Op44 | Op45 | Op46 | Op47 | Op48 | Op49 | Op50 | Op51 | Op52 | Op53 | Op54 | Op55 | Op56 | Op57 | Op58 | Op59 | Op60 | Op61 | Op62 | Op63 | Op64 | Op65 | Op66 | Op67 | Op68 | Op69 | Op70 | Op71 | Op72 | Op73 | Op74 | Op75 | Op76 | Op77 | Op78 | Op79 | Op80 | Op81 | Op82 | Op83 | Op84 | Op85 | Op86 | Op87 | Op88 | Op89 | Op90 | Op91 | Op92 | Op93 | Op94 | Op95 | Op96 | Op97 | Op98 | Op99 | Op100 | Op101 | Op102 | Op103 | Op104 | Op105 | Op106 | Op107 | Op108 | Op109 | Op110 | Op111 | Op112 | Op113 | Op114 | Op115 | Op116 | Op117 | Op118 | Op119 | Op120 | Op121 | Op122 | Op123 | Op124 | Op125 | Op126 | Op127 | Op128 | Op129 | Op130 | Op131 | Op132 | Op133 | Op134 | Op135 | Op136 | Op137 | Op138 | Op139 | Op140 | Op141 | Op142 | Op143 | Op144 | Op145 | Op146 | Op147 | Op148 | Op149 | Op150 | Op151 | Op152 | Op153 | Op154 | Op155 | Op156 | Op157 | Op158 | Op159 | Op160 | Op161 | Op162 | Op163 | Op164 | Op165 | Op166 | Op167 | Op168 | Op169 | Op170 | Op171 | Op172 | Op173 | Op174 | Op175 | Op176 | Op177 | Op178 | Op179 | Op180 | Op181 | Op182 | Op183 | Op184 | Op185 | Op186 | Op187 | Op188 | Op189 | Op190 | Op191 | Op192 | Op193 | Op194 | Op195 | Op196 | Op197 | Op198 | Op199 | Op200 | Op201 | Op202 | Op203 | Op204 | Op205 | Op206 | Op207 | Op208 | Op209 | Op210 | Op211 | Op212 | Op213 | Op214 | Op215 | Op216 | Op217 | Op218 | Op219 | Op220 | Op221 | Op222 | Op223 | Op224 | Op225 | Op226 | Op227 | Op228 | Op229 | Op230 | Op231 | Op232 | Op233 | Op234 | Op235 | Op236 | Op237 | Op238 | Op239 | Op240 | Op241 | Op242 | Op243 | Op244 | Op245 | Op246 | Op247 | Op248 | Op249 | Op250 | Op251 | Op252 | Op253 | Op254 | Op255 | Op256 | Op257 | Op258 | Op259 | Op260 | Op261 | Op262 | Op263 | Op264 | Op265 | Op266 | Op267 | Op268 | Op269 | Op270 | Op271 | Op272 | Op273 | Op274 | Op275 | Op276 | Op277 | Op278 | Op279 | Op280 | Op281 | Op282 | Op283 | Op284 | Op285 | Op286 | Op287 | Op288 | Op289 | Op290 | Op291 | Op292 | Op293 | Op294 | Op295 | Op296 | Op297 | Op298 | Op299 | Op300 | Op301 | Op302 | Op303 | Op304 | Op305 | Op306 | Op307 | Op308 | Op309 | Op310 | Op311 | Op312 | Op313 | Op314 | Op315 | Op316 | Op317 | Op318 | Op319 | Op320 | Op321 | Op322 | Op323 | Op324 | Op325 | Op326 | Op327 | Op328 | Op329 | Op330 | Op331 | Op332 | Op333 | Op334 | Op335 | Op336 | Op337 | Op338 | Op339 | Op340 | Op341 | Op342 | Op343 | Op344 | Op345 | Op346 | Op347 | Op348 | Op349 | Op350 | Op351 | Op352 | Op353 | Op354 | Op355 | Op356 | Op357 | Op358 | Op359 | Op360 | Op361 | Op362 | Op363 | Op364 | Op365 | Op366 | Op367 | Op368 | Op369 | Op370 | Op371 | Op372 | Op373 | Op374 | Op375 | Op376 | Op377 | Op378 | Op379 | Op380 | Op381 | Op382 | Op383 | Op384 | Op385 | Op386 | Op387 | Op388 | Op389 | Op390 | Op391 | Op392 | Op393 | Op394 | Op395 | Op396 | Op397 | Op398 | Op399 | Op400 | Op401 | Op402 | Op403 | Op404 | Op405 | Op406 | Op407 | Op408 | Op409 | Op410 | Op411 | Op412 | Op413 | Op414 | Op415 | Op416 | Op417 | Op418 | Op419 | Op420 | Op421 | Op422 | Op423 | Op424 | Op425 | Op426 | Op427 | Op428 | Op429 | Op430 | Op431 | Op432 | Op433 | Op434 | Op435 | Op436 | Op437 | Op438 | Op439 | Op440 | Op441 | Op442 | Op443 | Op444 | Op445 | Op446 | Op447 | Op448 | Op449 | Op450 | Op451 | Op452 | Op453 | Op454 | Op455 | Op456 | Op457 | Op458 | Op459 | Op460 | Op461 | Op462 | Op463 | Op464 | Op46 |
|----|------|----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
|----|------|----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|



```
03 50 E8 0103 848 BLBS R0,77$ ;BRANCH IF SUFFICIENT MEMORY
FFOF 31 0106 849 BRW 920$ ;OTHERWISE RETURN ERROR
08 A2 51 B0 0109 850 77$: MOVW R1,LNMB$W_SIZE(R2) ;SAVE NEW BLOCK SIZE WITHIN THE BLOCK
010D 851
010D 852
010D 853 ; WRITE LOCK THE LOGICAL NAME MUTEX AND THEN POSITION TO THE PARENT LOGICAL
010D 854 ; NAME TABLE. DEALLOCATE THE NEW LNMB IF UNABLE TO POSITION TO THE PARENT
010D 855 ; TABLE ENTRY.
010D 856
010D 857
52 DD 010D 858 PUSHL R2 ;SAVE LOGICAL NAME BLOCK ADDRESS
FEEF 30 010F 859 BSBW LNMB$LOCKW ;LOCK TABLES FOR WRITING
51 55 D0 0112 860 MOVL R5,R1 ;ACCESS MODE
52 68 7D 0115 861 MOVQ (R8),R2 ;TABLE NAME DESCRIPTOR
FEE5 30 0118 862 BSBW LNMB$FIRSTTAB ;SEARCH FOR SPECIFIED PARENT TABLE
54 8ED0 011B 863 POPL R4 ;RESTORE LOGICAL NAME BLOCK ADDRESS
03 50 E8 011E 864 BLBS R0,80$ ;BRANCH ON FAILURE
01AC 31 0121 865 BRW 160$
0124 866
0124 867
0124 868 ; IF THE PARENT LOGICAL NAME TABLE IS SHAREABLE THEN:
0124 869
0124 870 ; 1. MARK THE NEW TABLE AS SHAREABLE.
0124 871 ; 2. MAKE SURE THE NEW TABLE IS NOT MARKED AS CONFINED.
0124 872 ; 3. MAKE SURE THE CALLER HAS QUOTA ACCESS TO THE PARENT LOGICAL NAME TABLE.
0124 873 ; 3. MAKE SURE THAT THE CALLER HAS WRITE ACCESS TO THE SYSTEM DIRECTORY TABLE
0124 874 ; PROVIDED THE USER IS SPECIFYING THE NAME OF THE SHAREABLE TABLE AND NOT
0124 875 ; LETTING VMS DEFAULT NAME IT.
0124 876
0124 877
00 E1 0124 878 80$: BBC #LNMB$V SHAREABLE, - ;BRANCH IF THE PARENT TABLE ENTRY IS IN
3B 61 0126 879 LNMB$B_FLAGS(R1),90$ ;PROCESS-PRIVATE SPACE
57 02 CA 0128 880 BICL2 #LNMB$M_CONFINED,R7 ;SHAREABLE TABLES CAN'T BE CONFINED
00 57 10 E3 012B 881 BBCS #LNMB$V_SHAREABLE,R7,83$ ;MARK NEW TABLE AS SHAREABLE
012F 882
52 04 9A 012F 883 83$: MOVZBL #QUOTA_ACCESS,R2 ;CODE FOR ACCESS CHECK
54 54 DD 0132 884 PUSHL R4 ;SAVE LNMB PTR
04 AE D0 0134 885 MOVL 4(SP),R4 ;RESTORE PCB
FEC5 30 0138 886 BSBW LNMB$CHECK_PROT ;CHECK THE PROTECTION
54 8E D0 013B 887 MOVL (SP)+,R4 ;RESTORE LNMB
03 50 E8 013E 888 BLBS R0,85$ ;EXIT ON FAILURE
018C 31 0141 889 BRW 160$
0144 890
5A D5 0144 891 85$: TSTL R10 ;WAS A NAME SPECIFIED FOR THE NEW TABLE
59 13 0146 892 BEQL 100$ ;BRANCH IF ONE WASN'T
0148 893
52 02 9A 0148 894 MOVZBL #WRITE_ACCESS,R2 ;CODE FOR ACCESS CHECK
12 BB 014B 895 PUSHR #*M<R1,R4> ;SAVE LNMB AND PARENT TABLE HEADER ADDR
51 09 A1 D0 014D 896 MOVL LNMB$SL_NAME(R1),R1 ;RETRIEVE ADDRESS OF PARENT LNMB
51 0C A1 D0 0151 897 MOVL LNMB$SL_TABLE(R1),R1 ;RETRIEVE SYSTEM DIRECTORY TABLE HEADER
54 08 AE D0 0155 898 MOVL 8(SP),R4 ;RESTORE PCB
FEA4 30 0159 899 BSBW LNMB$CHECK_PROT ;CHECK THE PROTECTION
12 BA 015C 900 POPR #*M<R1,R4> ;RESTORE LNMB AND PARENT TABLE HEADER
70 50 E9 015E 901 BLBC R0,105$ ;EXIT ON FAILURE
3E 11 0161 902 BRB 100$
0163 903
0163 904 ;
```



```
0163 905 : IF THE PARENT TABLE IS DISCOVERED TO EXIST IN PROCESS-PRIVATE SPACE, THEN
0163 906 : THIS IS ALSO WHERE THE NEW LOGICAL NAME TABLE ENTRY SHOULD GO. DEALLOCATE
0163 907 : THE SYSTEM SPACE LNMB, AND ALLOCATE A SUFFICIENTLY SIZED BLOCK FROM P1
0163 908 : SPACE.
0163 909 :
0163 910 :
6E 7E 08 A4 3C 0163 911 90$: PUSHL R1 ;SAVE ADDRESS OF PARENT'S TABLE HEADER
00000058 8F C2 0165 912 MOVZWL LNMB$W_SIZE(R4),-(SP) ;SAVE SIZE OF LNMB AND COMPUTE SIZE
50 54 D0 0169 913 SUBL2 #ORBSK_LENGTH,(SP) ;OF BLOCK TO BE ALLOCATED FROM P1 POOL
FE8A' 30 0170 914 MOVL R4,R0 ;ADDRESS OF SYSTEM SPACE LNMB
0173 915 BSBW LNMB$DELBLK ;DEALLOCATE SYSTEM SPACE LNMB
0176 916 :
0176 917 POPL R1 ;SIZE OF STORAGE TO ALLOCATE
00000000'GF 16 0179 918 JSB G*EXESALOP1PROC ;ALLOCATE NEW LNMB FROM P1 SPACE
08 50 E8 017F 919 BLBS R0,95$ ;BRANCH IF SUCCESSFUL
6E 0124 8F 3C 0182 920 MOVZWL #SS$-INSFMEM,(SP) ;OTHERWISE RETURN INSUFFICIENT MEMORY
0186 31 0187 921 BRW 190$ ;ERROR AFTER RELEASING MUTEX
018A 922 :
018A 923 95$: MOVL R2,R4 ;ADDRESS OF NEW LNMB
08 A4 51 B0 018D 924 MOVW R1,LNMB$W_SIZE(R4) ;SAVE SIZE WITHIN BLOCK
51 8ED0 0191 925 POPL R1 ;ADDRESS OF PARENT'S TABLE HEADER
52 09 A1 D0 0194 926 MOVL LNMB$H_NAME(R1),R2 ;ADDRESS OF PARENT'S LNMB
01 E1 0198 927 BBC #LNMB$V_CONFINED,- ;IS THE PARENT ENTRY MARKED CONFINED?
04 10 A2 019A 928 LNMB$B_FLAGS(R2),100$ ;BRANCH IF NOT
00 57 01 E3 019D 929 BBCS #LNMB$V_CONFINED,R7,100$ ;MAKE SURE NEW ENTRY IS IF SO
01A1 930 :
01A1 931 :
01A1 932 : PERFORM QUOTA CHECKS. TWO SUCH QUOTA CHECKS ARE MADE:
01A1 933 :
01A1 934 : 1. THE CONTAINING TABLE (SYSTEM OR PROCESS DIRECTORY TABLE) IS CHECKED TO
01A1 935 : MAKE SURE IT HAS SUFFICIENT QUOTA TO CONTAIN THE NEW LOGICAL NAME TABLE
01A1 936 : ENTRY. NOTE THAT AN ASSUMPTION IS MADE THAT THE DIRECTORY TABLES ARE
01A1 937 : THEIR OWN QUOTA HOLDERS.
01A1 938 :
01A1 939 : 2. THE PARENT LOGICAL NAME TABLE'S QUOTA HOLDER IS CHECKED TO MAKE SURE IT HAS
01A1 940 : SUFFICIENT QUOTA FOR THE QUOTA WHICH WILL BE DEDUCTED FROM IT AND ALLOCATED
01A1 941 : SPECIFICALLY TO THE NEW TABLE.
01A1 942 :
01A1 943 :
52 09 A1 D0 01A1 944 100$: MOVL LNMB$H_NAME(R1),R2 ;RETRIEVE PARENT'S TABLE HEADER ADDRESS
52 0C A2 D0 01A5 945 MOVL LNMB$H_TABLE(R2),R2 ;RETRIEVE CONTAINING TABLE'S ADDRESS
50 08 A4 3C 01A9 946 MOVZWL LNMB$W_SIZE(R4),R0 ;SIZE OF NEW TABLE ENTRY
21 A2 50 D1 01AD 947 CMPL R0,LNMB$H_BYTES(R2) ;IS THERE SUFFICIENT QUOTA?
19 1A 01B1 948 BGTRU 103$ ;NO - DEALLOCATE LNMB AND RETURN ERROR
01B3 949 :
58 10 AC D0 01B3 950 MOVL CTQUOTA(AP),R8 ;RETRIEVE NEW TABLE'S QUOTA
20 13 01B7 951 BEQL 110$ ;SKIP SECOND QUOTA CHECK IF NOT PRESENT
58 68 D0 01B9 952 IFNORD #4,(R8),107$ ;CHECK READ ACCESS TO VALUE
01C2 953 MOVL (R8),R8 ;GET VALUE
52 19 A1 D0 01C2 954 :
21 A2 58 D1 01C6 955 101$: MOVL LNMB$H_QTABLE(R1),R2 ;RETRIEVE PARENT QUOTA HOLDER'S ADDRESS
0D 1B 01CA 956 CMPL R8,LNMB$H_BYTES(R2) ;IS THERE SUFFICIENT QUOTA?
50 224C 8F 3C 01CC 957 BLEQU 110$ ;YES - THEN CONTINUE
00FC 31 01D1 958 103$: MOVZWL #SS$_EXLNMQQUOTA,R0 ;NO - THEN DEALLOCATE LNMB AND RETURN
01D4 959 105$: BRW 160$ ; EXCEEDED QUOTA ERROR
50 0C 3C 01D4 960 :
961 107$: MOVZWL #SS$_ACCVIO,R0 ;NO ACCESS
```



```
F8 11 01D7 962 BRB 105$ ;EXIT
      01D9 963
      01D9 964
      01D9 965 : FILL IN THE LNMB PORTION OF THE LOGICAL NAME BLOCK FOR THE NEW LOGICAL NAME
      01D9 966 : TABLE ENTRY.
      01D9 967
      01D9 968 : REGISTER USAGE IS AS FOLLOWS:
      01D9 969
      01D9 970 : R1 = ADDRESS OF TABLE HEADER FOR PARENT LOGICAL NAME TABLE.
      01D9 971 : R3 = SIZE OF NEW LOGICAL NAME TABLE ENTRY'S NAME.
      01D9 972 : R4 = ADDRESS OF LOGICAL NAME BLOCK FOR NEW LOGICAL NAME TABLE.
      01D9 973 : R5 = ACCESS MODE.
      01D9 974 : R6 = ADDRESS OF PROTECTION MASK.
      01D9 975 : R7 = ATTRIBUTE BITS.
      01D9 976 : R8 = QUOTA.
      01D9 977 : R9 = ADDRESS OF PROBED AND COPIED TABLE NAME DESCRIPTOR.
      01D9 978 : R10 = ADDRESS OF PROBED AND COPIED LOGICAL NAME DESCRIPTOR.
      01D9 979 : R11 = ADDRESS OF WORD TO RECEIVE TABLE NAME LENGTH.
      01D9 980 :
      01D9 981
      50 0A A4 9E 01D9 982 110$: MOVAB LNMB$B_TYPE(R4),R0 ;POSITION TO BLOCK TYPE
      80 40 8F 90 01DD 983 :MOVAB #DYN$C_LNM,(R0)+ ;SET DATA STRUCTURE TYPE
      80 55 90 01E1 984 :MOVAB R5,(R0)+ ;SET OWNER ACCESS MODE
      01E4 985
      52 09 A1 D0 01E4 986 :MOVL LNMB$H_NAME(R1),R2 ;ADDRESS OF PARENT'S LOGICAL NAME BLOCK
      80 0C A2 D0 01E8 987 :MOVL LNMB$H_TABLE(R2),(R0)+ ;STORE DIRECTORY TABLE HEADER ADDRESS
      01EC 988
      80 08 57 89 01EC 989 :BISB3 R7,#LNMB$M_TABLE,(R0)+ ;STORE NAME ATTRIBUTES
      01F0 990
      01F0 991 :
      01F0 992 : IF THE CALLER HAS SPECIFIED A LOGICAL NAME STRING THEN THAT STRING BECOMES
      01F0 993 : THE NAME OF THE LNMB FOR THE NEW LOGICAL NAME TABLE ENTRY BY MOVING IT INTO
      01F0 994 : THE LOGICAL NAME BLOCK. OTHERWISE, THE UNIQUE NAME OF THE LNMB IS A
      01F0 995 : CONSTRUCTED QUANTITY OF FIXED (12 BYTES) SIZE.
      01F0 996 :
      01F0 997
      5A D5 01F0 998 :TSTL R10 ;LOGICAL NAME STRING SPECIFIED?
      2A 13 01F2 999 :BEQL 120$ ;NO - BRANCH TO CONSTRUCT UNIQUE NAME
      80 6A 90 01F4 1000 :MOVAB (R10),(R0)+ ;STORE LENGTH OF NAME
      7E 54 7D 01F7 1001 :MOVQ R4,-(SP) ;SAVE NEEDED REGISTERS OVER MOVTC
      51 DD 01FA 1002 :PUSHL R1
      00 04 BA 6A 2F 01FC 1003 :MOVTC (R10),a4(R10),#0,- ;CHECK FOR PROPER TABLE NAME SYNTAX AND
      00000000'EF 0201 1004 :EXESLNM_SYNTAX_DAT,- ;AT THE SAME TIME MOVE THE TABLE NAME
      60 6A 0206 1005 : (R10),(R0) ;INTO THE LOGICAL NAME TABLE ENTRY
      0B 1D 0208 1006 :BVS 115$ ;BRANCH IF TABLE NAME HAS INVALID CHARS
      50 55 D0 020A 1007 :MOVL R5,R0 ;POSITION PAST LNMB NAME STRING
      51 8E D0 020D 1008 :POPL R1 ;RESTORE SAVED REGISTERS
      54 7D 0210 1009 :MOVQ (SP)+,R4
      46 11 0213 1010 :BRB 130$ ;BRANCH AROUND UNIQUE NAME CONSTRUCTION
      0215 1011
      50 015C 32 BA 0215 1012 115$: POPR #^M<R1,R4,R5> ;RESTORE REGISTERS
      8F 3C 0217 1013 :MOVZWL #SS$_IVLOGTAB,R0 ;INVALID TABLE NAME STRING SPECIFIED
      B3 11 021C 1014 :BRB 105$ ;SO GO RETURN THE APPROPRIATE ERROR
      021E 1015
      80 80 14 90 021E 1016 120$: MOVAB #LNMB_HEX_TAB_LEN,(R0)+ ;STORE LENGTH OF NAME
      244D4E4C 8F D0 0221 1017 :MOVL #^A/CNM$7,(R0)+ ;STORE BEGINNING OF NAME
      53 1C D0 0228 1018 :MOVL #<8-1>*4,R3 ;STARTING NIBBLE POSITION
```



```
52 54 04 53 EF 022B 1019 125$: EXTZV R3,#4,R4,R2 ;EXTRACT HEX DIGIT
80 FDCB CF42 90 0230 1020 MOVB HEXDIGITS[R2],(R0)+ ;STORE ASCII EQUIVALENT
53 04 C2 0236 1021 SUBL #4,R3 ;ADJUST POSITION TO SUCCEEDING NIBBLE
FO 18 0239 1022 BGEQ 125$ ;ITERATE OVER 8 DIGITS
54 DD 023B 1023 PUSHL R4 ;SAVE ADDR OF LNMB
54 04 AE DO 023D 1024 MOVL 4(SP),R4 ;GET PCB ADDR
54 64 A4 DO 0241 1025 MOVL PCB$EPIID(R4),R4 ;GET PID
53 1C DO 0245 1026 MOVL #<8-15*4,R3 ;STARTING NIBBLE POSITION
52 54 04 53 EF 0248 1027 126$: EXTZV R3,#4,R4,R2 ;EXTRACT HEX DIGIT
80 FDAE CF42 90 024D 1028 MOVB HEXDIGITS[R2],(R0)+ ;STORE ASCII EQUIVALENT
53 04 C2 0253 1029 SUBL #4,R3 ;ADJUST POSITION TO SUCCEEDING NIBBLE
FO 18 0256 1030 BGEQ 126$ ;ITERATE OVER 8 DIGITS
54 8E DO 0258 1031 MOVL (SP)+,R4 ;RESTORE LNMB ADDR
025B 1032 :
025B 1033 : FILL IN THE LNMX PORTION OF THE LOGICAL NAME BLOCK FOR THE NEW LOGICAL NAME
025B 1034 : TABLE ENTRY. FOR LOGICAL NAME TABLES THE SOLE TRANSLATION CONSISTS OF THE
025B 1035 : TABLE HEADER.
025B 1036 :
025B 1037 :
80 80 02 90 025B 1038 130$: MOVB #LNMX$M_TERMINAL,(R0)+ ;STORE TRANSLATION ATTRIBUTES
80 82 8F 90 025E 1039 MOVB #LNMX$C_TABLE,(R0)+ ;STORE TRANSLATION INDEX (SPECIAL)
80 80 B4 0262 1040 CLRW (R0)+ ;INITIALIZE HASH CODE LOCATION TO 0
80 25 90 0264 1041 MOVB #LNMT$K_LENGTH,(R0)+ ;STORE LENGTH OF TABLE HEADER
0267 1042 :
0267 1043 : FILL IN THE LNMT$ PORTION OF THE LOGICAL NAME BLOCK FOR THE NEW LOGICAL NAME
0267 1044 : TABLE ENTRY. THE TABLE HEADER OF THE NEW ENTRY CONSTITUTE THE SOLE
0267 1045 : TRANSLATION OF THE NEW LOGICAL NAME TABLE ENTRY.
0267 1046 :
0267 1047 :
0267 1048 :
53 52 50 DO 0267 1049 MOVL R0,R2 ;SAVE ADDRESS OF TABLE HEADER
57 10 9C 026A 1050 ROTL #16,R7,R3 ;TABLE ATTRIBUTES TO LOW BYTE OF R3
80 53 90 026E 1051 MOVB R3,(R0)+ ;STORE TABLE HEADER ATTRIBUTES
0271 1052 :
80 01 A1 DO 0271 1053 MOVL LNMT$H_HASH(R1),(R0)+ ;HASH TABLE ADDRESS IS SAME AS PARENTS
0275 1054 :
80 80 D4 0275 1055 CLRL (R0)+ ;ZERO OBJECT RIGHTS BLOCK ADDR FOR NOW
80 64 9E 0277 1056 MOVAB (R4),(R0)+ ;STORE CONTAINING LNMB BLOCK ADDRESS
80 51 DO 027A 1057 MOVL R1,(R0)+ ;STORE PARENT TABLE HEADER ADDRESS
80 80 7C 027D 1058 CLRQ (R0)+ ;STORE CHILD TABLE HEADER ADDRESS
027F 1059 :STORE SIBLING TABLE HEADER ADDRESS
027F 1060 :
80 19 A1 DO 027F 1061 MOVL LNMT$H_QTABLE(R1),(R0)+ ;ASSUME QUOTA HOLDER IS SAME AS PARENTS
60 58 DO 0283 1062 MOVL R8,(R0)+ ;STORE TABLE QUOTA
04 13 0286 1063 BEQL 135$ ;BRANCH IF POOLED QUOTA
19 A2 52 DO 0288 1064 MOVL R2,LNMT$H_QTABLE(R2) ;NEW ENTRY IS A QUOTA TABLE
80 80 DO 028C 1065 135$: MOVL (R0)+,(R0)+ ;STORE QUOTA BYTES REMAINING (= QUOTA)
028F 1066 :
028F 1067 : FILL IN THE NEXT LNMX PORTION OF THE LOGICAL NAME BLOCK FOR THE NEW LOGICAL
028F 1068 : NAME TABLE ENTRY. THE LAST TRANSLATION BLOCK CONSISTS SOLELY OF A FLAGS
028F 1069 : FIELD, AND IS MARKED WITHIN THIS FLAGS FIELD AS THE LAST LNMX.
028F 1070 :
028F 1071 :
028F 1072 :
80 04 90 028F 1073 MOVB #LNMX$M_XEND,(R0)+ ;STORE END FLAG
0292 1074 :
0292 1075 :
```



```
0292 1076 : INITIALIZE THE OBJECT RIGHTS BLOCK WHICH EXISTS FOR ALL SHAREABLE LOGICAL NAME
0292 1077 : TABLES. PROCESS-PRIVATE LOGICAL NAME TABLES DO NOT REQUIRE SUCH A ORB BECAUSE
0292 1078 : BECAUSE PROTECTION CHECKING IS NOT REQUIRED, AND IS NEVER PERFORMED ON THEM.
0292 1079 :
0292 1080 :
00      00      E1 0292 1081      BBC      #LNMT$SV SHAREABLE, - :IS PARENT LOGICAL NAME TABLE SHAREABLE?
03 61      0292 1082      LNMT$B_FLAGS(R1),137$ :IF NOT, SKIP INITIALIZATION OF ORB
56 FD67' 30 0296 1083      BSBW      LNMT$INIT_PROT :INITIALIZE TABLE'S OBJECT RIGHTS BLOCK
52 52      DO 0299 1084 137$:      MOVL      R2,R6 :SAVE TABLE HEADER ADDRESS
029C 1085 :
029C 1086 :
029C 1087 : SET THE TEMPORARY BIT LNMT$SV NODELETE IN THE FLAGS BYTE OF THE LNMB BLOCK OF
029C 1088 : THE NEW LOGICAL NAME TABLE ENTRY'S PARENT, GRANDPARENT ETC... THIS WILL
029C 1089 : PREVENT THE NEW ENTRY FROM BEING INSERTED IF ITS INSERTION WOULD RESULT IN
029C 1090 : THE DELETION OF ANY LOGICAL NAME TABLE ENTRY IN ITS DIRECT LINE OF DESCENT;
029C 1091 : AND THUS, THE DELETION OF ITS PARENT TABLE.
029C 1092 :
029C 1093 :
01      01      E0 029C 1094 140$:      BBS      #LNMT$SV DIRECTORY, - :SYSTEM/PROCESS DIRECTORY TABLE?
OE 61      029E 1095      LNMT$B_FLAGS(R1),150$ :YES - GO INSERT NEW TABLE ENTRY
52 09 A1      DO 02A0 1096      MOVL      LNMT$SL_NAME(R1),R2 :ADDRESS OF PARENT'S LNMB BLOCK
10 10      88 02A4 1097      BISB2      #LNMT$SV NODELETE, - :SET THE TEMPORARY BIT BLOCKING DELETION
51 10 A2      02A6 1098      LNMT$B_FLAGS(R2) :OF THIS LOGICAL NAME TABLE ENTRY
OD A1      DO 02A8 1099      MOVL      LNMT$C_PARENT(R1),R1 :NO - RETRIEVE PARENT'S TABLE HEADER
EE 11      02AC 1100      BRB      140$ :ADDRESS AND CONTINUE
02AE 1101 :
02AE 1102 :
02AE 1103 : AT THIS POINT ALL CHECKS HAVE BEEN MADE, AND THE TABLE STRUCTURES MAY NOW
02AE 1104 : BE MODIFIED FOR THE FIRST TIME. INSERT THE NEW LOGICAL NAME TABLE ENTRY AND
02AE 1105 : THEN CLEAR THE TEMPORARY DO NOT DELETE BIT, LNMT$SV_NODElete REGARDLESS OF THE
02AE 1106 : OUTCOME OF THE INSERTION.
02AE 1107 :
02AE 1108 : THIS INSERTION MAY TAKE ONE OF THREE FORMS:
02AE 1109 :
02AE 1110 : 1. THE NEW LOGICAL NAME TABLE ENTRY MAYBE INSERTED AS A NEW LOGICAL NAME
02AE 1111 : TABLE. FOR THIS CASE TO OCCUR THE FOLLOWING CONDITIONS MUST HOLD TRUE.
02AE 1112 :
02AE 1113 : A. THERE IS NO EXISTING LOGICAL NAME TABLE ENTRY IN THE SAME DIRECTORY
02AE 1114 : (PROCESS OR SYSTEM) WITH THE SAME NAME AND ACCESS MODE.
02AE 1115 :
02AE 1116 : B. THERE IS NO EXISTING LOGICAL NAME TABLE ENTRY IN THE SAME DIRECTORY
02AE 1117 : (PROCESS OR SYSTEM) WITH THE SAME NAME AND AN INNER ACCESS MODE THAT
02AE 1118 : DOES NOT ALLOW ALIASES.
02AE 1119 :
02AE 1120 : 2. THE LOGICAL NAME TABLE ENTRY MAYBE "MAPPED" INTO AN EXISTING LOGICAL NAME
02AE 1121 : TABLE ENTRY. FOR THIS CASE TO OCCUR THE FOLLOWING CONDITIONS MUST BE MET.
02AE 1122 :
02AE 1123 : A. THE LNMT$V_CREATE_IF BIT MUST HAVE BEEN SET IN THE ATTRIBUTES FIELD.
02AE 1124 :
02AE 1125 : B. THERE MUST EXIST A LOGICAL NAME TABLE ENTRY WITH THE SAME NAME AND
02AE 1126 : ACCESS MODE WITHIN THE SAME DIRECTORY (PROCESS OR SYSTEM).
02AE 1127 :
02AE 1128 : 3. THE LOGICAL NAME TABLE ENTRY MAYBE INSERTED SUPERSEDING AN EXISTING ENTRY
02AE 1129 : IN THE SAME DIRECTORY (PROCESS OR SYSTEM) WITH THE SAME NAME AND ACCESS
02AE 1130 : MODE. THE OLD LOGICAL NAME TABLE ENTRY TOGETHER WITH ITS ENTIRE HIERARCHY
02AE 1131 : OF LOGICAL NAMES AND LOGICAL NAME TABLE ENTRIES IS DELETED, PROVIDED OF
02AE 1132 : COURSE, THAT THE OLD ENTRY WAS FOR A LOGICAL NAME TABLE. THE CONDITIONS
```



```
02AE 1133 : WHICH MUST BE MET FOR THIS CASE TO OCCUR ARE:
02AE 1134 :
02AE 1135 : A. THE LNMSV_CREATE_IF BIT MUST NOT HAVE BEEN SET IN THE ATTRIBUTES FIELD.
02AE 1136 :
02AE 1137 : B. THERE MUST EXIST A LOGICAL NAME TABLE ENTRY WITH THE SAME NAME AND
02AE 1138 : ACCESS MODE WITHIN THE SAME DIRECTORY (PROCESS OR SYSTEM).
02AE 1139 :
02AE 1140 : IF A CASE 1 OR 3 INSERTION IS PERFORMED, AND THE NEW LOGICAL NAME TABLE ENTRY
02AE 1141 : DOES NOT ALLOW ALIASES, THEN ANY LOGICAL NAME TABLE ENTRIES IN THE SAME
02AE 1142 : DIRECTORY (PROCESS OR SYSTEM) WITH THE SAME NAME BUT AT AN OUTER ACCESS MODES
02AE 1143 : ARE DELETED ALONG WITH THEIR HIERARCHY OF LOGICAL NAMES AND LOGICAL NAME
02AE 1144 : TABLE ENTRIES, PROVIDED THEY TOO ARE LOGICAL NAME TABLES.
02AE 1145 :
02AE 1146 :
51 54 DO 02AE 1147 150$: MOVL R4,R1 ;ADDRESS OF NEW LOGICAL NAME TABLE ENTRY
52 57 DO 02B1 1148 MOVL R7,R2 ;ATTRIBUTES
53 FD49' 30 02B4 1149 BSBW LNMSINSLOGTAB ;INSERT NEW LOGICAL NAME TABLE ENTRY
53 51 DO 02B7 1150 MOVL R1,R3 ;SAVE LNMB ADDRESS OF MAPPED-TO ENTRY
02BA 1151 ;IF SUCH A MAPPING HAS TAKEN PLACE
02BA 1152 :
51 OD A6 DO 02BA 1153 MOVL LNMTSL_PARENT(R6),R1 ;RETRIEVE PARENT'S TABLE HEADER
01 EO 02BE 1154 155$: BBS #LNMTSL_DIRECTORY,- ;SYSTEM/PROCESS DIRECTORY TABLE?
0E 61 02C0 1155 ;YES - GO CHECK INSERTION
52 09 A1 DO 02C2 1156 MOVL LNMTSL_NAME(R1),R2 ;ADDRESS OF PARENT'S LNMB BLOCK
10 8A 02C6 1157 BICB2 #LNMB$M_NODELETE,- ;CLEAR THE TEMPORARY BIT BLOCKING
02C8 1158 LNMB$B_FLAGS(R2) ;DELETION OF THIS LNMB
51 OD A1 DO 02CA 1159 MOVL LNMTSL_PARENT(R1),R1 ;NO - RETRIEVE PARENT'S TABLE HEADER
EE 11 02CE 1160 BRB 155$ ; ADDRESS AND CONTINUE
02D0 1161 :
08 50 DD 02D0 1162 160$: PUSHL R0 ;SAVE STATUS
50 50 E8 02D2 1163 BLBS R0,170$ ;BRANCH ON SUCCESS
50 54 DO 02D5 1164 MOVL R4,R0 ;LOGICAL NAME BLOCK FOR NEW TABLE ENTRY
FD25' 30 02D8 1165 BSBW LNMSDELBLK ;DELETE BLOCK CONTAINING NEW TABLE ENTRY
33 11 02DB 1166 BRB 190$ ;JOIN MAIN EXIT - STATUS ON STACK
02DD 1167 :
02DD 1168 :
02DD 1169 : AT THIS POINT THE NEW LOGICAL NAME TABLE HAS SUCCESSFULLY BEEN INSERTED.
02DD 1170 : FILL IN ANY SPECIFIED OUTPUT PARAMETERS (TABLEN AND/OR TABNAM) BEFORE
02DD 1171 : RETURNING THE STATUS TO THE CALLER OF THE SYSTEM SERVICE. IF THE NEW TABLE
02DD 1172 : ENTRY WAS JUST MAPPED TO AN EXISTING TABLE ENTRY, THEN THE LOGICAL NAME BLOCK
02DD 1173 : CONTAINING THE NEW TABLE ENTRY IS DELETED BEFORE RETURNING.
02DD 1174 :
02DD 1175 :
50 01 D1 02DD 1176 170$: CMPL #SS$-NORMAL,R0 ;WAS NEW ENTRY MAPPED TO EXISTING ONE?
0B 12 02E0 1177 BNEQ 175$ ;BRANCH IF NOT
50 54 DO 02E2 1178 MOVL R4,R0 ;ADDRESS OF NEW ENTRY
53 DD 02E5 1179 PUSHL R3 ;SAVE ADDRESS OF ENTRY MAPPED TO
FD16' 30 02E7 1180 BSBW LNMSDELBLK ;DELETE NEW ENTRY
53 8ED0 02EA 1181 POPL R3 ;ADDRESS OF ENTRY MAPPED TO
02ED 1182 :
51 11 A4 9E 02ED 1183 175$: MOVAB LNMB$T_NAME(R4),R1 ;ADDRESS OF TABLE NAME COUNTED STRING
50 81 9A 02F1 1184 MOVZBL (R1)+,R0 ;LENGTH OF NAME STRING
02F4 1185 :
5B D5 02F4 1186 TSTL R11 ;RETURN LENGTH?
03 13 02F6 1187 BEQL 180$ ;BRANCH IF NO
6B 50 B0 02F8 1188 MOVW R0,(R11) ;RETURN LENGTH
02FB 1189 :
```



|       |      |       |      |        |        |          |                      |   |
|-------|------|-------|------|--------|--------|----------|----------------------|---|
|       | 59   | D5    | 02FB | 1190   | 180\$: | TSTL     | R9                   | ;WANT LOGICAL NAME TABLE NAME RETURNED? |
|       | 11   | 13    | 02FD | 1191   |        | BEQL     | 190\$                | ;BRANCH IF NO                           |
| 69    | 50   | B1    | 02FF | 1192   |        | CMPW     | R0,(R9)              | ;ENOUGH ROOM?                           |
|       | 07   | 14    | 0302 | 1193   |        | BGTR     | 185\$                | ;BRANCH IF NOT ENOUGH ROOM              |
| 04 B9 | 61   | 50    | 0304 | 1194   |        | MOV C3   | R0,(R1),a4(R9)       | ;RETURN NAME STRING                     |
|       | 05   | 11    | 0309 | 1195   |        | BRB      | 190\$                |   |
| 6E    | 0214 | 8F    | 030B | 1196   | 185\$: | MOVZWL   | #SS\$_RESULTOVF,(SP) | ;NOT ENOUGH ROOM FOR NAME               |
|       |      |       | 0310 | 1197   |        |          |                      |   |
| 54    | 04   | AE    | D0   | 0310   | 1198   | 190\$:   | MOVL                 | 4(SP),R4                                |
|       |      | FCE9' | 30   | 0314   | 1199   |          | BSBW                 | LNMS\$UNLOCK                            |
|       | 50   | 8ED0  | 0317 | 1200   |        | POPL     | R0                   | ;RETRIEVE PCB ADDRESS                   |
|       |      | 04    | 031A | 1201   |        | RET      |                      | ;UNLOCK TABLES                          |
|       |      |       | 031B | 1202   |        |          |                      | ;RESTORE STATUS                         |
|       |      |       | 031B | 1203   |        |          |                      | ;RETURN TO CALLER                       |
|       |      |       | 031B | 1204 ; |        | .DISABLE | LSB                  |   |
|       |      |       |      |        |        | .PAGE    |                      |   |

```

031B 1206 .SBTTL EXESCRELM - CREATE LOGICAL NAME
031B 1207 :+
031B 1208 : EXESCRELM - CREATE LOGICAL NAME
031B 1209 :
031B 1210 : THIS SERVICE PROVIDES THE CAPABILITY TO CREATE A LOGICAL NAME ENTRY WITH
031B 1211 : SOME NUMBER OF EQUIVALENCE STRINGS.
031B 1212 :
031B 1213 : INPUTS:
031B 1214 :
031B 1215 : CNATTR(AP) = ADDRESS OF LOGICAL NAME ATTRIBUTES.
031B 1216 : CNTABNAM(AP) = ADDRESS OF TABLE NAME STRING DESCRIPTOR.
031B 1217 : CNLOGNAM(AP) = ADDRESS OF LOGICAL NAME STRING DESCRIPTOR.
031B 1218 : CNACMODE(AP) = ADDRESS OF ACCESS MODE OF LOGICAL NAME TO BE CREATED.
031B 1219 : CNITMLST(AP) = ADDRESS OF ITEM LIST DEFINING TRANSLATIONS.
031B 1220 :
031B 1221 : R4 = CURRENT PROCESS PCB ADDRESS.
031B 1222 :
031B 1223 : OUTPUTS:
031B 1224 :
031B 1225 : R0 LOW BIT CLEAR INDICATES FAILURE TO CREATE LOGICAL NAME TABLE ENTRY.
031B 1226 :
031B 1227 : R0 = SS$ ACCVIO - LOGICAL NAME DESCRIPTOR, LOGICAL NAME STRING,
031B 1228 : TABLE NAME DESCRIPTOR, TABLE NAME STRING, AN ITEM IN THE
031B 1229 : ITEM LIST, AN INDEX ITEM BUFFER, AN ATTRIBUTES ITEM
031B 1230 : BUFFER, A STRING ITEM BUFFER, CANNOT BE READ BY CALLING
031B 1231 : ACCESS MODE. TABLE ITEM BUFFER, TABLE ITEM SIZE BUFFER
031B 1232 : CANNOT BE WRITTEN BY CALLING ACCESS MODE.
031B 1233 :
031B 1234 : R0 = SS$ BADPARAM - INVALID ATTRIBUTE, ACCESS MODE, ITEM TYPE,
031B 1235 : ITEM LENGTH, ITEM SPECIFIED. LOGICAL NAME DESCRIPTOR,
031B 1236 : TABLE NAME DESCRIPTOR NOT SPECIFIED.
031B 1237 :
031B 1238 : R0 = SS$ DUPLNAM - ATTEMPT MADE TO SUPERSEDE NON-ALIASABLE
031B 1239 : LOGICAL NAME TABLE ENTRY.
031B 1240 :
031B 1241 : R0 = SS$ EXLNMQUOTA - INSUFFICIENT QUOTA AVAILABLE IN THE QUOTA
031B 1242 : TABLE FOR THE CREATION OF THE NEW LOGICAL NAME TABLE
031B 1243 : ENTRY.
031B 1244 :
031B 1245 : R0 = SS$ INSMEM - SUFFICIENT SYSTEM DYNAMIC MEMORY DOES NOT
031B 1246 : EXIST TO ALLOCATE LOGICAL NAME TABLE ENTRY AND
031B 1247 : IMPLICIT RESOURCE WAIT IS NOT ENABLED.
031B 1248 :
031B 1249 : R0 = SS$ IVLOGNAM - ZERO OR GREATER THAN MAXIMUM LENGTH
031B 1250 : LOGICAL NAME STRING, TABLE NAME STRING, OR EQUIVALENCE
031B 1251 : STRING SPECIFIED, OR THE LOGICAL NAME IS TO BE CONTAINED
031B 1252 : WITHIN A DIRECTORY TABLE AND IS EITHER GREATER THAN 31
031B 1253 : CHARACTERS IN SIZE OR HAS INVALID CHARACTERS FOR SUCH
031B 1254 : NAMES.
031B 1255 :
031B 1256 : R0 = SS$ _IVLOGTAB - INVALID LOGICAL NAME TABLE NAME SPECIFIED.
031B 1257 :
031B 1258 : R0 = SS$ _NOLOGTAB - LOGICAL NAME TABLE SPECIFIED DOES NOT EXIST.
031B 1259 :
031B 1260 : R0 = SS$ TOOMANYLNM - TOO MANY LEVELS OF RECURSION IN SEARCH
031B 1261 : FOR LOGICAL NAME TABLE.
031B 1262 :

```



```
031B 1263 : RO LOW BIT SET INDICATES SUCCESSFUL COMPLETION.
031B 1264 :
031B 1265 : RO = SSS$ BUFFEROVF - REQUEST SUCCESSFULLY COMPLETED. AN ITEM
031B 1266 : BUFFER IS NOT LARGE ENOUGH TO HOLD REQUESTED DATA.
031B 1267 :
031B 1268 : RO = SSS$ NORMAL - NORMAL COMPLETION, NEW ENTRY ENTERED IN
031B 1269 : SPECIFIED LOGICAL NAME TABLE.
031B 1270 :
031B 1271 : RO = SSS$ SUPERSEDE - NORMAL COMPLETION, NEW ENTRY SUPERSEDED
031B 1272 : PREVIOUS ENTRY IN SPECIFIED LOGICAL NAME TABLE.
031B 1273 :
031B 1274 : SIDE EFFECTS:
031B 1275 :
031B 1276 : THIS ROUTINE EXITS AT IPL 2, AND MUST CONTINUE TO DO SO, BECAUSE
031B 1277 : IT IS CALLED AT SYSTEM INITIALIZATION TIME.
031B 1278 :
031B 1279 :-
031B 1280
00000005 1281 .PSECT Y$EXEPAGED
OFFC 0005 1282 .ENTRY EXESCRELM, ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>
031F' 31 0007 1283 BRW EXECRELM
000A 1284
0000031B 1285 .PSECT YF$$LNM
031B 1286 .ENABLE LSB
031B 1287
031B 1288 :
031B 1289 : ERROR MESSAGES AND RETURNS
031B 1290 :
031B 1291
50 0C 3C 031B 1292 9000$: MOVZWL #SS$_ACCVIO,R0 ;ACCESS VIOLATION
04 031E 1293 RET
50 14 3C 031F 1294 9010$: MOVZWL #SS$_BADPARAM,R0 ;BAD SYSTEM SERVICE PARAMETER
04 0322 1295 RET
50 0124 8F 3C 0323 1296 9020$: MOVZWL #SS$_INSFMEM,R0 ;INSUFFICIENT MEMORY
04 0328 1297 9030$: RET
0329 1298
0329 1299 EXECRELM:
0329 1300
0329 1301 :
0329 1302 : VALIDATE AND COPY PARAMETERS AS NECESSARY. REGISTER ASSIGNMENT FOR THE
0329 1303 : PARAMETERS ARE AS FOLLOWS:
0329 1304 :
0329 1305 : R5 = ACCESS MODE.
0329 1306 : R7 = ATTRIBUTE BITS.
0329 1307 : R9 = ADDRESS OF PROBED AND COPIED TABLE NAME DESCRIPTOR.
0329 1308 : R10 = ADDRESS OF PROBED AND COPIED LOGICAL NAME DESCRIPTOR.
0329 1309 : R11 = ADDRESS OF START OF ITEM LIST.
0329 1310 :
0329 1311 : ---
0329 1312 :
50 10 AC D0 0329 1313 MOVL CNACMODE(AP),R0 ;GET SPECIFIED ACCESS MODE
14 13 032D 1314 BEQL 50$ ;BRANCH IF NOT PRESENT
032F 1315 IFNORD #1,(R0),9000$ ;CHECK READ ACCESS TO BYTE
50 60 9A 0335 1316 MOVZBL (R0),R0 ;GET VALUE
50 03 D1 0338 1317 CMPL #PSL$_C_USER,R0 ;CHECK FOR VALID ACCESS MODE
E2 1F 033B 1318 BLSSU 9010$ ;INVALID ACCESS MODE
033D 1319
```

```
033D 1320 :  
033D 1321 : IF THE ACCESS MODE OF THE NEW LOGICAL NAME WAS EXPLICITELY SPECIFIED AND THE  
033D 1322 : CALLER HAS THE SYSNAM PRIVILEGE, THEN THE NEW LOGICAL NAME IS CREATED WITH  
033D 1323 : THE SPECIFIED ACCESS MODE. OTHERWISE, THE ACCESS MODE OF THE CALLER IS  
033D 1324 : MAXIMIZED WITH ANY EXPLICITELY SPECIFIED ACCESS MODE AND USED TO CREATE THE  
033D 1325 : NEW LOGICAL NAME.  
033D 1326 :  
033D 1327 :  
033D 1328 :  
00000000'GF 16 0343 1329 50$: IFPRIV SYSNAM,60$ ;PRIVILEGE  
55 50 D0 0349 1330 60$: JSB G^EXES$MAXACMODE ;MAXIMIZED WITH MODE OF CALLER TO  
57 04 AC D0 034C 1331 MOVL R0,R5 ;DETERMINE ACCESS MODE OF NEW TABLE  
12 13 034C 1332 MOVL CNATTR(AP),R7 ;TABLE ATTRIBUTES  
0350 1333 BEQL 200$ ;BRANCH IF NOT PRESENT  
57 57 67 D0 0352 1334 IFNORD #4,(R7),9000$ ;CHECK READ ACCESS  
57 FFFFFFFF8 8F D3 0358 1335 MOVL (R7),R7 ;GET VALUE  
035B 1336 BITL #^C<- ;  
0362 1337 LNMSM_CONFINE! - ;CONFINE TO PROCESS  
0362 1338 LNMSM_CRELOG! - ;$CRELOG USED TO CREATE NAME  
0362 1339 LNMSM_NO_ALIAS - ;DO NOT ALLOW ALIASES  
0362 1340 >R7  
BB 12 0362 1341 BNEQ 9010$ ;INVALID TABLE ATTRIBUTES  
0364 1342  
5A 0C AC D0 0364 1343 200$: MOVL CNLOGNAM(AP),R10 ;ADDRESS OF LOGICAL NAME DESCRIPTOR  
B5 13 BEQL 9010$ ;ERROR IF NOT PRESENT  
036A 1345 IFNORD #8,(R10),9000$ ;CHECK ACCESS TO DESCRIPTOR  
50 6A 7E 0370 1346 MOVAQ (R10),R0 ;ADDRESS OF DESCRIPTOR  
FC8A' 30 0373 1347 BSBW LNMS$PROBER ;PROBE LOGICAL NAME STRING  
AF 50 E9 0376 1348 BLBC R0,9030$ ;BRANCH IF CAN'T READ OR NOT PRESENT  
7E 51 7D 0379 1349 MOVQ R1,-(SP) ;SAVE LOGICAL NAME DESCRIPTOR  
5A 5E D0 037C 1350 MOVL SP,R10 ;ADDRESS OF LOGICAL NAME DESCRIPTOR  
037F 1351  
59 08 AC D0 037F 1352 MOVL CNTABNAM(AP),R9 ;ADDRESS OF TABLE NAME DESCRIPTOR  
9A 13 0383 1353 BEQL 9010$ ;ERROR IF NOT PRESENT  
0385 1354 IFNORD #8,(R9),9000$ ;CHECK ACCESS TO DESCRIPTOR  
50 69 7E 038B 1355 MOVAQ (R9),R0 ;SET UP CALL  
FC6F' 30 038E 1356 BSBW LNMS$PROBER ;PROBE TABLE NAME STRING  
94 50 E9 0391 1357 BLBC R0,9030$ ;BRANCH IF CAN'T READ OR NOT PRESENT  
7E 51 7D 0394 1358 MOVQ R1,-(SP) ;SAVE TABLE NAME DESCRIPTOR  
59 5E D0 0397 1359 MOVL SP,R9 ;ADDRESS OF TABLE NAME DESCRIPTOR  
039A 1360  
039A 1361 :  
039A 1362 : PROBE AND VERIFY THE ITEM LIST. THIS IS THE FIRST OF TWO PASSES DOWN  
039A 1363 : THE ITEM LIST. THIS FIRST PASS IS BEING DONE TO ACCUMULATE  
039A 1364 : INFORMATION AS TO THE NUMBER OF TRANSLATION STRINGS BEING DEFINED AND  
039A 1365 : THEIR COLLECTIVE SIZE FOR USE IN DETERMINING THE AMOUNT OF SPACE TO  
039A 1366 : ALLOCATE FOR THE NEW LOGICAL NAME TABLE ENTRY. VALID ITEM TYPES FOR  
039A 1367 : THIS SYSTEM SERVICE ARE:  
039A 1368 :  
039A 1369 : ATTRIBUTES - ATTRIBUTES FOR NEXT TRANSLATION STRING  
039A 1370 : INDEX - INDEX TO BE ASSIGNED TO NEXT TRANSLATION STRING  
039A 1371 : STRING - EQUIVALENCE STRING  
039A 1372 : TABLE - LOGICAL NAME TABLE NAME (OUTPUT ITEM)  
039A 1373 : LNMBADDR - LOGICAL NAME LNMB ADDRESS (OUTPUT ITEM)  
039A 1374 :  
039A 1375 :  
7E 7C 039A 1376 CLRQ -(SP) ;CLEAR COUNTERS
```



| Address | Hex | Op | Op2 | Op3 | Op4 | Op5 | Op6 | Op7 | Op8 | Op9 | Op10 | Op11 | Op12 | Op13 | Op14 | Op15 | Op16 | Op17 | Op18 | Op19 | Op20 | Op21 | Op22 | Op23 | Op24 | Op25 | Op26 | Op27 | Op28 | Op29 | Op30 | Op31 | Op32 | Op33 | Op34 | Op35 | Op36 | Op37 | Op38 | Op39 | Op40 | Op41 | Op42 | Op43 | Op44 | Op45 | Op46 | Op47 | Op48 | Op49 | Op50 | Op51 | Op52 | Op53 | Op54 | Op55 | Op56 | Op57 | Op58 | Op59 | Op60 | Op61 | Op62 | Op63 | Op64 | Op65 | Op66 | Op67 | Op68 | Op69 | Op70 | Op71 | Op72 | Op73 | Op74 | Op75 | Op76 | Op77 | Op78 | Op79 | Op80 | Op81 | Op82 | Op83 | Op84 | Op85 | Op86 | Op87 | Op88 | Op89 | Op90 | Op91 | Op92 | Op93 | Op94 | Op95 | Op96 | Op97 | Op98 | Op99 | Op100 | Op101 | Op102 | Op103 | Op104 | Op105 | Op106 | Op107 | Op108 | Op109 | Op110 | Op111 | Op112 | Op113 | Op114 | Op115 | Op116 | Op117 | Op118 | Op119 | Op120 | Op121 | Op122 | Op123 | Op124 | Op125 | Op126 | Op127 | Op128 | Op129 | Op130 | Op131 | Op132 | Op133 | Op134 | Op135 | Op136 | Op137 | Op138 | Op139 | Op140 | Op141 | Op142 | Op143 | Op144 | Op145 | Op146 | Op147 | Op148 | Op149 | Op150 | Op151 | Op152 | Op153 | Op154 | Op155 | Op156 | Op157 | Op158 | Op159 | Op160 | Op161 | Op162 | Op163 | Op164 | Op165 | Op166 | Op167 | Op168 | Op169 | Op170 | Op171 | Op172 | Op173 | Op174 | Op175 | Op176 | Op177 | Op178 | Op179 | Op180 | Op181 | Op182 | Op183 | Op184 | Op185 | Op186 | Op187 | Op188 | Op189 | Op190 | Op191 | Op192 | Op193 | Op194 | Op195 | Op196 | Op197 | Op198 | Op199 | Op200 | Op201 | Op202 | Op203 | Op204 | Op205 | Op206 | Op207 | Op208 | Op209 | Op210 | Op211 | Op212 | Op213 | Op214 | Op215 | Op216 | Op217 | Op218 | Op219 | Op220 | Op221 | Op222 | Op223 | Op224 | Op225 | Op226 | Op227 | Op228 | Op229 | Op230 | Op231 | Op232 | Op233 | Op234 | Op235 | Op236 | Op237 | Op238 | Op239 | Op240 | Op241 | Op242 | Op243 | Op244 | Op245 | Op246 | Op247 | Op248 | Op249 | Op250 | Op251 | Op252 | Op253 | Op254 | Op255 | Op256 | Op257 | Op258 | Op259 | Op260 | Op261 | Op262 | Op263 | Op264 | Op265 | Op266 | Op267 | Op268 | Op269 | Op270 | Op271 | Op272 | Op273 | Op274 | Op275 | Op276 | Op277 | Op278 | Op279 | Op280 | Op281 | Op282 | Op283 | Op284 | Op285 | Op286 | Op287 | Op288 | Op289 | Op290 | Op291 | Op292 | Op293 | Op294 | Op295 | Op296 | Op297 | Op298 | Op299 | Op300 | Op301 | Op302 | Op303 | Op304 | Op305 | Op306 | Op307 | Op308 | Op309 | Op310 | Op311 | Op312 | Op313 | Op314 | Op315 | Op316 | Op317 | Op318 | Op319 | Op320 | Op321 | Op322 | Op323 | Op324 | Op325 | Op326 | Op327 | Op328 | Op329 | Op330 | Op331 | Op332 | Op333 | Op334 | Op335 | Op336 | Op337 | Op338 | Op339 | Op340 | Op341 | Op342 | Op343 | Op344 | Op345 | Op346 | Op347 | Op348 | Op349 | Op350 | Op351 | Op352 | Op353 | Op354 | Op355 | Op356 | Op357 | Op358 | Op359 | Op360 | Op361 | Op362 | Op363 | Op364 | Op365 | Op366 | Op367 | Op368 | Op369 | Op370 | Op371 | Op372 | Op373 | Op374 | Op375 | Op376 | Op377 | Op378 | Op379 | Op380 | Op381 | Op382 | Op383 | Op384 | Op385 | Op386 | Op387 | Op388 | Op389 | Op390 | Op391 | Op392 | Op393 | Op394 | Op395 | Op396 | Op397 | Op398 | Op399 | Op400 | Op401 | Op402 | Op403 | Op404 | Op405 | Op406 | Op407 | Op408 | Op409 | Op410 | Op411 | Op412 | Op413 | Op414 | Op415 | Op416 | Op417 | Op418 | Op419 | Op420 | Op421 | Op422 | Op423 | Op424 | Op425 | Op426 | Op427 | Op428 | Op429 | Op430 | Op431 | Op432 | Op433 | Op434 | Op435 | Op436 | Op437 | Op438 | Op439 | Op440 | Op441 | Op442 | Op443 | Op444 | Op445 | Op446 | Op447 | Op448 | Op449 | Op450 | Op451 | Op452 | Op453 | Op454 | Op455 | Op456 | Op457 | Op458 | Op459 | Op460 | Op461 | Op462 | Op463 | Op464 | Op46 |
|---------|-----|----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
|---------|-----|----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|

```
03FF 1434
03FF 1435 :
03FF 1436 : RAISE IPL TO AST DELIVERY LEVEL SO THAT THERE ARE NO
03FF 1437 : INTERRUPTIONS WHILE THE NEW LOGICAL NAME ENTRY IS BEING CREATED.
03FF 1438 :
03FF 1439 :
03FF 1440 2010$: SETIPL S^#IPL$ASTDEL ;RAISE TO AST DELIVERY LEVEL
0402 1441
0402 1442 :
0402 1443 : ALLOCATE A LOGICAL NAME BLOCK FOR THE NEW LOGICAL NAME TABLE ENTRY.
0402 1444 : ASSUME THAT THE NEW LOGICAL NAME TABLE WILL BE SHAREABLE, SO ALLOCATE
0402 1445 : THE SPACE FROM SYSTEM PAGED POOL. UNTIL THE LOGICAL NAME TABLE IN
0402 1446 : WHICH THE NEW ENTRY WILL BE LOCATED IS FOUND, WHETHER THE NEW
0402 1447 : LOGICAL NAME TABLE ENTRY WILL BE IN SYSTEM POOL AND SHAREABLE OR IN
0402 1448 : P1 SPACE AND NOT SHAREABLE IS NOT KNOWN. HOWEVER, THE LOGICAL NAME
0402 1449 : MUTEX MUST BE LOCKED BEFORE A SEARCH CAN BE MADE FOR THE LOGICAL
0402 1450 : NAME TABLE, AND ONCE THE MUTEX IS LOCKED, SYSTEM POOL CAN NOT
0402 1451 : ALTHOUGH P1 POOL CAN BE ALLOCATED. THEREFORE, THE NEW LOGICAL NAME
0402 1452 : TABLE ENTRY IS ASSUMED TO BE SHAREABLE, AND IF THE LOGICAL NAME
0402 1453 : TABLE WHICH TO TO CONTAIN THE NEW ENTRY IS FOUND TO RESIDE IN
0402 1454 : SYSTEM POOL, THEN THE SYSTEM POOL ALLOCATED FOR THE NEW ENTRY IS
0402 1455 : DEALLOCATED, AND PROCESS-PRIVATE POOL IS ALLOCATED IN ITS PLACE.
0402 1456 :
0402 1457 :
51 6E 04 C5 0402 1458 MULL3 #LNM$T_XLATION,(SP),R1 ;LNM$S OVERHEAD +
51 51 8E C0 0406 1459 ADDL2 (SP)+,R1 ;TRANSLATION STRING COUNT FIELDS +
51 51 8E C0 0409 1460 ADDL2 (SP)+,R1 ;TRANSLATION STRINGS SIZES +
51 51 6A C0 040C 1461 ADDL2 (R10),R1 ;LOGICAL NAME SIZE +
040F 1462 ADDL2 #<- ;LOGICAL NAME COUNT FIELD +
0410 1463 LNM$T_NAME+1+ - ;LNM$ OVERHEAD +
0410 1464 1 - ;TRAILER BYTE =
51 13 0410 1465 >,R1 ;SIZE OF SYSTEM POOL TO ALLOCATE
0412 1466
00000000'GF 16 0412 1467 JSB G^EXESALOPAGED ;ALLOCATE THE LOGICAL NAME TABLE ENTRY
03 50 E8 0418 1468 BLBS R0,2040$ ;BRANCH IF SUFFICIENT MEMORY
FF05 31 041B 1469 BRW 9020$ ;OTHERWISE RETURN ERROR
08 A2 51 B0 041E 1470 2040$: MOVW R1,LNM$W_SIZE(R2) ;SAVE NEW BLOCK SIZE WITHIN THE BLOCK
0422 1471
0422 1472 :
0422 1473 : WRITE LOCK THE LOGICAL NAME MUTEX AND THEN POSITION TO THE LOGICAL NAME
0422 1474 : TABLE THAT IS TO CONTAIN THE NEW LOGICAL NAME TABLE ENTRY. DEALLOCATE THE NEW
0422 1475 : LNMB IF UNABLE TO POSITION TO ANY TABLE ENTRY.
0422 1476 :
0422 1477 :
14 BB 0422 1478 PUSHR #^M<R2,R4> ;SAVE ADDRESS OF PCB AND NEW LNMB
51 FBD9' 30 0424 1479 BSBW LNMB$LOCKW ;LOCK TABLES FOR WRITING
51 55 D0 0427 1480 MOVL R5,R1 ;ACCESS MODE
52 69 7D 042A 1481 MOVQ (R9),R2 ;TABLE NAME DESCRIPTOR
FBD0' 30 042D 1482 BSBW LNMB$FIRSTTAB ;SEARCH FOR SPECIFIED TABLE
54 8ED0 0430 1483 POPL R4 ;RESTORE ADDRESS OF NEW LNMB
50 DD 0433 1484 PUSHL R0 ;SAVE RETURN STATUS
03 50 E8 0435 1485 BLBS R0,2050$ ;BRANCH ON FAILURE
021B 31 0438 1486 BRW 4020$
043B 1487
043B 1488 :
043B 1489 : IF THE NEW LOGICAL NAME TABLE ENTRY WILL BE SHAREABLE BECAUSE THE LOGICAL
043B 1490 : NAME TABLE WHICH WILL CONTAIN THE NEW ENTRY HAS BEEN FOUND TO BE, THEN MAKE
```



```

043B 1491 : SURE THE NEW LOGICAL NAME TABLE ENTRY WILL NOT BE MARKED AS CONFINED AND
043B 1492 : MAKE SURE THE CALLER HAS WRITE ACCESS TO THE CONTAINING TABLE.
043B 1493
043B 1494 2050$: BBC #LNMT$V_SHAREABLE - :BRANCH IF THE CONTAINING TABLE ENTRY
043D 1495 LNMT$B_FLAGS(R1),2070$ :IS IN PROCESS-PRIVATE SPACE
57 02 CA 043F 1496 BICL2 #LNMT$M_CONFINED,R7 :SHAREABLE NAMES CAN'T BE CONFINED
0442 1497
0442 1498 MOVZBL #WRITE_ACCESS,R2 :CODE FOR ACCESS CHECK
52 02 9A 0445 1499 PUSHL R4 :SAVE LNMB PTR
54 08 AE DO 0447 1500 MOVL 8(SP),R4 :RESTORE PCB
FBB2' 30 044B 1501 BSBW LNMT$CHECK_PROT :CHECK THE PROTECTION
54 8E DO 044E 1502 MOVL (SP)+,R4 :RESTORE LNMB
41 50 E8 0451 1503 BLBS R0,2090$ :OK
6E 50 DO 0454 1504 MOVL R0,(SP) :SAVE STATUS
01FC 31 0457 1505 BRW 4020$ :AND EXIT
045A 1506
045A 1507 :
045A 1508 : IF THE LOGICAL NAME TABLE THAT IS TO CONTAIN THE NEW LOGICAL NAME TABLE ENTRY
045A 1509 : IS DISCOVERED TO EXIST IN PROCESS-PRIVATE SPACE, THEN THIS IS ALSO WHERE THE
045A 1510 : NEW LOGICAL NAME ENTRY SHOULD GO. DEALLOCATE THE SYSTEM SPACE LNMB, AND
045A 1511 : ALLOCATE THE SAME SIZE BLOCK FROM P1 SPACE.
045A 1512 :
045A 1513
045A 1514 2070$: PUSHL R1 :SAVE ADDRESS OF CONTAINING TABLE HEADER
7E 08 A4 3C 045C 1515 MOVZWL LNMT$W_SIZE(R4),-(SP) :SAVE SIZE OF LNMB
50 54 DO 0460 1516 MOVL R4,R0 :ADDRESS OF SYSTEM SPACE LNMB
FB9A' 30 0463 1517 BSBW LNMT$DELBLK :DEALLOCATE SYSTEM SPACE LNMB
0466 1518
0466 1519 POPL R1 :SIZE OF STORAGE TO ALLOCATE
00000000'GF 16 0469 1520 JSB G*EXESALOP1PROC :ALLOCATE NEW LNMB FROM P1 SPACE
0C 50 E8 046F 1521 BLBS R0,2080$ :BRANCH IF SUCCESSFUL
04 AE 0124 8F 3C 0472 1522 MOVZWL #SS$ INSMEM,4(SP) :OTHERWISE RETURN INSUFFICIENT MEMORY
5E 04 CO 0478 1523 ADDL2 #4,SP :THROW AWAY TABLE HEADER ADDRESS
01DE 31 047B 1524 BRW 4030$ :RETURN ERROR AFTER RELEASING MUTEX
047E 1525
047E 1526 2080$: MOVL R2,R4 :ADDRESS OF NEW LNMB
08 A4 51 BO 0481 1527 MOVW R1,LNMT$W_SIZE(R4) :SAVE NEW BLOCKS SIZE WITHIN BLOCK
51 8ED0 0485 1528 POPL R1 :ADDRESS OF CONTAINING TABLE HEADER
52 09 A1 DO 0488 1529 MOVL LNMT$SL_NAME(R1),R2 :ADDRESS OF TABLE'S LNMB
01 E1 048C 1530 BBC #LNMT$V_CONFINED - :IS THE ENTRY MARKED CONFINED?
04 10 A2 048E 1531 LNMT$B_FLAGS(R2),2090$ :BRANCH IF NOT
00 57 01 E3 0491 1532 BBCS #LNMT$V_CONFINED,R7,2090$ :MAKE SURE NEW ENTRY IS IF SO
0495 1533
0495 1534 :
0495 1535 : MAKE SURE THAT THE QUOTA HOLDER OF THE LOGICAL NAME TABLE WHICH IS TO CONTAIN
0495 1536 : THE NEW LOGICAL NAME TABLE ENTRY HAS SUFFICIENT QUOTA FOR THE CREATION OF
0495 1537 : THIS NEW LOGICAL NAME TABLE ENTRY.
0495 1538 :
0495 1539
0495 1540 2090$: MOVL LNMT$SL_QTABLE(R1),R2 :RETRIEVE QUOTA HOLDER'S ADDRESS
52 19 A1 DO 0495 1541 MOVZWL LNMT$W_SIZE(R4),R0 :SIZE OF QUOTA TO BE WITHDRAWN
50 08 A4 3C 049D 1542
049D 1543 CMPL R0,LNMT$SL_BYTES(R2) :IS THEIR SUFFICIENT QUOTA?
21 A2 50 D1 04A1 1544 BLEQU 3000$ :YES - THEN CONTINUE
6E 224C 8F 3C 04A3 1545 MOVZWL #SS$ EXLNMQUOTA,(SP) :NO - THEN DEALLOCATE LNMB AND RETURN
01AB 31 04A8 1546 BRW 4020$ :
04AB 1547

```



```
04AB 1548 :  
04AB 1549 : BUILD THE LOGICAL NAME TABLE ENTRY. REGISTER USAGE IS AS FOLLOWS:  
04AB 1550 :  
04AB 1551 : R1 = ADDRESS OF THE LOGICAL NAME TABLE'S TABLE HEADER.  
04AB 1552 : R4 = ADDRESS OF LOGICAL NAME BLOCK FOR NEW LOGICAL NAME TABLE ENTRY.  
04AB 1553 : R5 = ACCESS MODE.  
04AB 1554 : R7 = ATTRIBUTE BITS.  
04AB 1555 : R9 = ADDRESS OF PROBED AND COPIED TABLE NAME DESCRIPTOR.  
04AB 1556 : R10 = ADDRESS OF PROBED AND COPIED LOGICAL NAME DESCRIPTOR.  
04AB 1557 : R11 = ADDRESS OF ITEM LIST.  
04AB 1558 :  
04AB 1559 :  
50 0A A4 9E 04AB 1560 3000$: MOVAB LNMB$B_TYPE(R4),R0 ;POSITION TO BLOCK TYPE  
80 40 8F 90 04AF 1561 MOVB #DYN$C_LNM,(R0)+ ;SET DATA STRUCTURE TYPE  
80 55 90 04B3 1562 MOVB R5,(R0)+ ;SET OWNER ACCESS MODE  
80 51 D0 04B6 1563 MOVL R1,(R0)+ ;ADDRESS OF CONTAINING TABLE HEADER  
80 57 90 04B9 1564 MOVB R7,(R0)+ ;STORE NAME ATTRIBUTES  
80 6A 90 04BC 1565 MOVB (R10),(R0)+ ;STORE LENGTH OF NAME  
54 DD 04BF 1566 PUSHL R4 ;SAVE LNMB ADDRESS ON STACK  
01 E0 04C1 1567 BBS #LNMT$V_DIRECTORY,- ;BRANCH IF THIS LOGICAL NAME TO BE  
07 61 04C3 1568 LNMT$B_FLAGS(R1),3005$ ;CONTAINED WITHIN A DIRECTORY HEADER  
60 04 BA 6A 28 04C5 1569 MOVCB (R10),@4(R10),(R0) ;MOVE LOGICAL NAME INTO LNMB NAME FIELD  
21 11 04CA 1570 BRB 3010$ ;JOIN COMMON CODE  
1F 6A B1 04CC 1571 ;  
0B 1B 04CF 1572 3005$: CMPW (R10),#LNMC_TABNAMLEN ;SIZE EXCEED MAX FOR NAME IN DIRECTORY?  
54 8ED0 04D1 1573 BLEQU 3009$ ;CONTINUE IF IT DOESNT  
6E 0154 8F 3C 04D4 1574 3007$: POPL R4 ;OTHERWISE RESTORE LNMB ADDRESS  
017A 31 04D9 1575 MOVZWL #SS$_IVLOGNAM,(SP) ;SET ERROR CODE  
04DC 1576 BRW 4020$ ;GO RETURN ERROR  
00 04 BA 6A 2F 04DC 1577 ;  
00000000'EF 04DE 1578 3009$: MOVTUC (R10),@4(R10),#0,- ;CHECK FOR PROPER LOGICAL NAME SYNTAX  
60 6A 04E1 1579 EXESLNM_SYNTAX_DAT,- ;AND AT THE SAME TIME MOVE THE LOGICAL  
E7 1D 04E6 1580 (R10),(R0) ;NAME INTO THE LNMB NAME FIELD  
53 55 D0 04E8 1581 BVS 3007$ ;GO RETURN ERROR IF IMPROPER SYNTAX  
54 8ED0 04EA 1582 MOVL R5,R3 ;ELSE SHIFT LNMX ADDR INTO PROPER REG  
04ED 1583 3010$: POPL R4 ;RESTORE LNMB ADDRESS FROM STACK  
04F0 1584 ;  
04F0 1585 :  
04F0 1586 : FILL IN THE LNMX PORTION OF THE LOGICAL NAME BLOCK FOR THE NEW LOGICAL NAME  
04F0 1587 : TABLE ENTRY. THIS INVOLVES PROCESSING THE ITEM LIST FOR A SECOND TIME SO  
04F0 1588 : THAT THE LOGICAL NAME TRANSLATION BLOCKS MAYBE CONSTRUCTED, AND ANY OUTPUT  
04F0 1589 : INFORMATION RETURNED.  
04F0 1590 :  
04F0 1591 :  
5B D5 04F0 1592 TSTL R11 ;WAS AN ITEM LIST DEFINED?  
03 12 04F2 1593 BNEQ 3030$ ;YES - GO PROCESS IT  
013C 31 04F4 1594 3020$: BRW 3950$ ;NO - SKIP ITEM LIST PROCESSING  
56 D4 04F7 1595 ;  
58 D4 04F9 1596 3030$: CLRL R6 ;0 IS THE DEFAULT INDEX  
04FB 1597 CLRL R8 ;NO ATTRIBUTES DEFINED AS YET  
0501 1598 3035$: IFNORD #4,(R11),3060$ ;CHECK IF FIRST LONGWORD READABLE  
52 02 AB 3C 0501 1599 3040$: ;  
ED 13 0501 1600 MOVZWL 2(R11),R2 ;GET ITEM TYPE  
0505 1601 BEQL 3020$ ;DONE IF ITEM TYPE IS ZERO  
0507 1602 IFNORD #12,4(R11),3060$ ;CHECK REST OF THIS DESCRIPTOR  
050E 1603 ;PLUS FIRST LONGWORD OF NEXT ONE  
050E 1604
```



```
050E 1605 CASE R2,<- ;HANDLE EACH ITEM TYPE SEPARATELY
050E 1606 ;INDEX ITEM
050E 1607 ;STRING ITEM
050E 1608 ;ATTRIBUTES ITEM
050E 1609 ;TABLE ITEM
050E 1610 >,W,#1
52 09 B1 051A 1611 CMPW #LNMS_LNMB_ADDR, R2 ;TEST FOR SPECIAL ITEM
15 13 051D 1612 BEQL 3100$
52 FFFF 8F B1 051F 1613 CMPW #LNMS_CHAIN,R2 ;TEST FOR CHAINED ITEM LIST
06 13 0524 1614 BEQL 3070$
0100 31 0526 1615 3050$: BRW 3930$ ;ILLEGAL ITEM
00F8 31 0529 1616 3060$: BRW 3920$ ;REPORT ACCESS VIOLATION
052C 1617
052C 1618 ;
052C 1619 ; POSITION TO THE NEXT CHAIN IN THE CHAINED ITEM LIST.
052C 1620 ;
052C 1621 ;
5B 04 AB D0 052C 1622 3070$: MOVL 4(R11),R11 ;GET POINTER
C2 13 0530 1623 BEQL 3020$ ;LAST ITEM
C7 11 0532 1624 BRB 3035$ ;GO PROCESS IT
0534 1625
0534 1626 ;
0534 1627 ; LOGICAL NAME BLOCK ADDRESS
0534 1628 ;
0534 1629 ; TEST IF THE LOGICAL NAME BLOCK ADDRESS CAN BE WRITTEN IN THE
0534 1630 ; REQUESTED PLACE. ( CURRENT USE IS TO LINK A LOGICAL NAME BLOCK
0534 1631 ; WITH MTL OR MAILBOX UCB )
0534 1632 ;
0534 1633 ;
6B 04 B1 0534 1634 3100$: CMPW #4,(R11) ;IS THE ITEM A LONGWORD
ED 12 0537 1635 BNEQ 3050$ ;ERROR IF NOT
50 04 AB D0 0539 1636 MOVL 4(R11),R0 ;RETRIEVE ITEM BUFFER ADDRESS
60 54 D0 053D 1637 IFNOWNRT #4,(R0),3060$ ;ACCVIO IF ITEM BUFFER NOT WRITEABLE
00D5 31 0543 1638 MOVL R4,(R0) ;MOVE THE ADDRESS OF LNM TO BUFFER
0546 1639 BRW 3910$ ;GO POSITION TO NEXT ITEM
0549 1640
0549 1641 ;
0549 1642 ; INDEX OR ATTRIBUTES ITEM.
0549 1643 ;
0549 1644 ; VALIDATE THE ITEM. SAVE THE INDEX OR ATTRIBUTES FOR APPLICATION TO
0549 1645 ; THE NEXT TRANSLATION BLOCK THAT IS TO BE CREATED.
0549 1646 ;
0549 1647 ;
6B 04 B1 0549 1648 3200$: CMPW #4,(R11) ;IS ITEM BUFFER AT LEAST A LONGWORD?
D8 1A 054C 1649 BGTRU 3050$ ;ERROR IF NOT
50 04 AB D0 054E 1650 MOVL 4(R11),R0 ;RETRIEVE ITEM BUFFER ADDRESS
50 60 D0 0552 1651 IFNORD (R11),(R0),3060$ ;ACCVIO IF ITEM BUFFER NOT READABLE
0558 1652 MOVL (R0),R0 ;PICK UP THE LONGWORD
055B 1653
52 01 B1 055B 1654 CMPW #LNMS_INDEX,R2 ;IS IT AN INDEX ITEM?
11 13 055E 1655 BEQL 3210$ ;YES - BRANCH AND VERIFY INDEX ITEM
50 FFFFFCFF 8F D3 0560 1656 BITL #^C<- ;TEST FOR INVALID ATTRIBUTES
0567 1657 LNMSM_CONCEALED! - ;TRANSLATION IS CONCEALED
0567 1658 LNMSM_TERMINAL - ;TRANSLATION IS TERMINAL
0567 1659 >,R0
58 50 F8 BD 12 0567 1660 BNEQ 3050$ ;INVALID ATTRIBUTES ITEM
8F 9C 0569 1661 ROTL #-8,R0,R8 ;SAVE ATTRIBUTES FOR LNMX CREATION
```



```
00AD 31 056E 1662 BRW 3910$ ;GO POSITION TO NEXT ITEM
50 FFFFFFF80 8F D3 0571 1663 3210$: BITL #*C127,R0 ;IS INDEX BETWEEN 0 AND 127?
16 13 0571 1664 BEQL 3220$ ;YES - NO PRIVILEGE NEEDED
0578 1665
057A 1666
057A 1667 ; THIS IS HERE SO THAT MTL OR MAILBOX UCB CAN HAVE ITS ADDRESS
057A 1668 ; STORED IN THE LOGICAL NAME BLOCK.
057A 1669
057A 1670
057A 1671
057A 1672
057A 1673 MOVPSL R2 ;GET THE PSL
52 00C00000 8F D3 057C 1674 BITL #PSL$M_PVMOD,R2 ;TEST IF PREVIOUS MODE WAS KERNEL
A1 12 0583 1675 BNEQ 3050$ ;NO - BAD INDEX VALUE
50 FFFFFFF81 8F D1 0585 1676 CMPL #LNM$SC_BACKPTR,R0 ;CORRECT INDEX
98 12 058C 1677 BNEQ 3050$ ;NO - BAD INDEX VALUE
05 11 058E 1678 BRB 3225$
56 50 D1 0590 1679 3220$: CMPL R0,R6 ;IS INDEX LESS THAN LAST ONE SEEN?
91 19 0593 1680 BLSS 3050$ ;YES - INVALID INDEX ITEM
56 50 D0 0595 1681 3225$: MOVL R0,R6 ;SAVE INDEX FOR LNM$ CREATION
0083 31 0598 1682 BRW 3910$ ;GO POSITION TO NEXT ITEM
059B 1683
059B 1684 ; STRING ITEM.
059B 1685
059B 1686
059B 1687 ; VALIDATE THE ITEM, INCLUDING THAT THE STRING SPECIFIED IS A VALID EQUIVALENCE
059B 1688 ; STRING. VERIFY THAT THE CREATION OF THIS TRANSLATION BLOCK WILL NOT EXCEED
059B 1689 ; THE AMOUNT OF SPACE ALLOCATED. FILL IN THE NEXT TRANSLATION BLOCK UTILIZING
059B 1690 ; THE STRING SPECIFIED AS THE TRANSLATION STRING AS WELL AS THE CURRENT INDEX
059B 1691 ; AND ATTRIBUTES SETTINGS. INCREMENT THE CURRENT INDEX.
059B 1692
059B 1693
50 6B 7E 059B 1694 3300$: MOVAQ (R11),R0 ;ADDRESS OF STRING ITEM DESCRIPTOR
FA5F' 30 059E 1695 BSBW LNM$PROBER ;PROBE TRANSLATION STRING
42 50 E9 05A1 1696 BLBC R0,3410$ ;BRANCH IF CAN'T READ OR NOT PRESENT
05A4 1697
50 53 54 C3 05A4 1698 SUBL3 R4,R3,R0 ;NUMBER OF BYTES CURRENTLY IN USE
50 06 C0 05A8 1699 ADDL2 #LNM$ST_XLATION+2,R0 ;ADD OVERHEAD FOR CURRENT TRANSLATION
50 51 C0 05AB 1700 ADDL2 R1,R0 ;ADD IN SIZE OF CURRENT TRANSLATION
08 A4 50 B1 05AE 1701 CMPW R0,LNM$W_SIZE(R4) ;EXCEED LOGICAL NAME BLOCK SIZE?
75 1A 05B2 1702 BGTRU 3930$ ;YES - RETURN AN ERROR
05B4 1703
83 58 90 05B4 1704 MOVB R8,(R3)+ ;CURRENT ATTRIBUTES BECOME LNM$ FLAGS
83 56 90 05B7 1705 MOVB R6,(R3)+ ;CURRENT INDEX LEVEL BECOMES LNM$ LEVEL
83 B4 05BA 1706 CLRW (R3)+ ;INITIALIZE HASH CODE LOCATION
56 D6 05BC 1707 INCL R6 ;INCREMENT INDEX LEVEL BY 1
83 51 90 05BE 1708 MOVB R1,(R3)+ ;STORE SIZE OF TRANSLATION STRING
54 DD 05C1 1709 PUSHL R4 ;SAVE NEEDED REGISTERS OVER MOV$3
63 62 51 28 05C3 1710 MOV$3 R1,(R2),(R3) ;MOVE TRANSLATION STRING INTO LNM$
54 8ED0 05C7 1711 POPL R4 ;RESTORE REGISTERS
52 11 05CA 1712 BRB 3910$ ;GO POSITION TO NEXT ITEM
05CC 1713
05CC 1714 ; TABLE ITEM.
05CC 1715
05CC 1716
05CC 1717 ; VALIDATE THE ITEM. STORE THE NAME OF THE LOGICAL NAME TABLE WHICH IS TO
05CC 1718 ; CONTAIN THIS NEW LOGICAL NAME TABLE ENTRY IN THE ITEM BUFFER PROVIDED, AND
```



```
05CC 1719 : THE SIZE OF THE NAME STORED IN THE ITEM SIZE BUFFER, IF PROVIDED.
05CC 1720 :
05CC 1721 :
50 7E 6B 7D 05CC 1722 3400$: MOVQ (R11),-(SP) ;SAVE DESCRIPTOR OF TABLE ITEM BUFFER
51 51 6E 3C 05CF 1723 MOVZWL (SP),R1 ;SIZE OF TABLE ITEM BUFFER
04 AE D0 05D2 1724 MOVL 4(SP),R0 ;ADDRESS OF TABLE ITEM BUFFER
53 DD 05D6 1725 PUSHL R3 ;SAVE CURRENT LNMX POSITION
53 D4 05D8 1726 CLRL R3 ;ACCESS MODE
00000000 GF 16 05DA 1727 JSB G*EXESPROBEW ;PROBE TABLE ITEM BUFFER FOR WRITTING
53 8E D0 05E0 1728 POPL R3 ;RESTORE CURRENT LNMX POSITION
51 45 50 7D 05E3 1729 MOVQ (SP)+,R1 ;RESTORE TABLE ITEM BUFFER DESCRIPTOR
E9 05E6 1730 3410$: BLBC R0,3940$ ;RETURN IF NOT WRITEABLE
05E9 1731 :
55 0C A4 D0 05E9 1732 MOVL LNMB$TABLE(R4),R5 ;ADDRESS OF CONTAINING TABLE HEADER
55 09 A5 D0 05ED 1733 MOVL LNMB$NAME(R5),R5 ;ADDRESS OF CONTAINING LNMB
55 11 A5 9E 05F1 1734 MOVAB LNMB$NAME(R5),R5 ;ADDRESS OF COUNT FIELD
50 85 9A 05F5 1735 MOVZBL (R5)+,R0 ;SIZE OF CONTAINING TABLE'S NAME
05F8 1736 :
51 50 B1 05F8 1737 CMPW R0,R1 ;ENOUGH ROOM IN BUFFER FOR NAME?
08 15 05FB 1738 BLEQ 3420$ ;BRANCH IF SUFFICIENT ROOM
6E 0601 8F 3C 05FD 1739 MOVZWL #SS$ BUFFEROVF,(SP) ;CHANGE RETURN STATUS
50 51 3C 0602 1740 MOVZWL R1,R0 ;RETURN AS MUCH AS POSSIBLE
0605 1741 :
51 08 AB D0 0605 1742 3420$: MOVL 8(R11),R1 ;WAS A RETURN LENGTH BUFFER SPECIFIED
09 13 0609 1743 BEQL 3430$ ;NO - DON'T RETURN LENGTH
61 50 B0 060B 1744 IFNOWRT #2,(R1),3920$ ;YES - PROBE RETURN LENGTH BUFFER
0614 1745 MOVW R0,(R1) ;AND RETURN LENGTH
0614 1746 :
62 7E 53 7D 0614 1747 3430$: MOVQ R3,-(SP) ;SAVE REGISTERS OVER MOVQ3
65 50 28 0617 1748 MOVQ R0,(R5),(R2) ;RETURN CONTAINING TABLE NAME STRING
53 8E 7D 061B 1749 MOVQ (SP)+,R3 ;RESTORE SAVED REGISTERS
061E 1750 :
5B 0C C0 061E 1751 3910$: ADDL2 #12,R11 ;POSITION TO NEXT ITEM
FEDD 31 0621 1752 BRW 3040$ ;AND CONTINUE ITEM LIST VERIFICATION
0624 1753 :
6E 0C 3C 0624 1754 3920$: MOVZWL #SS$ ACCVIO,(SP) ;ACCESS VIOLATION
2D 11 0627 1755 BRB 4020$ ;DEALLOCATE NEW LNMB AND RETURN ERROR
0629 1756 :
6E 14 3C 0629 1757 3930$: MOVZWL #SS$ BADPARAM,(SP) ;BAD PARAMETER SEEN
28 11 062C 1758 BRB 4020$ ;DEALLOCATE NEW LNMB AND RETURN ERROR
062E 1759 :
6E 50 D0 062E 1760 3940$: MOVL R0,(SP) ;SAVE RETURN STATUS
23 11 0631 1761 BRB 4020$ ;DEALLOCATE NEW LNMB AND RETURN ERROR
0633 1762 :
0633 1763 :
0633 1764 : FILL IN THE LAST LNMX PORTION OF THE LOGICAL NAME BLOCK FOR THE NEW LOGICAL
0633 1765 : NAME TABLE ENTRY. THE LAST TRANSLATION BLOCK CONSISTS SOLELY OF A FLAGS FIELD.
0633 1766 : AND IS MARKED WITHIN THIS FLAGS FIELD AS THE LAST LNMX.
0633 1767 :
0633 1768 :
83 04 90 0633 1769 3950$: MOVW #LNMB$M_XEND,(R3)+ ;STORE END FLAG
0636 1770 :
0636 1771 :
0636 1772 : AT THIS POINT ALL CHECKS HAVE BEEN MADE, AND THE TABLE STRUCTURES MAY NOW
0636 1773 : BE MODIFIED FOR THE FIRST TIME. INSERT THE NEW LOGICAL NAME TABLE ENTRY.
0636 1774 :
0636 1775 : THIS INSERTION MAY TAKE ONE OF TWO FORMS:
```

```

0636 1776 :
0636 1777 : 1.) THE LOGICAL NAME TABLE ENTRY MAYBE INSERTED AS A NEW LOGICAL NAME. THE
0636 1778 : FOLLOWING CONDITIONS MUST HOLD TRUE.
0636 1779 :
0636 1780 : A.) THERE IS NO LOGICAL NAME TABLE ENTRY WITH THE SAME NAME AND ACCESS
0636 1781 : MODE WITHIN THE SAME CONTAINING LOGICAL NAME TABLE.
0636 1782 :
0636 1783 : B.) THERE IS NO LOGICAL NAME TABLE ENTRY WITH THE SAME NAME AND AN
0636 1784 : INNER ACCESS MODE WITHIN THE SAME CONTAINING LOGICAL NAME TABLE
0636 1785 : THAT DOES NOT ALLOW ALIASES.
0636 1786 :
0636 1787 : 2.) THE ENTRY MAYBE INSERTED SUPERSEDING AN EXISTING ENTRY WITHIN THE SAME
0636 1788 : CONTAINING LOGICAL NAME TABLE WITH THE SAME NAME AND ACCESS MODE. THE
0636 1789 : OLD LOGICAL NAME TABLE ENTRY IS DELETED.
0636 1790 :
0636 1791 : IF EITHER CASE OCCURS, AND THE NEW LOGICAL NAME TABLE ENTRY DOES NOT ALLOW
0636 1792 : ALIASES, THEN ANY LOGICAL NAME TABLE ENTRIES IN THE SAME CONTAINING LOGICAL
0636 1793 : NAME TABLE WITH THE SAME NAME BUT AT AN OUTER ACCESS MODE ARE DELETED.
0636 1794 :
0636 1795 :
51 54 D0 0636 1796 : MOVL R4,R1 ;ADDRES OF NEW LOGICAL NAME TABLE ENTRY
52 57 D0 0639 1797 : MOVL R7,R2 ;ATTRIBUTES
F9C1' 30 063C 1798 : BSBW LNMSINSLOGTAB ;INSERT NEW LOGICAL NAME TABLE ENTRY
50 0631 8F B1 063F 1799 : CMPW #SS$ SUPERSEDE,R0 ;INSERTION SUCCEED WITH SUPERSEDE?
OA 12 0644 1800 : BNEQ 4010$ ;BRANCH IF NO
6E 0601 8F B1 0646 1801 : CMPW #SS$ BUFFEROVF,(SP) ;BUFFER OVERFLOW SEEN?
OF 13 064B 1802 : BEQL 4030$ ;YES - THEN RETURN THAT STATUS
6E 50 D0 064D 1803 : MOVL R0,(SP) ;OTHERWISE RETURN SUPERSEDE SUCCESS
09 50 E8 0650 1804 4010$: BLBS R0,4030$ ;BRANCH ON SUCCESS
6E 50 D0 0653 1805 : MOVL R0,(SP) ;OTHRWISE SAVE ERROR STATUS
0656 1806 :
50 54 D0 0656 1807 4020$: MOVL R4,R0 ;LOGICAL NAME BLOCK FOR NEW TABLE ENTRY
F9A4' 30 0659 1808 : BSBW LNMSDELBLK ;DELETE BLOCK CONTAINING NEW TABLE ENTRY
065C 1809 :
54 04 AE D0 065C 1810 4030$: MOVL 4(SP),R4 ;RETRIEVE PCB ADDRESS
F99D' 30 0660 1811 : BSBW LNMSUNLOCK ;UNLOCK TABLES
50 8ED0 0663 1812 : POPL R0 ;RESTORE STATUS
04 0666 1813 : RET ;RETURN TO CALLER
0667 1814 :
0667 1815 : .DISABLE LSB
0667 1816 :
0667 1817 : .PAGE

```



```

0667 1819 .SBTTL EXE$DELLNM - DELETE LOGICAL NAME
0667 1820 :+
0667 1821 : EXE$DELLNM - DELETE LOGICAL NAME
0667 1822 :
0667 1823 : THIS SERVICE PROVIDES THE CAPABILITY TO:
0667 1824 :
0667 1825 : 1. DELETE A SPECIFIED LOGICAL NAME.
0667 1826 : 2. DELETE A SPECIFIED LOGICAL NAME TABLE.
0667 1827 : 3. DELETE ALL THE LOGICAL NAME TABLE ENTRIES CONTAINED WITHIN A
0667 1828 : SPECIFIED LOGICAL NAME TABLE.
0667 1829 :
0667 1830 : INPUTS:
0667 1831 :
0667 1832 : DNACMODE(AP) = ADDRESS OF ACCESS MODE OF LOGICAL NAMES(S) TO BE DELETED.
0667 1833 : DNLOGNAM(AP) = ADDRESS OF LOGICAL NAME STRING DESCRIPTOR.
0667 1834 : DNTABNAM(AP) = ADDRESS OF TABLE NAME STRING DESCRIPTOR.
0667 1835 :
0667 1836 : R4 = CURRENT PROCESS PCB ADDRESS.
0667 1837 :
0667 1838 : OUTPUTS:
0667 1839 :
0667 1840 : R0 LOW BIT CLEAR INDICATES FAILURE TO DELETE LOGICAL NAME(S).
0667 1841 :
0667 1842 : R0 = SS$ ACCVIO - TABLE NAME DESCRIPTOR, TABLE NAME STRING
0667 1843 : LOGICAL NAME DESCRIPTOR, LOGICAL NAME STRING, CANNOT
0667 1844 : BE READ BY CALLING ACCESS MODE.
0667 1845 :
0667 1846 : R0 = SS$ BADPARAM - INVALID ACCESS MODE SPECIFIED. NO TABLE
0667 1847 : NAME DESCRIPTOR SPECIFIED.
0667 1848 :
0667 1849 : R0 = SS$ IVLOGNAM - ZERO OR GREATER THAN MAXIMUM LENGTH
0667 1850 : LOGICAL OR TABLE NAME STRING SPECIFIED.
0667 1851 :
0667 1852 : R0 = SS$ IVLOGTAB - INVALID TABLE NAME SPECIFIED.
0667 1853 :
0667 1854 : R0 = SS$ NOLOGNAM - LOGICAL NAME TABLE OR LOGICAL NAME
0667 1855 : SPECIFIED DOES NOT EXIST.
0667 1856 :
0667 1857 : R0 = SS$ NOLOGTAB - LOGICAL NAME TABLE SPECIFIED DOES NOT EXIST.
0667 1858 :
0667 1859 : R0 = SS$ NOPRIV - PROCESS DOES NOT HAVE PRIVILEGE TO DELETE
0667 1860 : THE SPECIFIED LOGICAL NAME(S).
0667 1861 :
0667 1862 : R0 = SS$ TOOMANYLNM - TOO MANY LEVELS OF RECURSION IN SEARCH
0667 1863 : FOR LOGICAL NAME TABLE OR LOGICAL NAME.
0667 1864 :
0667 1865 : R0 LOW BIT SET INDICATES SUCCESSFUL COMPLETION.
0667 1866 :
0667 1867 : R0 = SS$ NORMAL - NORMAL COMPLETION. LOGICAL NAME(S) HAVE BEEN
0667 1868 : DELETED.
0667 1869 :
0667 1870 : SIDE EFFECTS:
0667 1871 :
0667 1872 : THIS ROUTINE EXITS AT IPL 2.
0667 1873 :
0667 1874 : -
0667 1875 :

```



```
0000000A 1876 .PSECT Y$EXEPAGED
0660' OFFC 000A 1877 .ENTRY EXE$DELLNM,^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>
31 000C 1878 BRW EXE$DELLNM
000F 1879
00000667 1880 .PSECT YF$SLNM
0667 1881 .ENABLE LSB
50 0C 3C 0667 1882 900$: MOVZWL #SS$_ACCVIO,R0 ;ACCESS VIOLATION
04 066A 1883 RET
50 14 3C 066B 1884 910$: MOVZWL #SS$_BADPARAM,R0 ;BAD SYSTEM SERVICE PARAMETER
04 066E 1885 930$: RET
066F 1886
066F 1887 :
066F 1888 : VALIDATE AND COPY PARAMETERS AS NECESSARY. REGISTER ASSIGNMENT FOR THE
066F 1889 : PARAMETERS ARE AS FOLLOWS:
066F 1890 :
066F 1891 : R5 = ACCESS MODE.
066F 1892 : R9 = ADDRESS OF PROBED AND COPIED TABLE NAME DESCRIPTOR.
066F 1893 : R10 = ADDRESS OF PROBED AND COPIED LOGICAL NAME DESCRIPTOR.
066F 1894 :
066F 1895
066F 1896 EXE$DELLNM:
066F 1897
5A 08 AC D0 066F 1898 MOVL DNLOGNAM(AP),R10 ;ADDRESS OF LOGICAL NAME DESCRIPTOR
15 13 0673 1899 BEQL 10$ ;BRANCH IF NOT PRESENT
0675 1900 IFNORD #8,(R10),900$ ;CHECK ACCESS TO DESCRIPTOR
50 6A 7E 067B 1901 MOVAQ (R10),R0 ;ADDRESS OF DESCRIPTOR
F97F' 30 067E 1902 BSBW LNM$PROBER ;PROBE LOGICAL NAME STRING
EA 50 E9 0681 1903 BLBC R0,930$ ;BRANCH IF CAN'T READ OR NOT PRESENT
7E 51 7D 0684 1904 MOVQ R1,-(SP) ;SAVE LOGICAL NAME DESCRIPTOR
5A 5E D0 0687 1905 MOVL SP,R10 ;ADDRESS OF LOGICAL NAME DESCRIPTOR
068A 1906 10$:
59 04 AC D0 068A 1907 MOVL DNTABNAM(AP),R9 ;ADDRESS OF TABLE NAME DESCRIPTOR
DB 13 068E 1908 BEQL 910$ ;ERROR IF NOT PRESENT
0690 1909 IFNORD #8,(R9),900$ ;CHECK ACCESS TO DESCRIPTOR
50 69 7E 0696 1910 MOVAQ (R9),R0 ;SET UP CALL
F964' 30 0699 1911 BSBW LNM$PROBER ;PROBE TABLE NAME STRING
CF 50 E9 069C 1912 BLBC R0,930$ ;BRANCH IF CAN'T READ OR NOT PRESENT
7E 51 7D 069F 1913 MOVQ R1,-(SP) ;SAVE TABLE NAME DESCRIPTOR
59 5E D0 06A2 1914 MOVL SP,R9 ;ADDRESS OF TABLE NAME DESCRIPTOR
06A5 1915
50 0C AC D0 06A5 1916 MOVL DNACMODE(AP),R0 ;GET SPECIFIED ACCESS MODE
14 13 06A9 1917 BEQL 20$ ;BRANCH IF NOT PRESENT
06AB 1918 IFNORD #1,(R0),900$ ;CHECK ACCESS TO VALUE
50 60 9A 06B1 1919 MOVZBL (R0),R0 ;GET VALUE
50 03 D1 06B4 1920 CMPL #PSL$_C_USER,R0 ;CHECK FOR VALID ACCESS MODE
B2 1F 06B7 1921 BLSSU 910$ ;INVALID ACCESS MODE
06B9 1922
06B9 1923 :
06B9 1924 : IF THE ACCESS MODE OF THE LOGICAL NAME TABLE ENTRY(S) TO BE DELETED WAS
06B9 1925 : EXPLICITLY SPECIFIED AND THE CALLER HAS THE SYSNAM PRIVILEGE, THEN THE
06B9 1926 : SPECIFIED ACCESS MODE IS USED TO QUALIFY THE LOGICAL NAME TABLE ENTRY(S)
06B9 1927 : DELETION. OTHERWISE, THE ACCESS MODE OF THE CALLER IS MAXIMIZED WITH ANY
06B9 1928 : EXPLICITLY SPECIFIED ACCESS MODE AND USED TO QUALIFY THE LOGICAL NAME TABLE
06B9 1929 : ENTRY(S) DELETION.
06B9 1930 :
06B9 1931
06B9 1932 IFPRIV SYSNAM,30$ ;CALLER HAS SYSNAM PRIVILEGE
```



```
00000000'GF 16 06BF 1933 20$: JSB G^EXES$MAXACMODE ;MAXIMIZED WITH MODE OF CALLER TO
55 50 D0 06C5 1934 30$: MOVL R0,R5 ;DETERMINE ACCESS MODE OF TABLE ENTRY(S)
06C8 1935
06C8 1936
06C8 1937 : RAISE IPL TO AST DELIVERY LEVEL SO THAT THERE ARE NO INTERRUPTIONS WHILE
06C8 1938 : THE DELETION OF THE LOGICAL NAME TABLE ENTRY(S) IS BEING CARRIED OUT, AND
06C8 1939 : LOCK THE LOGICAL NAME MUTEX FOR WRITING.
06C8 1940
06C8 1941
06C8 1942
06C8 1943
06C8 1944
06C8 1945
06C8 1946
06C8 1947
06C8 1948
06C8 1949
06C8 1950
06C8 1951
06C8 1952
06C8 1953
06C8 1954
06C8 1955
06C8 1956
06C8 1957
06C8 1958
06C8 1959
06C8 1960
06C8 1961
06C8 1962
06C8 1963
06C8 1964
06C8 1965
06C8 1966
06C8 1967
06C8 1968
06C8 1969
06C8 1970
06C8 1971
06C8 1972
06C8 1973
06C8 1974
06C8 1975
06C8 1976
06C8 1977
06C8 1978
06C8 1979
06C8 1980
06C8 1981
06C8 1982
06C8 1983
06C8 1984
06C8 1985
06C8 1986
06C8 1987
06C8 1988
06C8 1989

F932' 30 SETIPL S^#IPL$ ASTDEL ;RAISE TO AST DELIVERY LEVEL
BSBW LNMS$LOCRW ;LOCK TABLES FOR WRITING

IF A LOGICAL NAME WAS SPECIFIED, THEN IT REPRESENTS THE LOGICAL NAME TABLE
ENTRY WITH THE SPECIFIED ACCESS MODE WHICH IS TO BE DELETED FROM THE LOGICAL
NAME TABLE WITH THE SPECIFIED LOGICAL NAME TABLE NAME. FIND THE FIRST SUCH
LOGICAL NAME TABLE ENTRY AND DELETE IT. IF THE ACCESS MODE REQUESTED IS OTHER
THAN USER, THAN ALL OUTER ACCESS MODE ALIASES IN THIS TABLE ARE ALSO DELETED.

NOTE THAT IF THE FIRST SUCH LOGICAL NAME TABLE ENTRY IS THAT OF A LOGICAL
NAME TABLE, THEN ALL LOGICAL NAMES CONTAINED WITHIN THE TABLE TOGETHER WITH
ALL ITS SUBTABLES AND THE LOGICAL NAMES CONTAINED WITHIN THEM ARE DELETED.

5A D5 TSTL R10 ;IS A SPECIFIC ENTRY TO BE DELETED?
54 13 BEQL 60$ ;BRANCH IF SUPPOSED TO DELETE THEM ALL

50 6A 7D MOVQ (R10),R0 ;LOGICAL NAME DESCRIPTOR
52 69 7D MOVQ (R9),R2 ;TABLE NAME DESCRIPTOR
F925' 30 BSBW LNMS$SEARCHLOG ;SEARCH FOR JUST SUCH A LOGICAL NAME
67 50 E9 BLBC R0,80$ ;EXIT IF NO NAME FOUND

OB A1 55 91 CMPB R5,LNMB$B_ACMODE(R1) ;DO THE ACCESS MODES MATCH
07 13 BEQLU 40$ ;IF SO THEN HAVE FOUND ENTRY TO DELETE
50 01BC 8F 3C MOVZWL #SS$_NOLOGNAM,R0 ;OTHERWISE GO RETURN ERROR
5A 11 BRB 80$

DETERMINE WHETHER THE CALLER CAN DELETE THE LOGICAL NAME TABLE ENTRY, AND
THEN DELETE IS IF SUCH ACCESS IS ALLOWED. THE ACCESS REQUIREMENTS FOR DELETION
ARE AS FOLLOWS:

LOGICAL NAME: THE CALLER NEEDS WRITE ACCESS TO THE CONTAINING LOGICAL
NAME TABLE.

LOGICAL NAME TABLE: THE CALLER NEEDS EITHER WRITE ACCESS TO THE CONTAINING
LOGICAL NAME TABLE (THE SYSTEM OR PROCESS DIRECTORY
TABLE), OR DELETE ACCESS TO THE LOGICAL NAME TABLE
ITSELF.

NOTE THAT IF THE LOGICAL NAME TABLE ENTRY IS PROCESS-PRIVATE THEN NO
PROTECTION CHECKING IS PERFORMED, AND THE CALLER CAN ALWAYS DELETE THE ENTRY.

32 51 1F E1 06EB 1987 40$: BBC #31,R1,50$ ;SKIP CHECK IF PROCESS-PRIVATE ENTRY
52 02 9A 06EF 1988 MOVZBL #WRITE_ACCESS,R2 ;CODE FOR ACCESS CHECK
51 DD 06F2 1989 PUSHL R1 ;SAVE LNMB ADDRESS
```



```
51 0C A1 D0 06F4 1990      MOVL LNMB$TABLE(R1),R1      ;GET TABLE HEADER ADDRESS
    F905' 30 06F8 1991      BSBW LNMB$CHECK_PROT      ;CHECK THE PROTECTION
    51 8ED0 06FB 1992      POPL R1      ;RESTORE LNMB
    20 50 E8 06FE 1993      BLBS R0,50$      ;DELETE THE ENTRY ON SUCCESS
    03 E1 0701 1994      BBC #LNMB$V_TABLE,-      ;RETURN AN ERROR ON FAILURE IF THE
    3F 10 A1 0703 1995      LNMB$B_FLAGS(R1),80$      ;ENTRY TO BE DELETED IS NOT A TABLE
    0706 1996
    52 08 9A 0706 1997      MOVZBL #DELETE_ACCESS,R2      ;CODE FOR ACCESS CHECK
    51 DD 0709 1998      PUSHL R1      ;SAVE LNMB ADDRESS
    50 11 A1 9A 070B 1999      MOVZBL LNMB$TABLE_NAME(R1),R0      ;RETRIEVE SIZE OF NAME STRING
    51 12 A140 9E 070F 2000      MOVAB LNMB$TABLE_NAME+1(R1),R1      ;POSITION TO LNMB
    51 05 A1 9E 0714 2001      MOVAB LNMB$TABLE_NAME+1(R1),R1      ;POSITION TO TABLE HEADER
    F8E5' 30 0718 2002      BSBW LNMB$CHECK_PROT      ;CHECK THE PROTECTION
    51 8ED0 071B 2003      POPL R1      ;RESTORE LNMB
    24 50 E9 071E 2004      BLBC R0,80$      ;QUIT ON FAILURE
    0721 2005
    F8DC' 30 0721 2006 50$: BSBW LNMB$DELETE_LNMB      ;DELETE ALL APPROPRIATE LOGICAL NAMES
    1F 11 0724 2007      BRB 80$      ;AND RETURN STATUS OF DELETION
    0726 2008
    0726 2009 :
    0726 2010 : IF NO LOGICAL NAME WAS SPECIFIED, THEN ALL THE LOGICAL NAME TABLE ENTRIES
    0726 2011 : CONTAINED WITHIN THE SPECIFIED LOGICAL NAME TABLE AND POSSESSING AN ACCESS
    0726 2012 : MODE EQUAL TO OR GREATER THEN THE DESIGNATED ACCESS MODE ARE TO BE DELETED.
    0726 2013 : POSITION TO THE SPECIFIED LOGICAL NAME TABLE, AND PERFORM THE ACTUAL DELETION
    0726 2014 : OF THE NAMES CONTAINED WITHIN THE TABLE.
    0726 2015 :
    0726 2016 : TWO POSSIBLE CASES EXIST:
    0726 2017 :
    0726 2018 : CASE 1: THE SPECIFIED LOGICAL NAME TABLE NAME IS THAT OF A LOGICAL NAME TABLE
    0726 2019 : OTHER THAN THE SYSTEM/PROCESS DIRECTORY TABLE. IN THIS CASE ALL THE
    0726 2020 : LOGICAL NAMES, BUT NOT THE LOGICAL NAME TABLE SUB-STRUCTURE, THAT
    0726 2021 : POSSESS AN ACCESS MODE EQUAL TO OR GREATER THAN THE DESIGNATED ACCESS
    0726 2022 : MODE ARE DELETED. THE LOGICAL NAME TABLE SUB-STRUCTURE IS NOT DELETED
    0726 2023 : BECAUSE ALL LOGICAL NAME TABLES ARE CONTAINED WITHIN THE SYSTEM OR
    0726 2024 : PROCESS DIRECTORY TABLES AND NOT WITHIN INDIVIDUAL LOGICAL NAME
    0726 2025 : TABLES.
    0726 2026 :
    0726 2027 : CASE 2: THE SPECIFIED LOGICAL NAME TABLE NAME IS THAT OF THE SYSTEM/PROCESS
    0726 2028 : DIRECTORY TABLE. IN THIS CASE ALL OF THE LOGICAL NAME TABLE ENTRIES
    0726 2029 : (INCLUDING ALL LOGICAL NAME TABLES) CONTAINED WITHIN THE SPECIFIED
    0726 2030 : DIRECTORY TABLE AND POSSESSING AN ACCESS MODE EQUAL TO OR GREATER
    0726 2031 : THAN THE DESIGNATED ACCESS MODE ARE DELETED.
    0726 2032 :
    0726 2033 : NOTE THAT IF THE LOGICAL NAME TABLE IS PROCESS-PRIVATE THEN NO PROTECTION
    0726 2034 : CHECKING IS PERFORMED, AND THE CALLER CAN ALWAYS DELETE THE ENTRY(S) IN THE
    0726 2035 : TABLE.
    0726 2036 :
    0726 2037 :
    51 55 D0 0726 2038 60$: MOVL R5,R1      ;ACCESS MODE
    52 69 7D 0729 2039      MOVQ (R4),R2      ;TABLE NAME DESCRIPTOR
    F8D1' 30 072C 2040      BSBW LNMB$FIRSTTAB      ;SEARCH FOR SPECIFIED LOGICAL NAME TABLE
    13 50 E9 072F 2041      BLBC R0,80$      ;BRANCH ON FAILURE
    0732 2042
    0732 2043 :
    0732 2044 : MAKE SURE THAT THE CALLER HAS WRITE ACCESS TO THE LOGICAL NAME TABLE BEFORE
    0732 2045 : DELETING ALL THE ENTRIES THAT IT CONTAINS.
    0732 2046 :
```



```

00 E1 0732 2047
09 61 0732 2048 BBC #LNMT$V SHAREABLE, - ;IS THE TABLE PROCESS-PRIVATE?
52 02 9A 0734 2049 LNMTH$B FLAGS(R1),70$ ;IF SO THEN SKIP ACCESS CHECK
F8C4' 30 0736 2050 MOVZBL #WRITE ACCESS,R2 ;CODE FOR ACCESS CHECK
06 50 E9 0739 2051 BSBW LNMT$CHECK_PROT ;CHECK THE PROTECTION
073C 2052 BLBC R0,80$ ;QUIT ON FAILURE
073F 2053
52 55 D0 073F 2054 70$: MOVL R5,R2 ;ACCESS MODE
F8BB' 30 0742 2055 BSBW LNMT$DELETE_TAB ;DELETE ALL ENTRIES IN SPECIFIED TABLE
0745 2056
0745 2057 ;
0745 2058 ; UNLOCK THE LOGICAL NAME TABLE MUTEX AND RETURN STATUS TO CALLER.
0745 2059 ;
0745 2060
50 DD 0745 2061 80$: PUSHL R0 ;SAVE RETURN CODE OVER UNLOCKING
F8B6' 30 0747 2062 BSBW LNMT$UNLOCK ;UNLOCK TABLES
50 8ED0 074A 2063 POPL R0 ;RESTORE RETURN CODE
04 074D 2064 RET ;RETURN TO CALLER
074E 2065
074E 2066 .DISABLE LSB
074E 2067
074E 2068 ; .PAGE

```

```

074E 2070      .SBTTL EXESTRNLNM      - TRANSLATE LOGICAL NAME
074E 2071      :+
074E 2072      : EXESTRNLNM - TRANSLATE LOGICAL NAME
074E 2073      :
074E 2074      : THIS SERVICE PROVIDES THE CAPABILITY TO LOOKUP A LOGICAL NAME IN THE SPECIFIED
074E 2075      : LOGICAL NAME TABLE, AND TO RETURN INFORMATION ABOUT IT IN THE CALLER SPECIFIED
074E 2076      : ITEM LIST.
074E 2077      :
074E 2078      : INPUTS:
074E 2079      :
074E 2080      :     TRATTR(AP)      = ADDRESS OF LOGICAL NAME TRANSLATION ATTRIBUTES.
074E 2081      :     TRTABNAM(AP)   = ADDRESS OF TABLE NAME STRING DESCRIPTOR.
074E 2082      :     TRLOGNAM(AP)   = ADDRESS OF LOGICAL NAME STRING DESCRIPTOR.
074E 2083      :     TRACMODE(AP)    = ADDRESS OF ACCESS MODE.
074E 2084      :     TRITMLST(AP)   = ADDRESS OF ITEM LIST.
074E 2085      :
074E 2086      :     R4 = CURRENT PROCESS PCB ADDRESS.
074E 2087      :
074E 2088      : OUTPUTS:
074E 2089      :
074E 2090      :     R0 LOW BIT CLEAR INDICATES FAILURE TO TRANSLATE LOGICAL NAME.
074E 2091      :
074E 2092      :     R0 = SS$ ACCVIO - LOGICAL NAME DESCRIPTOR, LOGICAL NAME STRING,
074E 2093      :     TABLE NAME DESCRIPTOR, TABLE NAME STRING, AN ITEM IN THE
074E 2094      :     ITEM LIST, AN INDEX ITEM BUFFER CANNOT BE READ BY
074E 2095      :     CALLING ACCESS MODE. A TABLE ITEM BUFFER, A TABLE ITEM
074E 2096      :     SIZE BUFFER, AN ATTRIBUTES ITEM BUFFER, AN ATTRIBUTES
074E 2097      :     ITEM SIZE BUFFER, A STRING ITEM BUFFER, A STRING ITEM
074E 2098      :     SIZE BUFFER, A LENGTH ITEM BUFFER, A LENGTH ITEM SIZE
074E 2099      :     BUFFER, AN ACMODE ITEM BUFFER, AN ACMODE ITEM SIZE
074E 2100      :     BUFFER CANNOT BE WRITTEN BY CALLING ACCESS MODE.
074E 2101      :
074E 2102      :     R0 = SS$ BADPARAM - INVALID ATTRIBUTE, ACCESS MODE, ITEM TYPE,
074E 2103      :     ITEM LENGTH, SPECIFIED. LOGICAL NAME DESCRIPTOR OR
074E 2104      :     TABLE NAME DESCRIPTOR NOT SPECIFIED.
074E 2105      :
074E 2106      :     R0 = SS$ IVLOGNAM - ZERO OR GREATER THAN MAXIMUM LENGTH
074E 2107      :     LOGICAL OR TABLE NAME STRING SPECIFIED.
074E 2108      :
074E 2109      :     R0 = SS$ _IVLOGTAB - INVALID TABLE NAME SPECIFIED.
074E 2110      :
074E 2111      :     R0 = SS$ NOLOGNAM - LOGICAL TABLE NAME ENTRY SPECIFIED DOES NOT
074E 2112      :     EXIST.
074E 2113      :
074E 2114      :     R0 = SS$ NOPRIV - PROCESS DOES NOT HAVE PRIVILEGE TO ACCESS
074E 2115      :     THE SPECIFIED LOGICAL NAME TABLE ENTRY.
074E 2116      :
074E 2117      :     R0 = SS$ TOOMANYLNM - TOO MANY LEVELS OF RECURSION IN SEARCH
074E 2118      :     FOR LOGICAL NAME TABLE.
074E 2119      :
074E 2120      :     R0 LOW BIT SET INDICATES SUCCESSFUL COMPLETION.
074E 2121      :
074E 2122      :     R0 = SS$ BUFFEROVF - REQUEST SUCCESSFULLY COMPLETED. AN ITEM
074E 2123      :     BUFFER IS NOT LARGE ENOUGH TO HOLD REQUESTED DATA.
074E 2124      :
074E 2125      :     R0 = SS$ _NORMAL - NORMAL COMPLETION.
074E 2126      :

```



```
074E 2127 : SIDE EFFECTS:
074E 2128 :
074E 2129 : THIS ROUTINE EXITS AT IPL 2.
074E 2130 :
074E 2131 :-
074E 2132 :
0000000F 2133 .PSECT Y$EXEPAGED
0742' 07FC 000F 2134 .ENTRY EXESTRNLNM, ^M<R2,R3,R4,R5,R6,R7,R8,R9,R10,R11>
31 0011 2135 BRW EXESTRNLNM
0014 2136
0000074E 2137 .PSECT YF$$SLNM
074E 2138 .ENABLE LSB
50 0C 3C 074E 2139 900$: MOVZWL #SS$_ACCVIO,R0 ;ACCESS VIOLATION
04 0751 2140 RET
50 14 3C 0752 2141 910$: MOVZWL #SS$_BADPARAM,R0 ;BAD SYSTEM SERVICE PARAMETER
04 0755 2142 920$: RET
0756 2143
0756 2144 EXESTRNLNM:
0756 2145
0756 2146 :
0756 2147 : VALIDATE AND COPY PARAMETERS AS NECESSARY. REGISTER ASSIGNMENT FOR THE
0756 2148 : PARAMETERS ARE AS FOLLOWS:
0756 2149 :
0756 2150 : R5 = ACCESS MODE.
0756 2151 : R7 = ATTRIBUTE BITS.
0756 2152 : R9 = ADDRESS OF PROBED AND COPIED TABLE NAME DESCRIPTOR.
0756 2153 : R10 = ADDRESS OF PROBED AND COPIED LOGICAL NAME DESCRIPTOR.
0756 2154 : R11 = ADDRESS OF START OF THE ITEM LIST.
0756 2155 :
0756 2156 :---
0756 2157
7E D4 0756 2158 CLRL -(SP) ;THIS WILL EVENTUALLY BE CHAIN COUNTER
0758 2159
57 04 AC D0 0758 2160 MOVL TRATTR(AP),R7 ;TRANSLATION ATTRIBUTES
12 13 075C 2161 BEQL 10$ ;ERROR IF NOT PRESENT
075E 2162 IFNORD #4,(R7),900$ ;CHECK ACCESS
57 57 67 D0 0764 2163 MOVL (R7),R7 ;GET VALUE
57 FFFFFFFF 8F D3 0767 2164 BITL #^C<- ;CASE SENSITIVE VS. CASE INSENSITIVE
076E 2165 LNMSM_CASE_BLIND -
076E 2166 >,R7
076E 2167 BNEQ 910$ ;INVALID TRANSLATION ATTRIBUTES
0770 2168
5A 0C AC D0 0770 2169 10$: MOVL TRLOGNAM(AP),R10 ;ADDRESS OF LOGICAL NAME DESCRIPTOR
DC 13 0774 2170 BEQL 910$ ;ERROR IF NOT PRESENT
0776 2171 IFNORD #8,(R10),900$ ;CHECK ACCESS TO DESCRIPTOR
50 6A 7E 077C 2172 MOVAQ (R10),R0 ;ADDRESS OF DESCRIPTOR
F87E' 30 077F 2173 BSBW LNMS$PROBER ;PROBE LOGICAL NAME STRING
DO 50 E9 0782 2174 BLBC R0,920$ ;BRANCH IF CAN'T READ OR NOT PRESENT
7E 51 7D 0785 2175 MOVQ R1,-(SP) ;SAVE LOGICAL NAME DESCRIPTOR
5A 5E D0 0788 2176 MOVL SP,R10 ;ADDRESS OF LOGICAL NAME DESCRIPTOR
078B 2177
59 08 AC D0 078B 2178 MOVL TRTABNAM(AP),R9 ;ADDRESS OF TABLE NAME DESCRIPTOR
C1 13 078F 2179 BEQL 910$ ;ERROR IF NOT PRESENT
0791 2180 IFNORD #8,(R9),900$ ;CHECK ACCESS TO DESCRIPTOR
50 69 7E 0797 2181 MOVAQ (R9),R0 ;ADDRESS OF DESCRIPTOR
F863' 30 079A 2182 BSBW LNMS$PROBER ;PROBE TABLE NAME STRING
B5 50 E9 079D 2183 BLBC R0,920$ ;BRANCH IF CAN'T READ OR NOT PRESENT
```

```

7E 51 7D 07A0 2184      MOVQ   R1,-(SP)      ;SAVE TABLE NAME DESCRIPTOR
59 5E D0 07A3 2185      MOVL    SP,R9        ;ADDRESS OF TABLE NAME DESCRIPTOR
                    07A6 2186
50 55 03 9A 07A6 2187      MOVZBL #PSL$C_USER,R5      ;DEFAULT IS USER MODE(ALL ACCESS)
10 AC D0 07A9 2188      MOVL    TRACMODE(AP),R0      ;GET SPECIFIED ACCESS MODE
OE 13 07AD 2189      BEQL     2000$      ;BRANCH IF NOT PRESENT
                    07AF 2190      IFNORD #1,(R0),900$      ;CHECK ACCESS
55 60 9A 07B5 2191      MOVZBL (R0),R5      ;DETERMINE ACCESS MODE OF LOGICAL NAME
55 03 D1 07B8 2192      CML     #PSL$C_USER,R5      ;INVALID ACCESS MODE?
95 1F 07BB 2193      BLSSU    910$      ;RETURN ERROR IF THIS IS THE CASE
                    07BD 2194
                    07BD 2195
                    07BD 2196      : RAISE IPL TO AST DELIVERY LEVEL SO THAT THERE ARE NO INTERRUPTIONS WHILE THE
                    07BD 2197      : TRANSLATION OF THE LOGICAL NAME IS BEING CARRIED OUT, LOCK THE LOGICAL NAME
                    07BD 2198      : MUTEX FOR READING, AND THEN SEARCH FOR THE SPECIFIED LOGICAL NAME.
                    07BD 2199
                    07BD 2200
                    07BD 2201 2000$: SETIPL S^#IPL$ ASTDEL      ;RAISE TO AST DELIVERY LEVEL
54 30 07C0 2202      BSBW     LNMSLOCKR      ;LOCK TABLES FOR READING
54 DD 07C3 2203      PUSHL    R4      ;SAVE PCB ADDRESS
                    07C5 2204
50 6A 7D 07C5 2205      MOVQ     (R10),R0      ;LOGICAL NAME DESCRIPTOR
52 69 7D 07C8 2206      MOVQ     (R9),R2      ;TABLE NAME DESCRIPTOR
04 57 19 E1 07CB 2207      BBC     #LNMS$V_CASE_BLIND,R7,2010$ ;CASE INSENSITIVE SEARCH?
00 55 08 E2 07CF 2208      BBSS     #8,R5,2010$      ;YES - SET CORRESPONDING BIT
                    07D3 2209
                    07D3 2210 2010$:
00000000 00000002 07D3 2211      .IF NE CAS$ MEASURE      ;CHECK FOR MEASUREMENT ENABLED
00000000 EF D6 07D3 2212      INCL     L^PMSS$GL_LOGNAM      ;IF YES COUNT CURRENT TRANSLATION
                    07D9 2213
                    07D9 2214      .ENDC
                    07D9 2215
54 30 07D9 2215      BSBW     LNMS$SEARCHLOG      ;SEARCH FOR JUST SUCH A LOGICAL NAME
50 DD 07DC 2216      PUSHL    R0      ;SAVE THE SEARCH STATUS
23 50 E9 07DE 2217      BLBC     R0,3020$      ;BRANCH IF NO NAME FOUND
                    07E1 2218
                    07E1 2219
                    07E1 2220      : CHECK THE CALLER'S ACCESS TO THE LOGICAL TABLE THAT HAS BEEN FOUND TO CONTAIN
                    07E1 2221      : THE SPECIFIED LOGICAL NAME. NOTE THAT ACCESS CHECKING IS NOT REQUIRED IF THE
                    07E1 2222      : LOGICAL NAME IS A PROCESS-PRIVATE LOGICAL NAME.
                    07E1 2223
                    07E1 2224
16 58 51 D0 07E1 2225      MOVL     R1,R8      ;ADDRESS OF LOGICAL NAME BLOCK
51 1F E1 07E4 2226      BBC     #31,R1,3010$      ;SKIP ACCESS CHECK IF PROCESS-PRIVATE
52 01 D0 07E8 2227      MOVL     #READ_ACCESS,R2      ;CODE FOR ACCESS CHECK
54 04 AE D0 07EB 2228      MOVL     4(SP),R4      ;RESTORE PCB ADDR
51 0C A8 D0 07EF 2229      MOVL     LNMB$ TABLE(R8),R1      ;ADDRESS OF TABLE HEADER
                    F80A' 30 07F3 2230      BSBW     LNMS$CHECK_PROT      ;CHECK THE PROTECTION
                    05 50 E8 07F6 2231      BLBS     R0,3010$      ;CONTINUE IF OKAY
6E 50 D0 07F9 2232      MOVL     R0,(SP)      ;SAVE ERROR STATUS
                    06 11 07FC 2233      BRB      3020$      ;AND EXIT
                    07FE 2234
                    07FE 2235
                    07FE 2236      : PROCESS THE ITEM LIST RETURNING WHAT INFORMATION THE CALLER WANTS INTO THE
                    07FE 2237      : SPECIFIED ITEM BUFFERS.
                    07FE 2238
                    07FE 2239      : VALID ITEMS ARE:
                    07FE 2240      : ACMODE - ACCESS MODE OF LOGICAL NAME TABLE ENTRY.

```



```
07FE 2241 : ATTRIBUTES - ATTRIBUTES OF LOGICAL NAME AND CURRENT TRANSLATION.
07FE 2242 : INDEX - INDEX OF TRANSLATION (INPUT ITEM).
07FE 2243 : LENGTH - LENGTH OF CURRENT TRANSLATION STRING.
07FE 2244 : MAX INDEX - MAXIMUM INDEX IN LOGICAL NAME TABLE ENTRY.
07FE 2245 : STRING - TRANSLATION STRING.
07FE 2246 : TABLE - LOGICAL NAME TABLE NAME STRING.
07FE 2247 : PARENT - PARENT LOGICAL NAME TABLE NAME STRING.
07FE 2248 :
07FE 2249 :
07FE 2250 : REGISTER USAGE IS AS FOLLOWS:
07FE 2251 :
07FE 2252 : R6 = CURRENT TRANSLATION INDEX.
07FE 2253 : R7 = ADDRESS OF FIRST LOGICAL NAME TRANSLATION BLOCK
07FE 2254 : R8 = ADDRESS OF LOGICAL NAME TABLE ENTRY.
07FE 2255 : R9 = ADDRESS OF CURRENT LOGICAL NAME TRANSLATION BLOCK.
07FE 2256 : R11 = ADDRESS OF CURRENT ITEM IN ITEM LIST.
07FE 2257 :
07FE 2258 :
5B 14 AC D0 07FE 2259 3010$: MOVL TRITMLST(AP),R11 :ADDRESS OF ITEM LIST
03 12 0802 2260 :BNEQ 3030$ :PROCESS ITEM LIST IF THERE IS ONE
01F1 31 0804 2261 3020$: BRW 4010$ :BRANCH IF NONE
0807 2262 :
50 11 A8 9A 0807 2263 3030$: MOVZBL LNMB$T_NAME(R8),R0 :SIZE OF LOGICAL NAME STRING
59 12 A840 9E 080B 2264 :MOVAB LNMB$T_NAME+1(R8)[R0],R9 :ADDRESS OF FIRST TRANSLATION BLOCK
57 59 D0 0810 2265 :MOVL R9,R7 :SAVE THIS ADDRESS
56 D4 0813 2266 :CLRL R6 :DEFAULT INDEX IS 0
02 E0 0815 2267 3035$: BBS #LNMX$V_XEND,- :LAST TRANSLATION BLOCK?
10 69 0817 2268 :LNMX$B_FLAGS(R9),3038$ :YES - THEN POSITION TO GET ITEM
01 A9 95 0819 2269 :LNMX$B_INDEX(R9) :POSITION TO (OR PAST) 0 LNMX?
0B 18 081C 2270 :3038$ :YES - THEN POSITION TO GET ITEM
50 04 A9 9A 081E 2271 :MOVZBL LNMX$T_XLATION(R9),R0 :SIZE OF TRANSLATION STRING
59 05 A940 9E 0822 2272 :MOVAB LNMX$T_XLATION+1(R9)[R0],R9 :POSITION TO NEXT TRANSLATION BLOCK
EC 11 0827 2273 :BRB 3035$ :CONTINUE LOOKING FOR SPECIFIED LNMX
0829 2274 3038$: IFNORD #4,(R11),3060$ :CHECK IF FIRST LONGWORD READABLE
082F 2275 3040$:
52 02 AB 3C 082F 2276 :MOVZWL 2(R11),R2 :GET ITEM TYPE
CF 13 0833 2277 :BEQL 3020$ :DONE IF ITEM TYPE IS ZERO
0835 2278 :IFNORD #12,4(R11),3060$ :CHECK REST OF THIS DESCRIPTOR
083C 2279 :PLUS FIRST LONGWORD OF NEXT ONE
083C 2280 :
083C 2281 :CASE R2,<- :HANDLE EACH ITEM TYPE SEPARATELY
083C 2282 :3100$, - :INDEX ITEM
083C 2283 :3200$, - :STRING ITEM
083C 2284 :3300$, - :ATTRIBUTES ITEM
083C 2285 :3400$, - :TABLE ITEM
083C 2286 :3500$, - :LENGTH ITEM
083C 2287 :3600$, - :ACMODE ITEM
083C 2288 :3700$, - :MAX INDEX ITEM
083C 2289 :3800$, - :PARENT ITEM
083C 2290 :>W,#1
FFFF 8F 52 B1 0850 2291 :CMPW R2,#^XLNMS_CHAIN :CHECK FOR CHAINED ITEM LIST
06 13 0855 2292 :BEQL 3070$
019B 31 0857 2293 3050$: BRW 3980$ :ILLEGAL ITEM
0193 31 085A 2294 3060$: BRW 3970$ :ACCVIO
085D 2295 :
085D 2296 :
085D 2297 : PROCESS A CHAINED ITEM LIST.
```



```
0400 8F FC AD D6 085D 2298 :  
FC AD B1 085D 2299 :  
5B 04 EF 14 0860 2300 3070$: INCL -4(FP) ;UPDATE ITEM LIST CHAIN COUNTER  
BB CO 11 0860 2301 CMPW -4(FP),#1024  
0866 2302 BGTR 3050$ ;TOO MANY - ASSUME LOOP  
0868 2303 MOVL 4(R11),R11 ;GET POINTER  
086C 2304 BRB 3038$ ;GO PROCESS IT  
086E 2305  
086E 2306 :  
086E 2307 : INDEX ITEM.  
086E 2308 :  
086E 2309 : VALIDATE THE ITEM. POSITION TO THE TRANSLATION BLOCK WITH THE SAME  
086E 2310 : OR A GREATER INDEX THEN THAT SPECIFIED BY THE ITEM.  
086E 2311 :  
086E 2312 :  
6B 04 B1 086E 2313 3100$: CMPW #4,(R11) ;IS ITEM BUFFER AT LEAST A LONGWORD?  
E4 1A 0871 2314 BGTRU 3050$ ;ERROR IF NOT  
56 04 AB D0 0873 2315 MOVL 4(R11),R6 ;PICK UP THE ITEM BUFFER ADDRESS  
0877 2316 IFNORD (R11),(R6),3060$ ;PROBE IT FOR READABILITY  
56 66 F6 087D 2317 CCTLB (R6),R6 ;IS THE INDEX BETWEEN -127 AND 127?  
D5 1D 0880 2318 BVS 3050$ ;NO - INVALID INDEX ITEM  
56 56 9A 0882 2319 MOVZBL R6,R6 ;ZERO OUT HIGH ORDER THREE BYTES  
59 57 D0 0885 2320 MOVL R7,R9 ;ADDRESS OF FIRST TRANSLATION BLOCK  
0888 2321  
0888 2322 3110$: BBS #LNMX$V XEND,- ;LAST TRANSLATION BLOCK?  
11 69 088A 2323 LNMX$B_FLAGS(R9),3120$ ;YES - THEN POSITION TO NEXT ITEM  
01 A9 56 91 088C 2324 R6,LNMX$B_INDEX(R9) ;POSITION TO (OR PAST) REQUESTED LNMX?  
08 15 0890 2325 BLEQ 3120$ ;YES - THEN POSITION TO NEXT ITEM  
50 04 A9 9A 0892 2326 MOVZBL LNMX$T_XLATION(R9),R0 ;SIZE OF TRANSLATION STRING  
59 05 A940 9E 0896 2327 MOVAB LNMX$T_XLATION+1(R9)[R0],R9 ;POSITION TO NEXT TRANSLATION BLOCK  
EB 11 089B 2328 BRB 3110$ ;CONTINUE LOOKING FOR SPECIFIED LNMX  
014A 31 089D 2329 3120$: BRW 3960$ ;GO POSITION TO NEXT ITEM  
08A0 2330  
08A0 2331 :  
08A0 2332 : STRING ITEM.  
08A0 2333 :  
08A0 2334 : VALIDATE THE ITEM. IF THE CURRENT TRANSLATION BLOCK IS THE LAST  
08A0 2335 : TRANSLATION BLOCK, OR IF THE INDEX OF THE CURRENT TRANSLATION BLOCK  
08A0 2336 : DOES NOT MATCH THE INDEX LAST SPECIFIED, THEN NOTHING IS RETURNED  
08A0 2337 : (A ZERO IS STORED IN THE RETURN ADDRESS LENGTH BUFFER). OTHERWISE,  
08A0 2338 : THE EQUIVALENCE STRING OF THE SPECIFIED TRANSLATION IS RETURNED.  
08A0 2339 :  
08A0 2340 :  
50 7C 08A0 2341 3200$: CLRQ R0 ;ASSUME 0 BYTES WILL BE RETURNED  
02 E0 08A2 2342 BBS #LNMX$V XEND,- ;POSITION TO LAST LNMX?  
01 A9 OD 69 08A4 2343 LNMX$B_FLAGS(R9),3210$ ;YES - 0 BYTES WILL BE RETURNED  
56 91 08A6 2344 CMPB R6,LNMX$B_INDEX(R9) ;POSITIONED TO SPECIFIED LNMX?  
07 12 08AA 2345 BNEQ 3210$ ;NO - 0 BYTES WILL BE RETURNED  
08AC 2346  
51 04 A9 9E 08AC 2347 MOVAB LNMX$T_XLATION(R9),R1 ;RETRIEVE ADDRESS AND SIZE OF  
50 81 90 08B0 2348 MOVB (R1)+,R0 ;TRANSLATION STRING  
00BF 31 08B3 2349 3210$: BRW 3900$ ;GO MOVE STRING INTO CURRENT ITEM  
08B6 2350  
08B6 2351 :  
08B6 2352 : ATTRIBUTES ITEM.  
08B6 2353 :  
08B6 2354 : VALIDATE THE ITEM. THE ATTRIBUTES OF THE LOGICAL NAME BLOCK ARE
```



```

08B6 2355 : ALWAYS RETURNED. IF A TRANSLATION WITH THE CURRENT INDEX EXISTS
08B6 2356 : THEN THE TRANSLATION ATTRIBUTES ARE RETURNED AND LNMSV_EXIST IS SET.
08B6 2357 :
08B6 2358 :
52 10 A8 9A 08B6 2359 3300$: MOVZBL LNMSB_FLAGS(R8),R2 ;LOGICAL NAME BLOCK FLAGS
02 E0 08BA 2360 BBS #LNMSV_XEND,- ;POSITION TO LAST LNMX?
17 69 08BC 2361 LNMSB_FLAGS(R9),3310$ ;YES - TRANSLATION DOES NOT EXIST
01 A9 56 91 08BE 2362 CMPB R6,LNMSB_INDEX(R9) ;POSITIONED TO SPECIFIED LNMX?
11 12 08C2 2363 BNEQ 3310$ ;NO - TRANSLATION DOES NOT EXIST
08C4 2364 :
50 50 69 9A 08C4 2365 MOVZBL LNMSB_FLAGS(R9),R0 ;TRANSLATION BLOCK FLAGS
50 50 08 9C 08C7 2366 ROTL #8,R0,R0 ;ROTATE THEM INTO THEIR PROPER PLACE
52 52 50 C8 08CB 2367 BISL2 R0,R2 ;STORE THEM
00000400 8F C8 08CE 2368 BISL2 #LNMSM_EXISTS,R2 ;SET THE TRANSLATION DOES EXIST BIT
51 0C A8 D0 08D5 2369 :
00 E1 08D9 2370 3310$: MOVL LNMSL_TABLE(R8),R1 ;GET CONTAINING TABLE HEADER ADDRESS
07 61 08DB 2371 BBC #LNMSH_V_SHAREABLE,- ;IS THE CONTAINING TABLE SHAREABLE?
52 00010000 8F C8 08DD 2372 LNMSH_FLAGS(R1),3320$ ;GO MOVE ATTRIBUTES IF NOT
00E2 31 08E4 2373 3320$: BISL2 #LNMSM_SHAREABLE,R2 ;SET SHAREABLE BIT
08E7 2374 BRW 3940$ ;GO MOVE ATTRIBUTES INTO CURRENT ITEM
08E7 2375 :
08E7 2376 :
08E7 2377 : TABLE ITEM.
08E7 2378 :
08E7 2379 : VALIDATE THE ITEM. RETURN THE TABLE NAME STRING OF THE LOGICAL
08E7 2380 : NAME TABLE IN WHICH THIS LOGICAL NAME TABLE ENTRY IS FOUND.
08E7 2381 :
08E7 2382 :
51 0C A8 D0 08E7 2383 3400$: MOVL LNMSL_TABLE(R8),R1 ;ADDRESS OF TABLE HEADER
51 09 A1 D0 08EB 2384 MOVL LNMSH_NAME(R1),R1 ;ADDRESS OF TABLE LNMB
51 11 A1 9E 08EF 2385 MOVAB LNMBST_NAME(R1),R1 ;RETRIEVE ADDRESS AND SIZE OF
50 81 9A 08F3 2386 MOVZBL (R1)+,R0 ;TABLE NAME
007C 31 08F6 2387 BRW 3900$ ;GO MOVE TABLE INTO CURRENT ITEM
08F9 2388 :
08F9 2389 :
08F9 2390 : LENGTH ITEM.
08F9 2391 :
08F9 2392 : VALIDATE THE ITEM. IF THE CURRENT TRANSLATION BLOCK IS THE LAST
08F9 2393 : TRANSLATION BLOCK, OR IF THE INDEX OF THE CURRENT TRANSLATION
08F9 2394 : BLOCK DOES NOT MATCH THE INDEX LAST SPECIFIED, THEN NOTHING IS
08F9 2395 : RETURNED (A ZERO IS STORED IN THE RETURN ADDRESS LENGTH BUFFER).
08F9 2396 : OTHERWISE, THE LENGTH OF THE TRANSLATION STRING OF THE SPECIFIED
08F9 2397 : TRANSLATION IS RETURNED.
08F9 2398 :
08F9 2399 :
52 D4 08F9 2400 3500$: CLRL R2 ;ASSUME 0 BYTES WILL BE RETURNED
08FB 2401 :
02 E0 08FB 2402 BBS #LNMSV_XEND,- ;POSITION TO LAST LNMX?
0A 69 08FD 2403 LNMSB_FLAGS(R9),3510$ ;YES - GO RETURN 0 LENGTH
01 A9 56 91 08FF 2404 CMPB R6,LNMSB_INDEX(R9) ;POSITIONED TO SPECIFIED LNMX?
04 12 0903 2405 BNEQ 3510$ ;NO - GO RETURN 0 LENGTH
52 04 A9 9A 0905 2406 MOVZBL LNMSH_XLATION(R9),R2 ;LENGTH OF TRANSLATION STRING
00BD 31 0909 2407 3510$: BRW 3940$ ;MOVE LONGWORD ITEM VALUE
00E6 31 090C 2408 3520$: BRW 3980$ ;BADPARAM
090F 2409 :
090F 2410 :
090F 2411 : ACMODE ITEM.

```



```

090F 2412 :
090F 2413 : VALIDATE THE ITEM. RETURN THE ACCESS MODE OF THE LOGICAL NAME TABLE
090F 2414 : ENTRY.
090F 2415 :
090F 2416 :
6B 01 B1 090F 2417 3600$: CMPW #1,(R11) ;IS ITEM BUFFER AT LEAST A BYTE?
F8 1A 0912 2418 BGTRU 3520$ ;ERROR IF NOT
0914 2419 :
50 04 AB D0 0914 2420 MOVL 4(R11),R0 ;RETRIEVE ADDRESS OF ITEM BUFFER
0918 2421 IFNOWRT #1,(R0),3620$ ;PROBE ITEM BUFFER
60 08 AB 90 091E 2422 MOVW LNMB$B_ACMODE(R8),(R0) ;RETURN ACMODE IN CURRENT ITEM
50 08 AB D0 0922 2423 MOVL 8(R11),R0 ;WAS A RETURN LENGTH BUFFER SPECIFIED?
09 13 0926 2424 BEQL 3610$ ;DON'T RETURN LENGTH IF ONE WASN'T
0928 2425 IFNOWRT #2,(R0),3620$ ;PROBE RETURN LENGTH BUFFER
60 01 B0 092E 2426 MOVW #1,(R0) ;MOVE IN NUMBER OF BYTES RETURNED
00B6 31 0931 2427 3610$: BRW 3960$ ;GO POSITION TO NEXT ITEM
00B9 31 0934 2428 3620$: BRW 3970$ ;ACCVIO
0937 2429 :
0937 2430 :
0937 2431 : MAX_INDEX ITEM.
0937 2432 :
0937 2433 : VALIDATE THE ITEM. RETURN THE MAXIMUM POSITIVE INDEX DEFINED FOR
0937 2434 : THE LOGICAL NAME TABLE ENTRY.
0937 2435 :
0937 2436 :
52 01 CE 0937 2437 3700$: MNEGL #1,R2 ;INITIALIZE MAX INDEX TO -1
51 57 D0 093A 2438 MOVL R7,R1 ;ADDRESS OF FIRST TRANSLATION BLOCK
093D 2439 :
093D 2440 3710$: BBS #LNMB$V_XEND,- ;POSITION TO LAST LNMB?
093F 2441 LNMB$B_FLAGS(R1),3720$ ;YES - HAVE FOUND MAXIMUM INDEX
52 0F 61 0941 2442 CVTBL LNMB$B_INDEX(R1),R2 ;NO - SAVE INDEX
50 01 A1 98 0945 2443 MOVZBL LNMB$T_XLATION(R1),R0 ;SIZE OF TRANSLATION STRING
51 05 A140 9E 0949 2444 MOVAB LNMB$T_XLATION+1(R1)(R0),R1 ;POSITION TO NEXT TRANSLATION BLOCK
ED 11 094E 2445 BRB 3710$ ;CONTINUE LOOKING FOR LAST LNMB
0950 2446 :
52 52 D5 0950 2447 3720$: TSTL R2 ;IS MAXIMUM INDEX A NEGATIVE NUMBER?
75 18 0952 2448 BGEQ 3940$ ;NO - GO RETURN MAXIMUM INDEX
52 01 CE 0954 2449 MNEGL #1,R2 ;YES - SET MAXIMUM INDEX TO -1
70 11 0957 2450 BRB 3940$ ;GO MOVE MAXIMUM INDEX INTO CURRENT ITEM
0959 2451 :
0959 2452 :
0959 2453 : PARENT TABLE ITEM.
0959 2454 :
0959 2455 : VALIDATE THE ITEM. IF THIS LNMB IS FOR A LOGICAL NAME TABLE, THEN RETURN
0959 2456 : THE TABLE NAME STRING OF THIS TABLE'S PARENT LOGICAL NAME TABLE; OTHERWISE,
0959 2457 : RETURN 0.
0959 2458 :
0959 2459 :
50 7C 0959 2450 3800$: CLRQ R0 ;ASSUME 0 BYTES WILL BE RETURNED
03 E1 095B 2461 BBC #LNMB$V_TABLE,- ;RETURN 0 BYTES IF THIS IS NOT A LNMB
15 10 AB 095D 2462 LNMB$B_FLAGS(R8),3900$ ;FOR A LOGICAL NAME TABLE
52 05 A7 9E 0960 2463 MOVAB LNMB$T_XLATION+1(R7),R2 ;POSITION TO TABLE HEADER
52 0D A2 D0 0964 2464 MOVL LNMB$C_PARENT(R2),R2 ;RETRIEVE PARENT TABLE HEADER ADDRESS
08 13 0968 2465 BEQL 3900$ ;RETURN 0 BYTES IF NO PARENT TABLE
51 09 A2 D0 096A 2466 MOVL LNMB$C_NAME(R2),R1 ;RETRIEVE PARENT LNMB ADDRESS
51 11 A1 9E 096E 2467 MOVAB LNMB$T_NAME(R1),R1 ;RETRIEVE ADDRESS AND SIZE OF
50 81 90 0972 2468 3810$: MOVW (R1)+,R0 ;PARENT TABLE NAME STRING

```



```

0975 2469
0975 2470 :
0975 2471 : THE CURRENT ITEM IS TO BE FILLED IN WITH A VARIABLE LENGTH CHARACTER STRING
0975 2472 : (TABLE, STRING, OR PARENT ITEM). IF THE ITEM BUFFER PROVIDED IS NOT
0975 2473 : SUFFICIENTLY LARGE TO CONTAIN ALL OF THE STRING, THEN THE RETURN STATUS IS
0975 2474 : CHANGED TO INDICATE THIS, AND AS MUCH OF THE INFORMATION AS CAN BE STORED IS
0975 2475 : RETURNED.
0975 2476 :
0975 2477 :
0975 2478 3900$: MOVQ R0, -(SP) ;SAVE CHARACTER STRING DESCRIPTOR
0975 2479 MOVQ (R11), -(SP) ;SAVE ITEM BUFFER DESCRIPTOR
0975 2480 MOVZWL (SP), R1 ;SIZE OF ITEM BUFFER
0975 2481 MOVL 4(SP), R0 ;ADDRESS OF ITEM BUFFER
0975 2482 CLRL R3 ;ACCESS MODE
0975 2483 JSB G^EXESPROBEW ;PROBE ITEM BUFFER
0975 2484 MOVQ (SP)+, R1 ;RESTORE ITEM BUFFER DESCRIPTOR
0975 2485 BLBS R0, 3910$ ;CONTINUE IF WRITEABLE
0975 2486 ADDL2 #8, SP ;REMOVE STRING DESCRIPTOR FROM STACK
0975 2487 MOVL R0, (SP) ;SAVE NEW STATUS
0975 2488 BRB 4010$ ;GO RELEASE MUTEX AND RETURN
0975 2489
0975 2490 3910$: MOVL (SP), R0 ;SIZE OF CHARACTER STRING TO BE RETURNED
0975 2491 BEQL 3930$ ;NOTHING TO RETURN IF SIZE IS 0
0975 2492 CMPW R0, R1 ;ENOUGH ROOM IN BUFFER?
0975 2493 BLEQU 3920$ ;YES - GO MOVE INFORMATION
0975 2494 MOVZWL #SS$ BUFFEROVF, 8(SP) ;NO - CHANGE STATUS TO BUFFER OVERFLOW
0975 2495 MOVZWL R1, R0 ;AND MOVE ONLY PART OF STRING
0975 2496
0975 2497 3920$: PUSHL R0 ;SAVE SIZE OF STRING TO BE MOVED
0975 2498 MOVC3 R0, 8(SP), (R2) ;MOVE THE CHARACTER STRING
0975 2499 POPL R0 ;RESTORE NUMBER OF BYTES MOVED
0975 2500
0975 2501 3930$: ADDL2 #8, SP ;REMOVE STRING DESCRIPTOR FROM STACK
0975 2502 MOVL 8(R11), R2 ;WAS A RETURN LENGTH BUFFER SPECIFIED?
0975 2503 BEQL 3960$ ;DON'T PROBE IF ONE WASN'T
0975 2504 IFNOWRT #2, (R2), 3970$ ;PROBE RETURN LENGTH BUFFER
0975 2505 MOVW R0, (R2) ;MOVE IN NUMBER OF BYTES RETURNED
0975 2506 BRB 3960$ ;GO POSITION TO NEXT ITEM
0975 2507
0975 2508 :
0975 2509 : THE CURRENT ITEM IS TO BE FILLED IN WITH A LONGWORD OF INFORMATION
0975 2510 : (LENGTH, MAX_INDEX, OR ATTRIBUTES ITEM).
0975 2511 :
0975 2512 :
0975 2513 3940$: CMPW #4, (R11) ;IS ITEM BUFFER AT LEAST A LONGWORD?
0975 2514 BGTRU 3980$ ;ERROR IF NOT
0975 2515 MOVL 4(R11), R0 ;RETRIEVE ADDRESS OF ITEM BUFFER
0975 2516 IFNOWRT #4, (R0), 3970$ ;PROBE ITEM BUFFER
0975 2517 MOVL R2, (R0) ;RETURN VALUE IN CURRENT ITEM
0975 2518 MOVL 8(R11), R0 ;HAS A RETURN LENGTH BUFFER SPECIFIED?
0975 2519 BEQL 3960$ ;DON'T RETURN LENGTH IF ONE WASN'T
0975 2520 IFNOWRT #2, (R0), 3970$ ;PROBE RETURN LENGTH BUFFER
0975 2521 MOVW #4, (R0) ;MOVE IN NUMBER OF BYTES RETURNED
0975 2522
0975 2523 :
0975 2524 : POSITION TO THE NEXT ITEM IN THE ITEM LIST.
0975 2525 :

```

|    |         |    |      |      |         |          |                     |  |   |
|----|---------|----|------|------|---------|----------|---------------------|--|---|
| 5B | OC      | CO | 09EA | 2526 |         |          |                     |  |   |
|    | FE3F    | 31 | 09EA | 2527 | 3960\$: | ADDL2    | #12,R11             |  | :POSITION TO NEXT ITEM  |
|    |         |    | 09ED | 2528 |         | BRW      | 3040\$              |  | :AND CONTINUE   |
| 6E | OC      | 3C | 09F0 | 2529 |         |          |                     |  |   |
|    | 03      | 11 | 09F0 | 2530 | 3970\$: | MOVZWL   | #SS\$,ACCVIO,(SP)   |  | :ACCESS VIOLATION   |
|    |         |    | 09F3 | 2531 |         | BRB      | 4010\$              |  | :DEALLOCATE NEW LNMB AND RETURN ERROR                         |
| 6E | 14      | 3C | 09F5 | 2532 |         |          |                     |  |   |
|    |         |    | 09F5 | 2533 | 3980\$: | MOVZWL   | #SS\$,BADPARAM,(SP) |  | :BAD PARAMETER SEEN   |
|    |         |    | 09F8 | 2534 |         |          |                     |  |   |
|    |         |    | 09F8 | 2535 |         |          |                     |  |   |
|    |         |    | 09F8 | 2536 |         |          |                     |  |   |
|    |         |    | 09F8 | 2537 | :       |          |                     |  | : RELEASE THE READ LOCK ON THE LOGICAL NAME MUTEX AND RETURN. |
|    |         |    | 09F8 | 2538 | :       |          |                     |  |   |
|    |         |    | 09F8 | 2539 | :       |          |                     |  |   |
| 54 | 04 AE   | DO | 09F8 | 2540 | 4010\$: | MOVL     | 4(SP),R4            |  | :ADDRESS OF PCB   |
|    | F601'   | 30 | 09FC | 2541 |         | BSBW     | LNMB\$UNLOCK        |  | :RELEASE LOCK ON LOGICAL NAME MUTEX                           |
|    | 50 8ED0 | 04 | 09FF | 2542 |         | POPL     | R0                  |  | :RESTORE RETURN STATUS  |
|    |         |    | 0A02 | 2543 |         | RET      |                     |  | :RETURN   |
|    |         |    | 0A03 | 2544 |         | .DISABLE | LSB                 |  |   |
|    |         |    | 0A03 | 2545 |         |          |                     |  |   |
|    |         |    | 0A03 | 2546 | :       | .PAGE    |                     |  |   |
|    |         |    | 0A03 | 2547 |         |          |                     |  |   |
|    |         |    | 0A03 | 2548 |         | .END     |                     |  |   |



SYSLNM  
Symbol table

- SYSTEM SERVICES TO MANIPULATE LOGICAL 16-SEP-1984 02:22:46 VAX/VMS Macro V04-00  
5-SEP-1984 03:54:58 [SYS.SRC]SYSLNM.MAR;1

Page 48  
(6)

```

ARMSM_DELETE = 00000008
ARMSM_EXECUTE = 00000004
ARMSM_READ = 00000001
ARMSM_WRITE = 00000002
CAS_MEASURE = 00000002
CNACMODE = 00000010
CNATTR = 00000004
CNITMLST = 00000014
CNLOGNAM = 0000000C
CNTABNAM = 00000008
CTACMODE = 00000020
CTATTR = 00000004
CTPARTAB = 0000001C
CTPROT = 00000014
CTQUOTA = 00000010
CTRESLEN = 0000000C
CTRESNAM = 00000008
CTTABNAM = 00000018
DELETE_ACCESS = 00000008
DNACMODE = 0000000C
DNLOGNAM = 00000008
DNTABNAM = 00000004
DYN$C_LNM = 00000040
EXESALOP1PROC ***** X 02
EXESALOPAGED ***** X 02
EXESCRELNM 00000005 RG 03
EXESCRELNT 00000000 RG 03
EXESDELLNM 0000000A RG 03
EXESLNM_SYNTAX_DAT ***** X 02
EXESMAXACMODE ***** X 02
EXESPROBEW ***** X 02
EXESPROBEW_DSC ***** X 02
EXESTRNLNM 0000000F RG 03
EXECRELNM 00000329 R 02
EXECRELNT 00000024 R 02
EXEDELNM 0000066F R 02
EXETRNLNM 00000756 R 02
HEXDIGITS 00000000 R 02
IPL$ ASTDEL = 00000002
LNMS$CHECK_PROT ***** X 02
LNMSC_TABNAMLEN = 0000001F
LNMS$DELBLK ***** X 02
LNMS$DELETE_LNMB ***** X 02
LNMS$DELETE_TAB ***** X 02
LNMS$FIRSTTAB ***** X 02
LNMS$INIT_PROT ***** X 02
LNMS$INSLGTAB ***** X 02
LNMS$LOCKR ***** X 02
LNMS$LOCKW ***** X 02
LNMSM_CASE_BLIND = 02000000
LNMSM_CONCEALED = 00000100
LNMSM_CONFINE = 00000002
LNMSM_CREATE_IF = 01000000
LNMSM_CRELOG = 00000004
LNMSM_EXISTS = 00000400
LNMSM_NO_ALIAS = 00000001
LNMSM_SHAREABLE = 00010000

```

```

LNMSM_TERMINAL = 00000200
LNMS$PROBER ***** X 02
LNMS$SEARCHLOG ***** X 02
LNMS$UNLOCK ***** X 02
LNMSV_CASE_BLIND = 00000019
LNMSV_CONFINE = 00000001
LNMSV_SHAREABLE = 00000010
LNMS_CHAIN = FFFFFFFF
LNMS_INDEX = 00000001
LNMS_LNMB_ADDR = 00000009
LNMSB$B_ACMODE = 0000000B
LNMSB$B_FLAGS = 00000010
LNMSB$B_TYPE = 0000000A
LNMSB$L_TABLE = 0000000C
LNMSB$M_NODELETE = 00000010
LNMSB$M_TABLE = 00000008
LNMSB$T_NAME = 00000011
LNMSB$V_CONFINE = 00000001
LNMSB$V_TABLE = 00000003
LNMSB$W_SIZE = 00000008
LNMT$B$B_FLAGS = 00000000
LNMT$B$K_LENGTH = 00000025
LNMT$B$L_BYTES = 00000021
LNMT$B$L_BYTESLM = 0000001D
LNMT$B$L_CHILD = 00000011
LNMT$B$L_HASH = 00000001
LNMT$B$L_NAME = 00000009
LNMT$B$L_ORB = 00000005
LNMT$B$L_PARENT = 0000000D
LNMT$B$L_QTABLE = 00000019
LNMT$B$L_SIBLING = 00000015
LNMT$B$V_DIRECTORY = 00000001
LNMT$B$V_SHAREABLE = 00000000
LNMX$B$B_FLAGS = 00000000
LNMX$B$B_INDEX = 00000001
LNMX$B$C_BACKPTR = FFFFFFFF81
LNMX$B$C_TABLE = FFFFFFFF82
LNMX$M_TERMINAL = 00000002
LNMX$M_XEND = 00000004
LNMX$T_XLATION = 00000004
LNMX$V_XEND = 00000002
LNMX$W_HASH = 00000002
LNMT_HEX_TAB_LEN = 00000014
ORB$C_LENGTH = 00000058
ORB$K_LENGTH = 00000058
PCBS$L_EPID = 00000064
PCBS$Q_PRIV = 00000084
PMS$GC_LOGNAM ***** X 02
PR$IPC = 00000012
PRV$V_SYSNAM = 00000002
PSL$C_USER = 00000003
PSL$M_PRIVMOD = 00C00000
QUOTA_ACCESS = 00000004
READ_ACCESS = 00000001
SS$ACC$VIO = 0000000C
SS$BADPARAM = 00000014
SS$BUFFEROVF = 00000601

```



SYSLNM  
Symbol table

- SYSTEM SERVICES TO MANIPULATE LOGICAL C 9  
16-SEP-1984 02:22:46 VAX/VMS Macro V04-00  
5-SEP-1984 03:54:58 [SYS.SRC]SYSLNM.MAR;1

Page 49  
(6)

SS\$\_EXLNMQUOTA = 0000224C  
SS\$\_INSFMEM = 00000124  
SS\$\_IVLOGNAM = 00000154  
SS\$\_IVLOGTAB = 0000015C  
SS\$\_NOLOGNAM = 000001BC  
SS\$\_NORMAL = 00000001  
SS\$\_RESULTOVF = 00000214  
SS\$\_SUPERSEDE = 00000631  
TRACMODE = 00000010  
TRATTR = 00000004  
TRITMLST = 00000014  
TRLOGNAM = 0000000C  
TRTABNAM = 00000008  
WRITE\_ACCESS = 00000002

+-----+  
! Psect synopsis !  
+-----+

| PSECT name  | Allocation        | PSECT No. | Attributes  |
|-------------|-------------------|-----------|---|
| . ABS .     | 00000000 ( 0.)    | 00 ( 0.)  | NOPIC USR CON ABS LCL NOSHR NOEXE NORD NOWRT NOVEC BYTE |
| \$AB\$\$    | 00000000 ( 0.)    | 01 ( 1.)  | NOPIC USR CON ABS LCL NOSHR EXE RD WRT NOVEC BYTE       |
| YF\$\$LNM   | 00000A03 ( 2563.) | 02 ( 2.)  | NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC BYTE       |
| Y\$EXEPAGED | 00000014 ( 20.)   | 03 ( 3.)  | NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC BYTE       |

+-----+  
! Performance indicators !  
+-----+

| Phase                  | Page faults | CPU Time    | Elapsed Time |
|------------------------|-------------|-------------|--------------|
| Initialization         | 30          | 00:00:00.07 | 00:00:00.34  |
| Command processing     | 106         | 00:00:00.55 | 00:00:01.48  |
| Pass 1                 | 403         | 00:00:15.02 | 00:00:31.49  |
| Symbol table sort      | 0           | 00:00:01.91 | 00:00:03.39  |
| Pass 2                 | 417         | 00:00:05.92 | 00:00:13.20  |
| Symbol table output    | 1           | 00:00:00.10 | 00:00:00.22  |
| Psect synopsis output  | 0           | 00:00:00.03 | 00:00:00.02  |
| Cross-reference output | 0           | 00:00:00.00 | 00:00:00.00  |
| Assembler run totals   | 959         | 00:00:23.60 | 00:00:50.15  |

The working set limit was 2100 pages.  
94360 bytes (185 pages) of virtual memory were used to buffer the intermediate code.  
There were 70 pages of symbol table space allocated to hold 1116 non-local and 159 local symbols.  
2548 source lines were read in Pass 1, producing 32 object records in Pass 2.  
25 pages of virtual memory were used to define 24 macros.



+-----+  
! Macro library statistics !  
+-----+

Macro library name

Macros defined

-----  
\$255\$DUA28:[SYS.OBJ]LIB.MLB;1  
\$255\$DUA28:[SYSLIB]STARLET.MLB;2  
TOTALS (all libraries)

-----  
11  
10  
21

1208 GETS were required to define 21 macros.

There were no errors, warnings or information messages.

MACRO/LIS=LIS\$:SYSLNM/OBJ=OBJ\$:SYSLNM MSRC\$:SYSLNM/UPDATE=(ENH\$:SYSLNM)+EXECMLS/LIB



0386 AH-BT13A-SE  
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION  
CONFIDENTIAL AND PROPRIETARY

